



Calhoun: The NPS Institutional Archive

DSpace Repository

Theses and Dissertations

1. Thesis and Dissertation Collection, all items

1989

A psychometric method for determining optimum

Shaw, Charles Houston

Monterey, California. Naval Postgraduate School

https://hdl.handle.net/10945/26188

Downloaded from NPS Archive: Calhoun



Calhoun is the Naval Postgraduate School's public access digital repository for research materials and institutional publications created by the NPS community. Calhoun is named for Professor of Mathematics Guy K. Calhoun, NPS's first appointed -- and published -- scholarly author.

> Dudley Knox Library / Naval Postgraduate School 411 Dyer Road / 1 University Circle Monterey, California USA 93943

http://www.nps.edu/library



يندلا درينا دراب

577 2 SOOR









NAVAL POSTGRADUATE SCHOOL Monterey, California



THE SIS 543723

A PSYCHOMETRIC METHOD FOR DETERMINING OPTIMUM, TACTICAL PATHS IN COMBAT DECISION MAKING AND ANALYSIS

by

Charles Houston Shaw, III

September 1989

Thesis Advisor

Samuel H. Parry

Approved for public release; distribution is unlimited





341.011

Unclassified

security classification of this page

			REPORT DOCU	MENTATION PAGE		
la Report Security Classification Unclassified				1b Restrictive Markings		
2a Securit	y Classification	Authority		3 Distribution Availability of Report	3 Distribution Availability of Report	
2b Declas	sification Down	grading Schedule		Approved for public release; distribution is unlimited.		
4 Perform	ing Organizatio	n Report Numberís)	5 Monitoring Organization Report Number(s)		
6a Name Naval P	of Performing C Ostgraduate S	Organization School	6b Office Symbol (<i>if applicable</i>) 55	7a Name of Monitoring Organization Naval Postgraduate School		
6c Address (city, state, and ZIP code) Monterey, CA 93943-5000				7b Address (city, state, and ZIP code) Monterey, CA 93943-5000		
8a Naine	of Funding Spor	nsoring Organization	n 8b Office Symbol (<i>if applicable</i>)	9 Procurement Instrument Identification Number		
8c Addres	s (city, state, an	d ZIP code)		10 Source of Funding Numbers		
				Program Element No Project No Task No Work Unit Accession No		
11 Title (1 PATHS	nclude security of IN COMBA	lassification) A PS AT DECISION	SYCHOMETRIC ME MAKING AND ANA	THOD FOR DETERMINING OPTI	MUM, TACTICAL	
12 Person	al Author(s) Cl	narles Houston S	Shaw, III			
13a Type of Report Master's Thesis From			ne Covered To	14 Date of Report (year, month, day) September 1989	15 Page Count 131	
16 Supple sition of	mentary Notatio the Departm	on The views exp nent of Defense	pressed in this thesis are or the U.S. Governmen	e those of the author and do not reflect nt.	the official policy or po-	
17 Cosati Codes 18 Subject Terms (continue o			Subject Terms (continue on	reverse if necessary and identify by block number	- 1	
Field	Group	Subgroup Ge	Generalized Value System (GVS), Condensed Army Mobility Management System (CAMMS), Tactical Movement Potential (TMP), Psyc			
19 Abstra This	ct (<i>continue on</i>) thesis exami	reverse if necessary on nes and demons	and identify by block number trates a methodology fi) or determining optimum, tactical move	ment paths for a specified	

This thesis examines and demonstrates a methodology for determining optimum, tactical movement paths for a specified vehicle and or small unit based on the operator's cognitive decision processes, as well as the physical effects of terrain and environment on mobility. The approach specifically uses psychometric techniques inherent to the Generalized Value System (GVS) in order to determine a "Power Function" based on the specific tactical scenario and given equipment configuration which provides a means to determine the Tactical Movement Potential (TMP) for each terrain cell. This cognitive value in an interval scale can then be translated into the same scale as the physical continuum using techniques proposed by L.L. Thurstone and W.S. Torgerson. The cognitive time value based on the user's decision process is then added to the physical traversal times for each cell computed from output provided by The Condensed Army Mobility Management System (CAMMS). This renders a value mapping which can be optimized using one of several existing algorithms. The Dijkstra Algorithm is used in this demonstration model. The resulting sets of path points are optimized for speed time and the cognitive tactical considerations evaluated using these psychometric methods thereby rendering a truly optimum, tactical movement path and optimum traversal time. The movement path and resulting times can be used in combat planning and modelling. This output is also particularly important in determining the time values needed to compute the Situationally Inherent Power (SIP) of the GVS. In actuality, this methodology could be applied to almost any tactical decision process in the development of expert systems and models.

20 Distribution Availability of Abstract Sunclassified unlimited same as report DTIC users	21 Abstract Security Classification Unclassified	
22a Name of Responsible Individual	22b Telephone (include Area code)	22c Office Symbol
Samuel H. Parry	(408) 646-2779	55Py

DD FORM 1473.84 MAR

83 APR edition may be used until exhausted All other editions are obsolete security classification of this page

Unclassified

T245555

Approved for public release; distribution is unlimited.

A Psychometric Method for Determining Optimum, Tactical Paths in Combat Decision Making and Analysis

by

Charles Houston Shaw, III Captain, United States Army B.S., United States Military Academy, 1979

Submitted in partial fulfillment of the requirements for the degree of

MASTER OF SCIENCE IN OPERATIONS RESEARCH

ABSTRACT

This thesis demonstrates a method to determine optimum, tactical movement paths for a specified vehicle and or small unit based on the operator's cognitive decision processes, as well as the physical effects of terrain and environment on mobility. The approach uses psychometric techniques inherent to the Generalized Value System (GVS) to determine a "Power Function" based on a specific tactical scenario and given equipment configuration and provides a means to determine the Tactical Movement Potential (TMP) for each terrain cell. This cognitive value in an interval scale can then be translated into the same scale as the physical continuum using techniques proposed by L.L. Thurstone and W.S. Torgerson. The cognitive time value based on the user's decision process is then added to the physical traversal times for each cell computed from output provided by The Condensed Army Mobility Management System (CAMMS). This renders a value mapping which can be optimized using one of several existing algorithms. The Dijkstra Algorithm is used in this demonstration model. The resulting sets of path points are optimized for speed time and the cognitive tactical considerations evaluated using these psychometric methods. The movement path and resulting times can be used in combat planning and modelling. This output is also particularly important in determining the time values needed to compute the Situationally Inherent Power (SIP) of the GVS. This methodology could be applied to almost any tactical decision process in the development of expert systems and models.



THESIS DISCLAIMER

The views expressed in this thesis are those of the author and do not reflect the official policy or position of the Department of Defense or the U.S. Government.

The reader is further cautioned that certain vehicle system input parameters used and portions of the computer program developed in this research are not valid for all scenarios of interest. While every effort has been made, within the time available, to verify all computer programs; they cannot be considered validated. Any application of the methodology using these programs is done so at the user's own risk.

TABLE OF CONTENTS

I.	IN	TRODUCTION					
	А.	GENERAL					
	B.	PROBLEM STATEMENT					
		1. Purpose					
		2. Scope					
		3. Assumptions					
H	B.	ACKGROUND					
	А.	PREVIOUS ROUTE SELECTION AND TACTICAL MOVEMENT MOD-					
	EL	<mark>.</mark> S					
		1. The Dynamic Tactical Simulation (DYNTACS) Model					
		2. The Simulation of Tactical Alternative Responses (STAR) Model 5					
		3. Other Route Selection Methodologies					
	В.	CURRENT MOBILITY MODELS					
		1. The Condensed Army Mobility Management System (CAMMS)7					
		a. Physical Considerations Affecting Mobility					
		b. CAMMS Output Mappings 8					
		c. Technology to the Field					
	C.	COGNITIVE CONSIDERATIONS IMPACTING ON MOVEMENT 8					
II	I. F	PSYCHOMETRICS AND PSYCHOPHYSICAL ANALYSIS IN THE GVS 10					
	А.	GENERAL					
	Β.	THE MEASUREMENT OF VALUES 11					
		1. Interval Scales					
		a. Continuous Response Scale Judgements					
		b. Comparative Judgements 12					
		c. Categorical Judgements 12					
	C.	THE EXPERIMENTAL DESIGN					
		1. Scenario Development					
		2. Survey Construction and Execution					
	D.	RELATING THE COGNITVE AND PHYSICAL CONTINUUMS 17					

	1.	Computing Interval Scales from Categorical Responses
	2.	Converting Interval Scales to Usable Forms
		a. The Natural Origin and Anchoring in Computing Interval Scales . 20
		b. The Linear Transformation
	3.	Regression Analysis of the Interval Scale Values
	4.	The Psychometric Power Function
	5.	Translating Values of the Interval Scale to the Physical Scale 21
IV	MODI	EL CONSTRUCTION
А.	GE?	NERAL
В.	TER	RAIN DATA BASES 23
C.	REQ	QUIRED INPUTS
D.	TH	E MOBILITY MODEL, CAMMS (VERSION 2.0)
E.	LIN	E-OF-SIGHT MODELS
F.	REL	ATIVE EFFECTIVE RANGE METHODOLOGIES
G.	APF	PLYING THE PSYCHOMETRIC FUNCTION
H.	TH	E OPTIMIZATION
	1.	Dijkstra´s Algorithm
	2.	Combinatorial Optimization
		a. Assumptions
		b. Methodology
		c. The Combinatorial Optimization Algorithm
		d. Conclusions
[.	MOI	DEL OUTPUT
V. C	ONCI	LUSIONS AND RECOMMENDATIONS
А.	GE?	NERAL
Β.	CO?	SCLUSIONS
	1.	Model Verification
	2.	Output Analysis
C.	REC	COMMENDATIONS
	1.	Enhancements and Areas for Research
		a. Approved Scenario List 39
		b. Expanded Survey and Regression Capability 39
		c. Multiple Vehicle Paths and Formation Structure 40

		d. Relative Effective Range Determinations 40
		e. Symmetric Applications
	2.	Methodology Utilization and Future Applications
		a. Tactical Decision Tool
		b. Tactical Training Tool 41
		c. Combat Model Preprocessor / Subroutine
		d. Research and Analysis Tool 41
		e. The Generalized Value System, GVS
D.	SU	
APPE	NDI	X A. A SURVEY OF FACTORS INFLUENCING TACTICAL
СОМ	[BA]	Г MOVEMENT
А.	1N	TRODUCTION
	1.	Purpose
	2.	Structure
		a. Key Variables 43
		b. Rating Categories 43
		c. Discussion
	3.	Instructions
Β.	PE	RSONAL HISTORY DATA
	1.	Present Rank:
	2.	Branch or MOS: 46
	3.	Experience:
	4.	Opinion:
C.	ΤA	CTICAL MOVEMENT SURVEY 47
	1.	OPORD 1-89, HQ TF 1-15 XXX
	2.	Example Survey Scenarios for Questions 34 through 41 48
APPE	NDI	X B. TRANSFORMING THE CATEGORICAL RESPONSES TO AN
INTE	ERV.	AL SCALE
А.	RA	W FREQUENCIES
В.	GR	ROUPED FREQUENCIES
C.	RE	ELATIVE FREQUENCIES
D.	CU	UMULATIVE RELATIVE FREQUENCIES
E.	E	XTREME INSTANCES

F. GROUPED CUMULATIVE RELATIVE FREQUENCY MATRICES 58
G. COMPUTER PROGRAMS USED
H. THE NORMALIZED AND TRANSFORMED VALUES OF THE IN-
STANCES
I. THE REGRESSION MATRIX
APPENDIX C. REGRESSION ANALYSIS OF COGNITIVE FACTORS AF-
FECTING MOVEMENT
A. SURFACE PLOTS
B. REGRESSION USING GRAFSTAT 82
C. REGRESSION USING SAS 86
1. THE FIRST SAS MULTIPLE REGRESSION
2. THE SECOND SAS MULTIPLE REGRESSION
APPENDIX D. COMBINATORIAL OPTIMIZATION PROGRAM USING
LAGRANGIAN RELAXATION
APPENDIX E. EXAMPLE MODEL OUTPUT
LIST OF REFERENCES 112
BIBLIOGRAPHY 114
INITIAL DISTRIBUTION LIST

LIST OF TABLES

Table	1.	TECHNICAL	DATA	FOR	MISSLE SYSTEM EQUATIONS	30
Table	2.	TECHNICAL	DATA	FOR	BALLISTIC SYSTEM EQUATIONS	31

LIST OF FIGURES

Figure	1.	Comparison of Relative Effective Range for Soviet MBT vs. ATGM 28
Figure	2.	Comparison of Relative Effective Range for U.S. MBT vs. 1FV 29
Figure	3.	Surface Plot of TMP Versus SPD and RNG for No LOS
Figure	4.	Surface Plot of TMP Versus SPD and RNG for 2-3 LOS
Figure	5.	Surface Plot of TMP Versus SPD and RNG for 4- LOS
Figure	6.	Surface Plot of TMP Versus SPD and RNG for All LOS
Figure	7.	Surface Plot of TMP Versus SPD and LOS for All RNG
Figure	8.	Surface Plot of TMP Versus RNG and LOS for All SPD
Figure	9.	Residual Analysis of the Four Variable Regression
Figure	10.	Residual Analysis of the Five Variable Regression
Figure	11.	CAMMS Output Mapping For Set 3 97
Figure	12.	TOP Output Mapping For Set 3
Figure	13.	CAMMS Output Mapping For Set 4
Figure	14.	TOP Output Mapping For Set 4 100
Figure	15.	CAMMS Output Mapping For Set 5 101
Figure	16.	TOP Output Mapping For Set 5 102
Figure	17.	CAMMS Output Mapping For Set 6 103
Figure	18.	TOP Output Mapping For Set 6 104
Figure	19.	CAMMS Output Mapping For Set 15 105
Figure	20,	TOP Output Mapping For Set 15 106
Figure	21.	TOP Mapping With A High Risk Averse Posture For Set 15 107
Figure	22.	CAMMS Output Mapping For Set 16 108
Figure	23.	TOP Output Mapping For Set 16 109
Figure	24.	TOP Mapping With A High Risk Averse Posture For Set 16 110
Figure	25.	TOP Mapping With An Extreme Risk Averse Posture For Set 16 111

ACKNOWLEDGEMENTS

I would like to express my deepest appreciation and heart-felt thanks to the following persons for their invaluable assistance and support in the preparation of this thesis.

- My wife, Suzanne, who gave me ten wonderful years. I'm sorry things didn't turn out better.
- My darling children: Yannah, Tanaiya, Heather, and Justin: who have suffered most from the trials and tribulations of the past two years. I hope I can make things up to you in the future.
- Dr. Sam Parry for his timely and conscientious guidance in more ways than one over the past year.
- Dr. Art Schoenstadt for his meticulous attention to detail and support as second reader.
- Mr. Terril C. Falls for his superb assistance in the coding and preparation of the model. A truly remarkable job T.C..
- The MSD Group at the WES: especially Dr. John Farr, Mr. Roger Meier, and Mr. Tommy Dean; who helped make this all possible.
- Drs. Marcuson and Hadala at the U.S. Geotechnical Laboratory for their interest and oversight in this project.
- The TRADOC Analysis Command, Monterey for their assistance, support, and facilities over the past year.

Thanks again for everything you've done. I wouldn't have finished without all of you.

I. INTRODUCTION

A. GENERAL

The ability to accurately portray the battlefield environment is a key requirement in combat model development. This same ability is required in the construction of tactical decision aids and tools. One major factor to be considered in any of these applications is the effect of terrain, vegetation, and weather on the mobility trafficability of weapons systems and units. Another major factor is the effect of these same parameters on visibility, detection, and acquisition by various weapons systems. While the preceding factors are objective for the most part and can be accurately measured; other factors are not so clearly defined and may possess large variances. This is certainly the case where a human decision process is required such as the decision logic used by various combat unit and vehicle commanders in tactical movement. A clear distinction must be made between mobility as modelled in relation to the physical constraints of the battlefield and movement which requires interaction with the user decision maker or must be modelled taking the pertinent cognitive considerations as well as the physical constraints of the battlefield into account.

In any case, all of these factors and more must be accounted for in our combat models and tactical decision tools. There are a number of existing high resolution combat models and tactical decision aids which incorporate many of these functions. Most of these packages use one of several available versions of digitized terrain data and either actual, historical, or user input weather data. Most combat models also incorporate appropriate tactical decision logic algorithms to control some key functions such as detection, acquisition, and other essential combat actions of player units. Some tactical decision tools also do this. However, at the present time there is no combat model or tactical decision tool which combines the appropriate decision logic to determine the optimum path a unit or vehicle should traverse in order to simultaneously maximize speed and trafficability, minimize inter-visibility and detection, and appropriately balance their effects in terms of the decision logic.

The need and desire of commanders and combat planners to have and use such tactical decision tools and to incorporate them into combat models is of definite benefit. Some commanders presently have a tactical decision aid in the form of the Army Mobility Model (AMM) and the Condensed Army Mobility Management System

1

(CAMMS) which provide trafficability, speed, and time contour mappings for use in route selection and other tactical decisions. There are also any number of combat models available for study where a commander or combat analyst can select appropriate terrain data bases and manually input desired unit or vehicle path points and or positions. This is the case with present JANUS based models, the Battalion Combat Outcome Model (BCOM), and others. However, there is no tactical decision tool or combat model that can systemically determine sets of optimum, tactical path points for the commander or for use in analysis. This is also true of almost all models where tactical decision processes are represented.

The first requirement in developing such a model is to properly identify those variables which could and or would affect the tactical movement or other decision process such as the mission, threat, corresponding locations, ranges to various threats, vehicular agility or localized speed, allowable completion time, and others. It is soon obvious that a large number of variables, many having probable interactions with other variables, exist. The possible combinations or instances is quite large and each variable may vary significantly between instances. Structuring this maze in order to be able to extract usable data on the cognitive process is no small task.

Another requirement is finding a theoretically sound method for evaluating large groups of variables simultaneously and then being able to compute a specific value which appropriately measures their combined effect on the process. This field of study has a name all its own. Psychophysics.

A third requirement is to find a theoretically sound method that allows for the mapping of these psychophysical values into an appropriate physical continuum so that they may be used concurrently with physical attributes and variables in the model. This field of study also has a name all its own, Psychometry.

The art of combining and applying these techniques is known as Psychometrics. We will use these techniques in conjunction with an existing mobility model, CAMMS (Version 2.0), to provide total movement time values based on physical engineering traversal times and the translated psychometric times for each terrain cell and subsequent traverse segment on the battlefield. These values will then be used as network cost values in a form of Dijkstra's Algorithm which renders the set of minimum cost optimum path points for that scenario.

The organization, purpose, scope, and assumptions of this research are explained in this Introduction. Background information on previous route selection methodologies, terrain representations, physical attributes of terrain considered in mobility, cognitive considerations which impact on movement, and the desire to place such technologies in the hands of the commander in the field is presented in Chapter II. The development of the "Psychometric Function" using psychometric procedures inherent to the Generalized Value System, GVS, is shown in Chapter III. Application of these techniques and construction of the model algorithm is detailed in Chapter IV. Results of the algorithm implementation on an AT-386 personal computer and limited verification of these results are presented in Chapter V. Proposed enhancements to the existing model and areas requiring additional study are presented in Chapter VI. Finally, Chapter VII discusses possible utilizations for this methodology and proposed applications with respect to tactical decision and training tools, research and analysis tools, combat models, and the Generalized Value System.

It is of significant interest to note that prominent Soviet military analysts. Nikita Moiseyev in particular, have proposed a model framework based on decision theoretic developments using such state variables and decision functions since the 1970's. Two specific areas discussed have been tactical decision processes and movement of the line of contact. [Ref. 1: pp. 21-26]

B. PROBLEM STATEMENT

1. Purpose

This thesis examines and demonstrates a methodology for determining optimum, tactical movement paths for a specified vehicle and or small unit based on the operator's cognitive decision processes, as well as the physical effects of terrain and environment on mobility. The resulting sets of path points are optimized for speed time and the cognitive tactical considerations evaluated using psychometric methods thereby rendering a truly optimum, tactical movement path and optimum traversal time. The movement path and resulting times are to be used in combat planning and modelling. This output is also particularly important in determing the time values needed to compute the Situationally Inherent Power (SIP) of the GVS.

2. Scope

This research will be limited to one specific scenario of interest in order to demonstrate the methodology without undue involvement in various scenarios with different sets of fixed state variables. The specific scenario used is discussed in detail in Chapter III. This research will not involve detailed studies of relative effective range used in the algorithm and discussed in Chapter IV. There will also not be any extensive verification and validation of the results of the computer application of the algorithm due to a lack of time and resources.

This research will examine the use of a movement model based on the methodology for a single vehicle unit of specified type and mission against a threat array of specified types performing a certain mission while in a selected area of operations and known terrain.

3. Assumptions

- 1. The mathematical forms of range dependency equations studied by Bonder and Farrell and used to portray perceived lethality as relative effective range curves related to those found in JANUS are correct.
- 2. The survey results, interval scales, and regression analysis are valid for the range of values surveyed only. However, these should encompass the vast majority of instances.
- 3. The translated cognitive time scale and traversal time scales are additive and not multiplicative.
- 4. This methodology is applicable to all types of tactical decision processes when the appropriate state variables can be identified.

II. BACKGROUND

A. PREVIOUS ROUTE SELECTION AND TACTICAL MOVEMENT MODELS

1. The Dynamic Tactical Simulation (DYNTACS) Model

The DYNTACS Model was developed by the Systems Research Group at Ohio State University from 1964 to 1969. The model is extremely high resolution in order to predict individual unit performance in armored combat engagements from both the design and operational perspectives [Ref. 2]. Dynamic programming is used to run and solve the simulation which consists of a driver program and 34 subroutines. At least 15 of these algorithms are related to or affect tactical movement in the model [Ref. 3]. An explicit surface terrain representation of the battlefield is used in order to determine plane departure points for a predetermined grid size [Ref. 3: pp. 57-66]. This representation is closely related to and can be derived from explicit grid terrain data available from a number of sources [Ref. 4: pp. 3.3-3.15].

The model determines an optimum route for an advancing element or unit by optimization where "Tactical Difficulty" is minimized. Tactical difficulty is computed using a heuristic of the form, TD = (1 + E)T, where E is the difficulty computed due to a set of factors along each route segment and T is the travel time for that segment [Ref. 3: pp. 94-116]. Such heuristic procedures are computationally efficient but do not guarantee an optimal solution. The set of factors and corresponding values for the difficulty, E, were obtained using comparative judgement techniques. Travel times are computed using engineering models for each weapon system. It is interesting to note that difficulty is a function of the effective range, actual range, and threat disposition [Ref. 3: pp. 97-100] and that psychometric methods similar to many we will examine were used to obtain these values. The major shortcoming with the DYNTACS approach is that the cognitive and physical scales are related multiplicatively using a heuristic due to existing computer limitations rather than developing a truly optimal technique.

2. The Simulation of Tactical Alternative Responses (STAR) Model

The STAR Model is similar to DYNTACS in most respects except that dynamic programming is discarded and the optimization is performed in FORTRAN applying Dijkstra's Algorithm. The additional concept of the "Sliding Pattern" is used to restrict the search for the path [Ref. 5: pp. 23-34]. The route selection is performed sequentially from start point, to a horizon or horizons, to an objective by sliding the optimization

along the network. Unfortunately, the identical heuristic equation found in DYNTACS is also applied in this model [Ref. 5: p. 33] rendering it suspect.

3. Other Route Selection Methodologies

There are any number of similar movement models proposed over the past 25 years and certainly all of them cannot be mentioned. However, it is necessary to introduce another type of model which is probabilistic in nature. One such model was investigated and formulated by Sitmourang [Ref. 6] in 1981. This dynamic route selection model performs an optimization in order to minimize the probability of being attrited enroute to the destination. The attrition probabilities along each route segment are derived from two sources. These are enemy elements capable of destroying the tactical element and terrain factors which end movement. Speed reduces the probability of attrition due to the enemy but increases the probability of attrition due to terrain, especially rough terrain [Ref. 6: pp. 21-22]. The total probability of being attrited, P, is taken to be the sum of the probability of being killed by the enemy, PKFOE, and the probability of being killed due to terrain/speed, PKVEL, which is minimized using Dijkstra's Algorithm [Ref. 6: p. 34].

There are a number of problems with this methodology. The model assumes perfect information in computing probability of kill due to enemy. This is certainly not the case in most tactical decisions. The probability of attrition due to terrain speed is computed using a heuristic equation with a power factor or constant for all combinations of conditions which is applied to a ratio of recommended speed to actual speed. This value is then used multiplicatively with normal expectancy in order to determine a probability of attrition due to speed in given terrain [Ref. 6: pp. 24-26]. No reference or theoretical support for this technique is provided. This certainly makes such a methodology suspect.

B. CURRENT MOBILITY MODELS

Mobility models provide comprehensive mappings by terrain cell or other construct of the measure or ability of weapons systems to physically traverse types of terrain in varying conditions. Mobility models should not be confused with movement models which attempt to describe how tactical elements traverse the battlefield based on both physical and cognitive considerations. The two primary mobility models used today are The NATO Research Mobility Model (NRMM) and The Condensed Army Mobility Management System (CAMMS). Most mobility routines used in models today are based on this family of models. The NRMM and CAMMS are both derived from the Army Mobility Model (AMM) developed in the 1970's. The CAMMS is currently used as the base model for:

- 1. The Planning Analysis Work Station (PAWS)
- 2. The Terrain Analysis Work Station (TAWS)
- 3. The Airland Battlefield Environment (ALBE)
- 4. The Digital Terrain Support System (DTSS)

The model is also used by numerous Army, Defense, and other government activities to include The Defense Mapping Agency, The U.S. Army Command and General Staff College, The United States Military Academy, The Army Research Institute, The U.S. Army Engineer School, The U.S. Army Training and Doctrine Command (TRADOC), and The TRADOC Analysis Command (TRAC). The CAMMS is used as the base mobility model in this research due to its applicability and acceptance in the modelling community.[Ref. 7]

1. The Condensed Army Mobility Management System (CAMMS)

The CAMMS vehicle performance model was originally developed by simplifying the existing AMM through addition of a vehicle preprocessor and restricting the model to one vehicle type at a time. Obstacle performance is also determined statistically based on years of testing and data collection. This allows the CAMMS to operate on personal computers versus larger mainframe computers for which the AMM was developed. The model is much too large and detailed to be discussed fully here; however, an examination of the physical aspects considered in the CAMMS, output available, and current uses of the model is worthwhile.

a. Physical Considerations Affecting Mobility

The CAMMS off road prediction model evaluates three general categories of terrain data. These are surface geometry data, surface composition data, and vegetation data. Surface geometry data includes slope information, surface roughness factors, and all obstacle data. Surface composition data primarily relates to the type of soil and its strength which are greatly affected by weather. The vegetation data includes stem diameter, type, and spacing data along with visibility information. These data are used in a number of routines to compute surface traction, resistance, obstacle traction, interference, gap crossing capability, vegetation effect, and ride dynamics which are combined to produce a highly accurate speed prediction for the vehicle.[Ref. 7]

b. CAMMS Output Mappings

The CAMMS is widely used throughout the Army and particularly in the European Theater of Operations. A range of mappings or Tactical Decision Aids, TDA's, are currently available in the CAMMS. These include:

- 1. Vehicle Predictions
 - a. Speed
 - b. Time
 - c. Reason Limited
 - d. Comparison of Two Vehicles
- 2. Foot Soldier Prediction
- 3. Maneuver Damage Prediction
- 4. Soil Strength Prediction
- 5. Route Analysis Prediction

The vehicle predictions and especially speed and time mappings for the digitized terrain grid are of most significance to this research [Ref. 7]. These will be addressed concerning their potential use in subsequent chapters.

c. Technology to the Field

The CAMMS takes advantage of recent advancements in the personal computer field to provide an extremely powerful yet portable and inexpensive tool for the commander in the field. The most current CAMMS requires only an IBM compatible AT personal computer with a math coprocessor, DOS 3.2, EGA graphics, 1 megabyte of RAM, and sufficient hard disk drive storage in order to operate. All the TDA's mentioned previously are available in a matter of minutes provided the appropriate digitized terrain data bases are available. The only shortcoming in the current system is the lack of standarization in terrain data bases and lack of data in general for some regions. The CAMMS is being used extensively as an aid on REFORGER exercises and as an operational planning aid in some tactical units.

The methodology developed during this research will also be derived so as to make it conformable for use on a personal computer. This will allow the model to be used as a portable tactical decision tool in the hands of the commander.

C. COGNITIVE CONSIDERATIONS IMPACTING ON MOVEMENT

The discussion up to this point makes it quite apparent that tactical movement modelling is much more involved than mobility modelling. The major question becomes, how do we model the cognitive decision process? There is no definitive answer to this question and numerous techniques are available and feasible depending on the application. It is apparent that the mission, terrain effects, and threat all influence the combatant or tactical decision maker to some degree. The decision concerning where and when to move is made based on the combatant's evaluation of how the enemy can affect his mission accomplishment and or survival as he moves to each possible location. There is also a question of the trade-off made by most humans between surviving and accomplishing a mission within a certain time. Some people are more risk averse than others.

The process is synonomous to shopping for fruit or vegetables of different types and deciding which items to purchase based on their size, shape, color, texture, and price. The shopper makes a determination when comparing different items as to which is best in terms of overall quality relative to all others and what he will purchase with a certain amount of funds just as a combatant makes a determination of the potential lethality facing him based on the types of enemy, their range, and their capabilities based on range and disposition in order to decide what risk he can accept when moving on the battlefield.

An enumeration of the variables identified as relative to this tactical movement decision process and how they are structured for use in this research is provided in detail in Chapter III.

III. PSYCHOMETRICS AND PSYCHOPHYSICAL ANALYSIS IN THE GVS

A. GENERAL

The Generalized Value System, GVS, is an axiomatic value system used as a tool for evaluating the power or potential of entities at present and future times. The formal structure of GVS was first proposed by Professor Arthur Schoenstadt of the Naval Postgraduate School in 1985 [Ref. 8: p. 3]. This procedure outlines a method of determining the state of an entity over time, allows us to compare the values of entities relative to one another, and is consistent for all entities on the battlefield. The values assigned to each entity are referred to as "power" in previous GVS documentation.

Power is a subjective value given to each element on the battlefield and combines both inherent and derived power. Derived power consists of the power an element possesses due to its ability to influence support other friendly elements [Ref. 9: p. 33]. Inherent power is the ability of an element to directly affect the outcome of a battle [Ref. 9: p. 32]. Inherent power may be categorized as Basic Inherent Power (BIP) or Situational Inherent Power (SIP) which are the power an element has at full strength and the power an element is predicted to have at some future time, respectively. The SIP is highly dependent on the available time, t_a , which is determined by the time domain networks for the respective battlefield [Ref. 8: p. 5].

The methodology proposed in this research directly supports use of the GVS by providing a means of determining actual optimum time values for the terrain grid network representing the battlefield. The methodology will also provide actual optimum time values and sets of path points for use in other combat models using conventional Lanchester attrition or firepower scores as long as they utilize explicit terrain grid networks for representing the battlefield. It will also provide excellent tactical movement planning and decision tools when incorporated into the appropriate mobility models.

Modelling the cognitive process in order to determine appropriate values for a given tactical movement scenario and instance and to then be able to map these values into the physical continuum, time, on the battlefield requires an understanding of how attitudes are measured, how to develop respective interval scales, how to convert cognitive values in interval scale into physical values in a ratio scale, and how to solve for the "Psychometric Power Function" which allows the user to solve for this value given any set of realistic variables at different levels.

B. THE MEASUREMENT OF VALUES

The correct measurement of psychological values is fundamental to evaluating instances or combinations of variables and subsequently being able to use them in any physical construct. However, there are numerous ways to develop measurements and each results in different scales with varying characteristics. The three major characteristics of measurement are order, distance, and origin. Distinctions between types of measurement and types of scale depends on what combinations of these characteristics exist [Ref. 10: p. 15].

A nominal scale exhibits none of these characteristics and will therefore not be evaluated in terms of potential use [Ref. 10: p. 17]. An ordinal scale does possess order and may have an origin; however, the scale does not exhibit distance which results in no ability to discriminate between instances in terms of a value [Ref. 10: p. 16]. This limits potential types of usable scales in psychophysical analysis to interval scales.

1. Interval Scales

Interval scales always possess the properties of order and distance. It is also often possible to determine a rational origin for such scales [Ref. 11: p. 196]. Interval scales which exhibit all three major characteristics are known as ratio scales. These scales are the most important scales used in math and science and the term "measurement" is often restricted to these types of scales [Ref. 10: p. 31]. Interval scales can be determined in a variety of ways for sets of instances and scenarios. Three powerful methods are Continuous Response Scale Judgements, Comparative Judgements, and Categorical Judgements.

a. Continuous Response Scale Judgements

A continuous response scale allows a judge to indicate the value of an instance on a continuous scale between a minimum and maximum bound, normally 0 to 100. This method lends itself to Analysis of Variance (ANOVA) testing commonly used to determine relationships. The scale value of each instance is easily obtained and the summary statistics along with the distribution of responses for each instance are also easily obtained. However, one problem with this approach is that judges have difficulty actually determining values to assign between various instances [Ref. 8: p. 10]. This is magnified the larger the number of instances becomes. For example, only five variables broken down into five distinct levels would result in 5^s or 3125 unique combinations of variables requiring responses. It is extremely difficult for a judge to realistically place a value on each with this number of instances and this approach was rejected due to this factor.

b. Comparative Judgements

The Law of Comparative Judgements presents the judge with all possible pairs of instances in order to determine which has the greater value in each pair. This discriminal process relies on the principle of "just noticeable differences" developed by L.L. Thurstone. The results of these judgements can be tabulated to provide a discriminal difference and deviation [Ref. 11: pp. 39-47]. Application of this theory is done using the method of paired comparisons. A matrix solution based on the frequencies of the responses is used to compute an interval scale. However, with n instances it requires $\frac{n(n-1)}{2}$ comparisons [Ref. 10: pp. 166-179]. For the five variables broken down into five levels, this results in 3125 instances and 4,881,250 separate comparisons. This is far more comparisons than is feasible in most studies and too labor intensive in terms of data collection.

c. Categorical Judgements

The Law of Categorical Judgements parallels the Law of Comparative Judgements in many respects. The judges evaluate each instance independently and select a rating category they feel best represents the general value of that instance. The categories are understood to be a mutually exclusive set of successive intervals which collectively exhaust all possible values of the continuum. Each rating category has descriptors and explanations which serve to help the judge with his task [Ref. 12: p. 1]. Normally distributed responses for each instance across the sampled population is a key assumption of this method. This is easily observed by examining the frequency matrix in Appendix B. Computing the interval and or ratio scale is relatively straight forward using a matrix solution [Ref. 10: pp. 205-239]. A clear, concise method is given by Professor Glenn Lindsay. Discussions with Drs. Parry and Lindsay at The U.S. Naval Postgraduate School assured that such an approach would be theoretically sound and yield usable results without requiring excessive survey and data collection effort and time once the scenarios were properly structured.

C. THE EXPERIMENTAL DESIGN

As previously addressed in the Problem Statement, the purpose of this study is to develop and demonstrate a methodology for determining an optimum, tactical movement path based on both the cognitive and physical considerations or constraints of the battlefield. As was also stated in the Introduction, devising and structuring tactical scenarios which insure the correct combinations of state variables or instances impacting on movement logic are addressed to the appropriate sample population can be an enormous and complex task. Administering the data collection effort once scenarios are developed is another major step in the experiment.

The process becomes more structured once the data are obtained. The Law of Categorical Judgements is used in this case and a well defined method for obtaining and translating the interval seale from the responses is available. Multiple regression analysis can then be applied to determine the functional relationship of the scale values for each instance to the set of state variables. The resulting regression equation becomes the "Psychometric Power Function" needed to determine values for use in GVS and other models.

1. Scenario Development

Identification of all possible state variables or those items needed to describe the specific tactical situation is the first step. This was accomplished in several ways by examining previous and ongoing tactical movement studies, reviewing doctrinal information on movement, and through discussions with groups of selected officers and combat modellers familiar with tactical movement. The following 14 variables are identified as the significant factors affecting decisions on tactical movement:

- 1. Mission
- 2. Time available
- 3. Equipment and resources available
- 4. Threat equipment and capability
- 5. Threat intention or mission
- 6. Range to the threat
- 7. Cover
- 8. Concealment
- 9. Environment, both weather and obscurrants
- 10. Area of operations or theater
- 11. Speed or vehicular agility
- 12. Range or distance to the objective
- 13. Obstacles, both natural and man-made
- 14. Artillery

The problem now becomes how to organize these variables into scenarios containing organized combinations or instances in order to provide a means of measuring certain attitudes concerning tactical movement. The number of state variables and their respective levels must be structured to reduce the required number of responses while maintaining the desired degree of fidelity in the experiment.

One technique is to eliminate any variables not significant to a majority of sources. This was the case with the variable artillery since the major impact doctrinally concerned obscurrants which fall under environment. In addition, other sources considered artillery to influence movement only through the use of improved or special munitions which usually fall under obstacles.

A second technique is to fix selected state variables for a given scenario, especially those which are categorical variables and not suited to a regression analysis. The respondent or judge is made aware of these in the definition of the scenario and the resulting scale and function are only valid for that specified combination of fixed variables. The following state variables are fixed when using this methodology.

- 1. Mission
- 2. Threat intention or mission
- 3. Area of operations or theater
- 4. Equipment and resources available
- 5. Threat equipment and capability

A third technique is to identify which variables may be combined when actually considered by the decision maker. This is the case when evaluating cover, concealment, environment, and range. All of these combine to determine the degree of inter-visibility or "line-of-sight" between the element and the threat. This line-of-sight or LOS and the number of lines-of-sight are what become critical to an element manuevering on the battlefield. There are also a number of excellent line of sight algorithms available for use in combat modelling.

This same technique is applicable in the case of localized speed or vehicular agility. Obstacles, environment, and vegetation combine with the terrain itself to determine speed. An element moving over the terrain is not concerned with soil moisture or tree stem spacing but with the total effect all these variables have on his speed. The combatant evaluates movement based on speed because he knows that the greater his speed, the less likely it is he may be engaged and the less time he will require to reach his objective in general. The Condensed Army Mobility Management System, CAMMS, provides excellent and highly accurate speed mappings for digitized terrain data.

The variable "range to threat" also requires further investigation. A combatant must evaluate many threats simultaneously and they are often different types with varying capabilities. The combatant makes his tactical movement decision based upon the greatest known or suspected enemy capability which can influence his mission at that moment. This becomes his greatest perceived threat. As mentioned previously, the combatant makes a determination of the potential lethality facing him based on the types of enemy, their range, and their capabilities based on range and disposition. A variation of the range dependency equations used in many Lanchester models will be used to calculate the "Relative Effective Range" or RER of each enemy system and allow the analyst to compare the lethality of various systems at different ranges much the same as the combatant. These have several mathematical forms studied by Seth Bonder and Bob Farrell from 1969 through 1974 [Ref. 13: No page]. The minimum RER of all threat systems with line-of-sight at a particular location then becomes the range which equates to that range given in the survey and used in the model.

One last observation concerns the variable time. Time actually becomes the dependent variable for which we wish to determine a relationship. The range to the objective is also directly related to and affects the time domain network inherent to GVS. These two variables are not included in the set of state variables given for each instance.

This now reduces the number of state variables to the five fixed variables identified previously and the following three key variables.

- I. Localized speed
- 2. Number of lines of sight
- 3. Range to the greatest threat

The three key variables must now be broken down into distinct levels in order to construct the set of instances needed for the opinion survey. An extract of the actual survey used is located at Appendix A. A conscious decision was made to keep the required number of responses at a level which allowed the the survey to be completed in an hour or less by a respondent. The variables are each divided into four levels which cover the majority of conceivable occurrances for each variable. This results in 4³ or 64 instances to be evaluated and which must be appropriately organized for the survey.
2. Survey Construction and Execution

This is only a pilot survey given to a limited population of U.S. Army and Marine Corps officers assigned to the U.S. Naval Postgraduate School, TRAC-Monterey, and Fort Ord. A total of 62 surveys were distributed during a one week period allowing two weeks for a response. A minimum of 25 surveys was needed and it was hoped that 50 usable surveys could be obtained. A total of 42 surveys were received at the end of three weeks of which 40 usable surveys were compiled to provide the data set located at Appendix B.

The actual survey used to gather responses is located at Appendix A. The state variables, divided into contiguous levels as listed, are organized into the 64 combinations or instances. These are then randomized to alleviate any possible influence on the respondents or judges due to ordering of the variables as each instance is evaluated. The number of levels and resulting number of instances has been kept as small as possible while still providing sufficient fidelity in the data in order to demonstrate the validity of this method without undue effort in the data collection. The cross-country or localized speed is broken down into levels of 0 to 5 KMPH, 6 to 15 KMPH, 16 to 30 KMPH, and 31 to 45 KMPH. The number or degree of LOS is divided into no lines-of-sight, 1 line-of-sight, 2 or 3 lines-of-sight, and 4 or more lines-of-sight. The range is divided into one kilometer bands out to 4000 meters. The exact value used for each variable within each band was also determined randomly in the case of speed and range using a pseudo-normal random number generator with the median value of the variable in that level as the mean. This provides further assurance that judges are not influenced by ordering or repeating of values.

The fixed variables are defined in an operations order given as part of the survey. The Central Army Group (CENTAG) area of Germany is the setting for an Army '92 balanced team with M1 Tanks, M2 IFV's, and attachments to conduct a deliberate attack against T80 and T72 Tank, BMP IFV, and BRDM2 ATV equipped Soviet units in defensive positions. Information on aircraft, helicopter, and artillery support is also provided.

The introduction of the survey also contains detailed explanations of the value being rated and the rating categories with examples of instances that would normally fall into that category. The five categories are :

- 1. No Movement Potential
- 2. Marginal Movement Potential
- 3. Effective Movement Potential
- 4. Good Movement Potential
- 5. Excellent Movement Potential

This rating of the state of a tactical element with respect to possible tactical movement based on the combination of variables or the instance is then combined with the corresponding ratings provided by all other judges in order to establish a data set from which an interval scale can be determined. This comprises the raw frequency matrix located at Appendix B, Section A.

D. RELATING THE COGNITVE AND PHYSICAL CONTINUUMS

The ability to accurately relate the cognitive and physical aspects of the battlefield varies immensely depending on the action being studied, the scenario, and the target population. Numerous methods can be applied allowing for complete translation of the cognitive continuum into the physical or structuring the resultant scales in order to perform a combinatorial optimization. Two specific methods and the underlying theory associated with them are examined in this study.

1. Computing Interval Scales from Categorical Responses

The theory involved in deriving interval scales using the Law of Categorical Judgements is fully explained by Professor Glenn Lindsay [Ref. 12: pp. 6-12] and W.S. Torgerson [Ref. 10: pp. 207-227]. However, a review of the major points and underlying assumptions is worthwhile. There are 6 key assumptions when using this technique.

- 1. Judges' feelings about the scale value of an instance are normally distributed across the population with mean μ_i and variance σ_i^2 .
- 2. The categories must be a mutually exclusive set of successive intervals which collectively exhaust the property continuum.
- 3. Five categories are required for rating instances.
- 4. Judges' feelings about a category upper bound are normally distributed so that for category j, the upper bound would have mean μ_j and variance σ_j^2 .
- 5. This also implies that judges feelings about the distance between an instance value and category bound are normally distributed.
- 6. Category bounds have the same variances for all j categories.

The technique takes the raw frequency matrix for all instances as mentioned and first divides these frequencies by the total number of respondents in order to determine the relative frequencies for each instance and category. These relative frequencies are then summed across the categories for each instance to derive cumulative relative frequencies which are related to cumulative values under a normal curve. These cumulative relative frequencies for category j of instance i become the normal probabilities, p_{iq} , used in computing the interval scale. The p_{iq} are grouped based on which instances have categories with similar ratings and all p_{iq} greater than 0.98 and less than 0.02 are rolled over into the adjacent category in order to reduce the effect and possible influence of outlying judges. Treating the p_{iq} as the area under a Normal (0,1) Curve, the Z matrix of normal values can be constructed. Row, column, and grand averages are computed from this matrix along with an estimate of the standard deviation. The interval scale values of all instances are computed as the grand average minus the value of the row average times the standard deviation. A linear transform is then used to obtain the correct distance for the scale.

The 10 step method of interval scale development given by Lindsay is shown below:

- 1. Arrange the raw frequency data in tablular form where the rows are instances and the columns represent categories. Columns should be sorted in a rank order from least to most favorable as left to right columns respectively.
- 2. Compute the cumulative relative frequencies for each row and record these values in a new table. This table is referred to as the P array and all values of $p_{i,j}$ greater than 0.98 or less than 0.02 are combined with the following category eliminating extreme cases. This creates an n by (m-k) array where k is the number of columns removed.
- 3. Treating the $p_{i,j}$ values as leftward areas under a Normal (0,1) Curve, find the corresponding value of Z from a normal distribution table. Record these values as a new table which is the $Z = || z_{i,j} ||$ array.
- 4. For each instance, i, in the Z array; compute the row average, \overline{z}_i .
- 5. For each column or category, j, in the Z array; compute the column average, b_j . Note that $\overline{b_j}$ is the value of category j's upper bound on the interval scale.
- 6. Compute the grand average, \overline{b} , of all Z values.
- 7. Compute $B = \sum_{j=1}^{m-k} (b_j \overline{b})^2$ which is the sum of the squared column differences.
- 8. For each row compute $A_i = \sum_{j=1}^{m-k} (z_{i,j} \overline{z}_j)^2$, the sum of the squared individual differences.

9. For each instance compute
$$\sqrt{\frac{B}{A_t}}$$
, an estimate of $\sqrt{\sigma_t^2 + c}$.

10. Finally, for each row or instance compute $S_i = \overline{b} - \overline{z}_i \times \sqrt{\frac{B}{A_i}}$, for all i.

The *S*, values are the interval scale values of the instances which are on the same scale as the category bounds, b_j . This now enables us to impart distance and a rational origin to the scale through anchoring and linear transformations. The above procedure is performed on the raw data at Appendix B. The data is segregated into 7 groups corresponding to how instances were rated by like categories. The first and last groups cannot be utilized in determing interval scales since they represent extreme instances in the survey, have incomplete Z_{ij} arrays, and only contain one boundry point. All groups have incomplete Z_{ij} arrays which is why they are segregated. A tactic which enables us to continue with the scale development requires performing the scaling procedure on each group and then performing a linear transformation between groups with two or more common boundries [Ref. 12: pp. 18-20]. Each group of data is then normalized and an interval scale computed utilizing the A Programming Lanquage (APL) program at Appendix B, Section G. The APL program "NORM" was originally developed by Paul M. Crawford during his thesis research [Ref. 8: p. 89]. The results of the normalization and interval scale for each group are located at Appendix B, Section H.

2. Converting Interval Scales to Usable Forms

The major requirement at this point is to transform the interval scale values for all groups into one contiguous scale by establishing initial boundry values for one group and then performing the linear transformations on the remaining groups. This provides consistent values for all instances evaluated on one usable scale. Another necessity in order to use the scale in models is to convert the interval scale into a ratio scale by establishing a rational origin and anchor point or points which intersect on the physical and cognitive scales. This allows us to directly map the two continuums together simultaneously. The boundry conditions applied will begin with Group II where a rational origin can be applied at the boundry in common with the extreme points shown at Appendix B, Section E. A method to anchor the other extreme end of the scale will also be discussed.

a. The Natural Origin and Anchoring in Computing Interval Scales

The extreme cases reflecting excellent potential correspond to cases which reflect little or no anti-potential. We can reverse the rating categories if desired (which was done in this case) so that excellent TMP or no anti-potential is the worst rating and then perform the normalization procedure and develop the scales. This is done in order to correctly place the rational origin. The physical scale of the battlefield based on traversal times between cells or nodes reflects only the effects of constraints on the physical mobility of a given system. At long ranges when there is no inter-visibility with opposing forces and the system can move with great speed, there is no effect due to the cognitive considerations of the battlefield. This zero point or rational origin on the cognitive scale corresponds to the effect any cognitive rating of these extreme cases would have and also the respective value of this boundry on the scale. An arbitrary value of 100 was selected for the upper boundry of Group II. This now allows for the use of the APL program "TRANS" shown at Appendix B, Section G. This program was also originally developed by Paul Crawford [REF. 8: p. 90].

b. The Linear Transformation

The linear transformation performed by this program solves a set of simultaneous equations on each group of the form:

Lower Bound = α + (β x Best Column Average) Upper Bound = α + (β x Worst Column Average)

where the column averages are already computed and the bounds are input. Once α and β are known, the instance values and other intermediate boundry values can be easily computed. These other boundry values along with those input are then used to perform linear transformations on all other groups with two or more boundries in common. All groups can then be combined in order to form one contiguous scale and the value of the extreme cases located at the rational origin may be added to the set of scale values of the instances. The set of transformed instance values is shown at Appendix B, Section I in the last column. The set of instance values along with its corresponding set of variable values are combined to form the regression matrix shown at Appendix B, Section I.

3. Regression Analysis of the Interval Scale Values

Multiple regression techniques are used on the data and derived scale values. Two different regression packages, Grafstat and SAS, are used applying backward elimination procedures. Plots of the independent variables taken two at a time with the instance values of TMP are done and then surface fitting procedures applied in Grafstat. These plots are similar to scatter plots and used in much the same way. Relationships between independent variables are of particular interest. The example plots in Appendix C. Section A reflect the linear relationships between pairs of variables. The fitted surfaces appear as planes. Due to this result, multiple linear regression is used to include product terms of all pairs of independent variables. Appendix C, Section B gives the results of backward elimination using Grafstat and Appendix C, Section C gives the corresponding results of backward elimination using SAS. Each section gives the best 4 and 5 variable models based on the largest R^2 with the best acceptable levels of significance.

The respective best regression equations for the four variable case and the five variable case are:

$$TMP = 118.24 - 0.015(RNG) + 12.0(LOS) - 2.0(SPD) + 0.2(LOS \times SPD)$$
(1)

$$TMP = 112.32 - 0.012(RNG) + 11.4(LOS) - 1.7(SPD) + 0.21(LOS \times SPD) - 0.00015(RNG \times SPD)$$
^{2}

These were the only two equations found acceptable based on the multiple regression analysis.

4. The Psychometric Power Function

The "Psychometric Power Function" is the selected best regression equation from the regression analysis. The scale can be fully determined by taking the set of maximum and minimum values for the independent variables and using these to compute the corresponding maximum and minimum values of TMP from the regression equation. The user must be aware that use of this equation or power function is only valid for the initial range of values surveyed and used in the regression. The minimum value reflects the rational origin or highest TMP which imparts zero additional time to the physical scale as discussed previously. The problem now becomes how to anchor the other extreme of the scale which reflects the maximum scale value or no TMP.

5. Translating Values of the Interval Scale to the Physical Scale

The essential step proposed by this methodology requires translating the cognitive values obtained using psychometrics into the same scale as the physical traversal time scale of the battlefield or to be able to somehow perform a combinatorial optimization between the two scales. There is a fortunate structure in the data resulting from the survey. Referring to Appendix B, Section E; there is only one extreme instance occuring on the end of the scale opposite the rational origin. It is therefore possible to prompt the user or survey a selected population to determine the amount of additional time in mission completion a combatant would be willing to accept in order to avert such a tactical instance. It is only possible to construct such an anchor due to the fact that there is only one or are a relatively small number of related instances placed at this extreme end of the continuum. The scale value of this combination of variables or instance is easily calculated. It becomes quite simple to then translate the cognitive scale to the time scale by dividing the scale or TMP values by the maximum value computed from the power function for the extreme instance which results in a (0,1) scale. Then multiply through by the given additional time value from a population mean or as provided by an individual respondent. This time scale obtained using the cognitive data can be used additively with the physical traversal time scale. Values for each individual user or a mean value for a selected population could be preferred depending on the application. This translation allows for speed and simplicity when performing the optimization using Dijkstra's algorithm which is discussed in Chapter IV. Such an approach is highly preferred if at all possible. However, it is often not possible to relate the cognitive and physical scales as in this research. Other optimization techniques which work in combinatorial optimization applications are also discussed in Chapter IV.

IV. MODEL CONSTRUCTION

A. GENERAL

This chapter outlines overall structure of the model and how the methodology already discussed is controlled and implemented. There is also some detailed examination of algorithms and methodologies; particularly concerning line-of-sight, relative effective range, and minimum cost optimization. This study follows a logical order beginning with required inputs, continues with algorithms and theory used to process data in the model, examines optimization techniques, and concludes with the model output.

The research version of this model, called the Tactical Optimum Path or TOP Model, is located at TRAC; Monterey, California and at the Mobility Systems Division, U.S. Geotechnical Laboratory; Vicksburg, Mississippi. The current model contains approximately 80,000 lines of code with most routines done in FORTRAN and the user interface, graphics, and data management executed in the C Programming Language which is used as a shell. More detailed documentation and a draft users manual for the model will be published as a joint technical report through the U.S. Army Waterways Experiment Station in late 1989.

B. TERRAIN DATA BASES

The digitized terrain data bases used for this model are the identical terrain data bases used for the CAMMS (Version 2.0). This is 100 meter grid explicit terrain data translated specifically for this version of the CAMMS [Ref. 7]. The model allows for selection of a geographic region, country, area, and specified "Quad" sheet. This selection corresponds to one of the fixed scenario variables, area of operations, identified previously.

A detailed explanation of explicit terrain data and its use can be found in *Lecture Notes In High Resolution Combat Modelling* by James K. Hartman [Ref. 4]. We will therefore dispense with any major discussion of these data. It is important to note that many of the terrain parameters provided in the data set are used in other algorithms. This is true of the line-of-sight (LOS) algorithms used. Portions of these algorithms have been altered to conform to this specific terrain data base.

C. REQUIRED INPUTS

The remaining required inputs primarily relate to the scenario development or fixed variables as well. Two of these variables needed as inputs are the appropriate missions of each force. Two other variables comprise the equipment mix available to each force. These variables are input to the model by the user during initialization of the program. The variables listed up to this point encompass all the fixed scenario variables for the methodology. It is important to stress that only the psychometric function determined for that specific combination of variables or scenario is valid for that combination in the model.

There are presently three other inputs to this model which must be addressed in our discussion. These are the element locations for each force, current environment, and the parameter related to the extreme scale value selection for translating the cognitive scale which was discussed in Chapter III, Section D. The necessity of this last input is evident. The locations and environment are necessary in determing path start, intermediate, and end points as well as range and line-of-sight results. The environment also affects mobility calculations and may be played using real time data once the Airland Battlefield Environment (ALBE) system is incorporated in the CAMMS.

The user inputs these data to include season, current weather, light condition, and soil-moisture condition for the environment. The user must input initial locations and any required subsequent locations depending on the mission as each type of combat element is entered. The user is then prompted as the last step prior to initiation of the program to provide the time value corresponding to the extreme case or anchor cited previously or to select the expected value derived from the sample population. This concludes all required inputs necessary to run the model.

D. THE MOBILITY MODEL, CAMMS (VERSION 2.0)

The CAMMS has evolved from research, testing, and analysis conducted over the past 15 years. The CAMMS was initiated in 1983 in order provide a capability for predicting mobility in a field environment in real time [Ref. 7]. There are numerous outputs available from the CAMMS relating to mobility as listed in Chapter II. This model will utilize two specific output mappings and files from the CAMMS Route Analysis Prediction: the Vehicle Speed Prediction Map and a version of the Vehicle Time Contour Map. These mappings provide the localized cross-country speed or vehicular agility which is one of the independent variables necessary for the psychometric function and the traversal times along each segment between nodes which comprises the set of arc traversal values for the physical continuum. These output values are valid for the specified item or weapon system on that terrain under the specified environmental conditions. The weather and environment are incorporated in all calculations through the Soil Moisture Strength Prediction which is one of the first routines performed by the CAMMS [Ref. 7]. A speed value is stored for all vehicle types for each grid cell or node to be used in later calculations. The arc traversal times for segments between all adjacent grid cells or nodes are also stored for later use.

The output provided up to this point by the CAMMS are all mobility modelling calculations to be used in the model. The remaining areas we will examine pertain to the cognitive considerations affecting movement and performing the optimization.

E. LINE-OF-SIGHT MODELS

The model also determines if lines-of-sight exist and to what degree or how many in order to obtain the next independent variable, LOS. There are several excellent means by which to determine LOS. A detailed explanation of line-of-sight calculations based on all types of terrain data can be found in *Lecture Notes In High Resolution Combat Modelling* by James K. Hartman [Ref. 4]. We will therefore dispense with any major discussion of LOS modelling here.

The LOS algorithms used in this model are derivations of two LOS subroutines, IVSCAN and VISTA, developed and used by the BDM Corporation in the Battalion Combat Outcome Model (BCOM) and U.S. Army TRAC respectively. The subroutines allow for point to point LOS determinations or inter-visibility fan determinations depending on the desired application and which routine is used. The subroutines are modified to use the explicit grid terrain data parameters from the CAMMS terrain data base.

The number of LOS for a given grid cell or node is determined by using the intervisibility fan from each known or suspected threat location to obtain a frequency count of the total number of lines-of-sight for each cell, FLOS. This value is also one of the independent variables stored for use later in the model.

F. RELATIVE EFFECTIVE RANGE METHODOLOGIES

The value of range used in the model requires a more detailed discussion than do the other variables. One of the assumptions given initially addressed the fact that the forms of the range dependency equations studied and proposed by Seth Bonder and Bob Farrell are correct [Ref. 13]. Several such forms and their use are expounded by James Taylor [Ref. 14 : pp. 93-99]. One similar form was used by Gordon Clark in DYNTACS

in determing the "Difficulty", E, from his set of comparative judgements [Ref. 3: p. 98]. While there appears to have been a great deal of past interest in such a methodology; there has not been any significant or sufficient analysis of how lethality and particularly perceived lethality on the part of a combatant is affected by range. Such a study is well beyond the scope of this thesis and is not attempted. This is the primary reason the stated assumption is made. However, an explanation of the equation forms and why they are used in this research is necessary.

The basic approach concerning range in this model is to assume the combatant has sufficient technical knowledge of the systems on the battlefield in order to accurately assess their potential effectiveness against other systems. It is possible to use Probability of Hit, Probability of Kill|Hit, and Total Probability of Kill values from classified AMSAA JANUS model scenarios along with the classified effective range data for a weapon system type to fit one of the equation forms previously proposed. This becomes the perceived as well as actual lethality curve for that system. The systems all have various maximum effective ranges with differing curves and equations. The systems are equated through the use of a baseline range which is assumed to be the range of the battlefield against which the actual range to maximum effective range ratio or difference is adjusted. This results in a Relative Effective Range, RER, which reflects the range given in the survey and used in the model.

Some technical data from unclassified reports, periodicals, and the general population's knowledge files were easily obtained. These sources provided some idea as to the shape and resulting type of equations the lethality curves for various systems possessed. Ranges were obtained from current military periodicals [Ref. 15]. The next step is to find a set of fictitious yet properly structured and ordered parameters for the equation forms identified from these sources. A number of potential forms could be evaluated. Actual ranges and parameters examined in JANUS data files or other sources are not used in this research. The following four equations are examined based on discussions with and previous analysis performed by the aforementioned combat modellers:

$$RER = RG \left\{ \frac{RA_i}{RM_l} \right\}^{\mu_i}$$
⁽³⁾

$$RER = RG\left\{e^{-x_i(RM_i - RA_i)}\right\}$$

$$\tag{4}$$

$$RER = \frac{RG}{(\gamma_i + 1)} \left\{ \gamma_i - \cos\left(\frac{\pi \times RA_i}{RM_i}\right) \right\}$$
⁽⁵⁾

$$RER = \frac{RG}{(\gamma_i + 1)} \left\{ \gamma_i + \cos\left(\frac{2 \times \pi \times R.4_i}{RM_i}\right) \right\}$$
(6)

where,

RER is the Relative Effective Range used in the model

RG is the baseline range used for this tactical scenario

 RA_i is the actual range to system i

 RM_i is the maximum effective range of system i

 μ , α , and γ are the respective shape scale parameters for each respective equation form

Equation number 3 is a basic Power form of the range dependency equation similar to the actual versus maximum range ratio attrition equation used in Lanchester models [Ref. 14: p.98]. Equation number 4 is an Exponential form which works well when fitting non-ballistic weapon systems with fairly constant lethality over range such as current generation anti-armor missle systems. Equation 5 is a Half-Cosine form which works well for systems that tend to have much smaller lethalities in comparison to most other systems such as small arms. Equation 6 is a Full-Cosine form applicable for systems which may have minimum as well as maximum effective ranges. [Ref. 14: pp. 96-99]

Sample graphical results of the plots performed is useful at this point. Figure 1 shows a comparison of the Soviet T72 main Battle Tank versus an AT5 Spandrael Anti-Tank Missle.



Figure 1. Comparison of Relative Effective Range for Soviet MBT vs. ATGM

The tank is represented by a Power equation with a μ of 4.0 and *RM* of 3200 meters and the ATGM is represented by an Exponential equation with an α of 0.00080 and *RM* of 5000 meters. The RER is plotted on a logrithmic scale due to the extremely low values of RER at shorter ranges. Low RER implies greater lethality. Note the significant difference in Relative Effective Range out to approximately 1200 meters. The tank is perceived to have much greater lethality at these shorter ranges. No major difference is evident between 1400 and 2000 meters; but, the lethality of the ATGM remains more constant over range and Relative Effective Range changes in favor of the missle from 2500 meters out to the limit of the battlefield.

A similar comparison exists for the M1A1 Main Battle Tank and the M2.3 Infantry Cavalry Fighting Vehicle where the tank is a ballistic system and the IFV is a missle system based on the anti-tank missle system in addition to a 25 millimeter chain gun. This comparison is shown in Figure 2.



Figure 2. Comparison of Relative Effective Range for U.S. MBT vs. IFV

The tank is represented by a Power equation with a μ of 4.25 and *RM* of 3500 meters and the IFV is represented by an Exponential equation with an α of 0.00090 and *RM* of 4000 meters. Note the significant difference in Relative Effective Range signifying the tank is the greatest perceived threat out to 2000 meters and the IFV equipped with the TOW-2 missle is obviously greater past approximately 2800 meters.

Complete listings of the systems included, the equation forms used, and resulting parameters are shown in Tables 1 and 2. Only the Power and Exponential forms are used in this analysis and in the model. Table 1 lists the values of the maximum range and scale parameter, α , for systems represented using the Exponential form equation and Table 2 lists the values of the maximum range and shape parameter, μ , for systems represented using the Power presented using the Power form equation.

NOMENCLATURE	COUNTRY	PARAMETER, α	MAXIMUM RANGE
AT4 ATGM	USSR	0.00085	4000 m.
AT5 ATGM	USSR	0.00080	5000 m.
AT3 ATGM	USSR	0.0030	1500 m.
BMP-1 IFV	USSR	0.00275	2000 m.
BMP-2 IFV	USSR	0.00080	4000 m.
BRDM-2 ATV	USSR	0.00075	5000 m.
HIP HELO	USSR	0.00180	4000 m.
HIND HELO	USSR	0.0010	4000 m.
M901 1TV	USA	0.0010	4000 m.
M2 3 1FV CFV	USA	0.00090	4000 m.
TOW ATGM	USA	0.00125	4000 m.
DRAGON ATGM	USA	0.00250	1000 m.
AH1S HELO	USA	0.0010	4000 m.
APACHE HELO	USA	0.00075	4000 m.

 Table 1.
 TECHNICAL DATA FOR MISSLE SYSTEM EQUATIONS

It is also important to note that we can compare NATO and Soviet systems using these curves. Note that the T72 Main Battle Tank has a lower μ value and is not as effective as the M1A1 Main Battle Tank nor does it possesses as long a maximum effective range. The difference is noticeable when the plots shown in Figures 1 and 2 are compared.

It is also interesting to note how the lethality for various systems change with respect to range. This gives some idea as to whether or not the RER calculated makes sense or is verifiable. The small change in slope of approximately 0.1 observed within the first 1000 meters of actual range for both tank weapons systems is one example. This range is within the boresight range of each system and there is little or no change in the trajectory of tank cannon munitions at such short ranges. The slope and subsequent RER support these facts. The slope between 2000 and 3000 meters actual range increases to approximately 1.7 indicating perceived lethality decreases more quickly. There is almost no difference in the RER of 1 at 500 meters range and the RER of 14 at 1000 meters range for the M1A1 Tank. However, there is a significant difference in the RER of 2600 at 3500 meters for the tank. The TOW-2 missle on the IFV has an RER of only 1200 at 3500 meters range. While these equations and parameters are fictitious, their application and results correspond to the manner in which experienced military personnel tend to compare these systems.

NOMENCLATURE	COUNTRY	PARAMETER, μ	MAXIMUM Range
T54 55 MBT	USSR	3.50	2000 m.
T62 64A MBT	USSR	3.75	2800 m.
T64B 72 MBT	USSR	4.00	3200 m.
T80 MBT	USSR	4.25	3200 m.
BTR60 60P PC	USSR	0.50	1500 m.
DIS. INF.	USSR	0.40	1000 m.
UNK. VEH.	USSR	1.50	4000 m.
UNK. OTHER	USSR	1.00	4000 m.
M48 60 MBT	USA	3.80	2800 m.
M60AI MBT	USA	3.90	3200 m.
M60A3 MBT	USA	4.00	3200 m.
M1P1 MBT	USA	4.10	3200 m.
MIA1 MBT	USA	4.25	3500 m.
M113 PC	USA	0.50	1200 m.
M60CEV	USA	0.80	1000 m.
DIS. INF.	USA	0.40	1000 m.
UNK. VEH.	USA	1.50	4000 m.
UNK. OTHER	USA	1.00	4000 m.

 Table 2.
 TECHNICAL DATA FOR BALLISTIC SYSTEM EQUATIONS

For this model, an RER value for each cell or node is determined by taking the actual range, RA, for each system with line-of-sight to that cell and using this range in the appropriate RER equation form for that system. The minimum value of the RER for all systems with line-of-sight, if more than one exists, is retained as the RER value for a cell.

The data and equation forms identified and derived from this short study do need to be evaluated more thoroughly. However, such an effort is beyond the scope of this thesis and would require development of an extensive experiment in order to sufficiently determine how perceived lethality is affected by range for various weapons systems. Equation forms with exact parameters derived from existing AMSAA data would almost certainly be classified as would the results of such an experiment. This is certainly a proposal for future study and enhancements; but, the assumption stated is used at this point in order to continue development of methodology based on the use of psychometric techniques without undue requirements due to an analysis of perceived lethality and or inclusion of classified data.

All required inputs to the model are complete once the CAMMS has been run; the LOS calculations are performed; the SPD, FLOS, and RER values have been obtained for each cell; and the arc traversal times between all adjacent cells are stored. The application of the cognitive portion of the model and transformation of the values to be used in the optimization can now be done.

G. APPLYING THE PSYCHOMETRIC FUNCTION

The physical time scale is already determined from the CAMMS but we must utilize the other data as inputs to the psychometric or decision function derived from the regression analysis in order to obtain the cognitive or tactical time scale. The regression equation or decision function uses FLOS, RER, and SPD as independent variables in order to output a dependent variable, Tactical Movement Potential or TMP. This value is computed as a ratio scale value for each cell through application of a rational origin and then translated into the corresponding physical time scale made up of the traversal times through the use of an anchor as outlined in Chapter III. Section D. We now have two sets of corresponding time values.

The cognitive or tactical time values represent the additional cost in units of time, equivalent to those time units on the physical scale, for a combat element to enter that cell based on the existing set or combination of state variables. The two sets of time values are additive. Consequently, the tactical time computed for each cell is then added to the physical traversal times stored for each arc which enters or has a tail node in that particular cell. This set of time values becomes the total time along each arc and the set of values desired for use in the optimization.

H. THE OPTIMIZATION

Optimization of this set of translated network values is performed using Dijkstra's algorithm which is relatively quick and efficient in this application. However, it is not always possible to determine a rational origin and particularly one or more anchors in order to translate the cognitive scale. Dijkstra's algorithm can solve the optimization problem very simply if the requirement is to either reach the objective by minimizing tactical difficulty which is equivalent to maximizing TMP, to reach the objective by minimizing only the traversal time, or to reach the objective by minimizing some total translated time as in this case. However, the problem is one of combinatorial optimization when it is not possible to determine a relationship between the two scales. We will first conduct a quick review of minimum cost optimization using Dijkstra's algorithm and then examine one method for performing the same optimization combinatorially on separate physical and cognitive scales.

1. Dijkstra's Algorithm

Dijkstra's algorithm uses a label setting procedure on a network graph with non-negative costs for all arcs in the network. This network structure must be maintained in order to avoid possible negative cycle lengths. Two sets of cells are maintained. The first set are those cells whose shortest distance or minimum cost path is already known. The second set consists of all other non-traversed cells. The known set is initially comprised of only the start or source node. At each iteration, a new cell is added to the known set which has the shortest distance or minimum cost path to the start point. The minimum cost value or shortest distance can be recorded or a predecessor array maintained. Eventually, all possible cells on the battlefield are included in the known set. At this point, the minimum cost path from the source to any other cell is available and the value can be determined. [Ref. 16: pp. 203-208]

Dijkstra's algorithm can be made even more efficient by limiting the nodes searched at each iteration. This is applicable in the model since the only permissible arcs are those between adjacent cells. The algorithm can also be used to perform a minimum cost optimization along a set of intermediate objective points or cells through application of the "Sliding Pattern Concept" [Ref. 5: pp. 22-26]. The optimization is performed locally between the ordered set of cells n times, where n is the number of intermediate eells when the order is specified and must be maintained. The optimization is performed in total until all intermediate cells are labeled or in the known set and all are contained along one unique path. This can be accomplished using any number of data structures. The set of objective points or cells is input by the user when the model is being initialized. In summation, Dijkstra's algorithm is quite useful for almost any network and can be adapted to make it even faster and more efficient with little work.

2. Combinatorial Optimization

The optimization problem can be solved very simply if the requirement is to either reach the objective by minimizing some cost along one unique scale when the cognitive and physical scales can be related as demonstrated in the previous sections. However, the problem is one of combinatorial optimization when it is not possible to determine a relationship between the two scales. This requires the analyst to find a method by which it is possible to minimize tactical difficulty while also optimizing the traversal time. The optimized time must be less than time \overline{T} and the tactical difficulty must also be minimized within this optimization. Time \overline{T} should be given by the user or obtained from the mission statement of the scenario. The model should select a route which satifies all constraints while solving one equation for both tactical difficulty, td_x , and the traversal time, t_x . A method that combines both constraints into one equation is the use of a Lagrangian multiplier, $\lambda \ge 0$, which can be used in the following equation:

$$\min_{\text{all } \mathbf{x}} (td + \lambda \times t) \mathbf{x} - \lambda \times \overline{T}$$
⁽⁷⁾

where,

x is a vector of the arcs which make up a network solution

td is the tactical difficulty based on exposure associated with each x

- t is the travel time associated with each x
- λ is the Lagrangrain multiplier

 \overline{T} is the maximum time limit to traverse the network

a. Assumptions

- 1. \overline{T} is larger than the time it takes an element to reach its objective using a shortest time network solution.
- 2. The network is undirected. This allows an element at destination B to backtrack along its route if that route offers a less difficult route and still meets the \overline{T} time limit to reach the final objective.

b. Methodology

The equation is used to calculate the shortest path based on λ using Dijkstra's algorithm. The algorithm shown at Appendix I uses a hierarchial adjacency list to search for the shortest path between the start point and the intermediate point and then from the intermediate point to the final objective. Other data structures could be used.

To calculate the maximum possible value, λ_{max} , the largest t_x from all the edges in the network is multiplied by the number of vertices in the network. If λ_{max} is used as λ in the equation, the objective function minimizes the time traveled throughout the network with no regard to tactical difficulty. When λ is zero, the minimum possible value of tactical difficulty is found. There exists a λ such that $0 \le \lambda \le \lambda_{max}$ gives the op-

timum tradeoff in minimizing the tactical difficulty while ensuring the traversal time constraint is not violated.

The best lower bound for the equation is determined by solving for $\max_{\lambda \ge 0} L(\lambda)$ which can be solved by doing a binary search from λ_{\min} to λ_{\max} . As long as the slope of $L(\lambda)$ is non-positive then the route selected is a feasible solution with regard to \overline{T} . A binary search is conducted on the interval between λ_{\min} and λ_{\max} until a specified interval, ε , is obtained between λ_{\max} and λ_{\min} . This λ with ε sufficiently small indicates the search for the optimum path minimizing tactical difficulty while arriving at the objective within \overline{T} traversal time has been accomplished.

c. The Combinatorial Optimization Algorithm

A VS-Fortran program was developed to solve the tactical movement problem (see Appendix 1) and consists of the following steps:

- 1. The data set containing the edges and their associated time and difficulty values are read into a hierarchial adjacency list. The value of the maximum t_x and TDMAX in the network are found.
- 2. Initially Dijkstra's algorithm is called to find the slope, objective function value and path for $\lambda = 0$ and $\lambda_{max} = TDMAX \times (Nodes-1)$
- 3. A check is conducted between λ_{\min} and λ_{\max} and if $\lambda_{\max} \lambda_{\min} \leq \varepsilon$ then the program is completed and the shortest path with the lowest tactical difficulty has been found.
- 4. λ_{mid} is the midpoint between λ_{min} and λ_{max}
- 5. Dijkstra's algorithm is called to compute a slope, objective value and path based on λ_{mid}
- 6. If the slope is positive then λ_{mid} becomes λ_{min} and Step 3 is repeated. Otherwise the slope is non-positive, indicating a feasible path and λ_{mid} becomes the new λ_{max} . The objective function value of λ_{mid} is compared to the previous best objective function value, OBJMAX. If λ_{mid} objective value is larger than OBJMAX, λ_{mid} objective value becomes the new OBJMAX and the optimal path, OPTX, is updated. Go to Step 3.

Once the ε value has been reached the optimum path and associated optimal values for time and tactical difficulty are outputted to a file.

d. Conclusions

The complexity of Dijkstra's algorithm is $O(|V|^2)$ and the complexity of the binary search is $O(\log_2 TDMAX)$. The Dijkstra algorithm is utilized with each iteration of the binary search; therefore, the total complexity of the program is $O(|V|^2 \log_2 TDMAX)$

To calculate the required number of iterations for a set of nodes, use the equation $\frac{1}{|V|^2 t_{\text{max}}^2}$ to determine the interval required and then solve for the number of iterations, k, using the equation

$$k > \frac{3\log_2 |V| + \log_2 TDMAX + 2\log_2 T_{\max}}{\log_2 2}$$
(8)

or use an ε of sufficiently small value.

Changes to the program can be made to decrease the run time if more information is known about the nature of the network. In a directed network the Dijkstra's algorithm can be changed to stop the search once point B has been found and then continue from point B until point C is found. The search could also be restricted over certain portions of the network based on the network's structure, greatly reducing the number of searches. Another method that could be incorporated is changing the binary search to a slope intercept search over the interval between λ_{max} and λ_{max} . These methods were not incorporated in this model since it could be used to model several types of networks with varying numbers of intermediate points and structures.

I. MODEL OUTPUT

The output for the model is designed to be presented graphically in addition to the data files for use in models. Some output is available interactively during model initialization. All output is available upon completion of a model run for use in planning, analysis, and to provide an audit trail. The key output is certainly the set of optimum path points and total route traversal time.

Interactive output consists of LOS fans displayed to the screen, a selection of base maps which include terrain elevation or vehicle speed maps, element locations, area of operation outline, and path point locations. Upon initiation of the model, cells are labelled in accordance with Dijkstra's algorithm and shown on the screen until completion of the routine, at which time the optimum path is displayed. The data are also stored for later use. Elimination of the interactive graphics capability when the model is interfaced with a combat model will greatly reduce run time.

Final output is comprised of a selection of mappings which are the vehicle speed map or SPD map, FLOS map, RER map, TMP map, and total time map. The locations, path points, area of operations outline, and actual optimum path can be imposed on any one of the selected base maps. Base maps for hard copy output may be selected in scales from 1 to 25,000 up to and including 1 to 250,000. Actual cell values for each state variable can be accessed by selecting a point interactively with a bit mapping utility. The set of optimum path points are easily obtained from a data file.

V. CONCLUSIONS AND RECOMMENDATIONS

A. GENERAL

The working model is resident in the warlab of The TRADOC Analysis Command; Monterey, California. Initial verification runs were conducted on 17 through 25 July 1989. The model is specifically tailored so as to optimize speed and efficiency on a PC-AT 386 computer. A Dell System 325 with VGA-Plus graphics and a high speed, wide carriage color printer for hard copy output was purchased to support the model. Results and subsequent conclusions and recommendations based on the methodology implementation and model runs are addressed in the following two sections.

B. CONCLUSIONS

1. Model Verification

The ability to perform a validation of the model within the scope of this thesis is impractical if validation is possible at all. However, verification in terms of the general behavior exhibited by the model and the sensibility of the results must certainly be examined. A very strong verification is not even possible without additional support and experimentation. Certainly, a more stringent verification or validation should be the focus of additional study; but, we must rely on the knowledge of experienced military officers and combat modellers in order to accomplish this limited verification.

There were 16 different variations of fixed state variables initiated for the test scenario, each with a different set of beginning path points and objectives. The expected value of 5.5 minutes for the scale time value is used in 10 of the model runs. A value of 0.0 minutes is used in 2 of the model runs in order to compare the results to the base CAMMS model runs where there is no effect due to TMP. There are no discrepancies in these comparisons. There are 4 other model runs which use times varying from 2.0 to 100.0 minutes in order to determine some idea of the sensitivity of the model with respect to the scale time value. This is related to allowing the user to input this value based on their own risk posture where a large value implies risk aversity. Some output from these verification runs are located at Appendix E. A full scale demonstration of the model was presented to a selected audience of military officers and professors on 19 July 1989. Impressions concerning the model results and and proposed enhancements were solicited with an enthusiastic response to the results.

2. Output Analysis

The model appears to work extremely well in terms of the route selection process using the expected value and in terms of the sensitivity analysis for varying risk postures. The first four pairs of 1 to 25,000 scale plots shown in Appendix E reflect movement based strictly on mobility versus tactical movement using the expected scale time value. The last two pairs reflect a change in risk posture where the expected time scale value is compared to greater times signifying a more risk averse posture.

The results are quite evident from these output mappings. The methodology and use of a psychometric decision function does provide a set of path points which appear to optimize TMP during movement in addition to mobility considerations. The model can also be applied deterministically, stochastically, or individually using different values for the scale time value. These output also appear to support sensitivity of the model to varying risk postures.

C. RECOMMENDATIONS

1. Enhancements and Areas for Research

a. Approved Scenario List

The scenarios discussed in the development of this methodology are a key element in further applications and research concerning the methodology. A complete set of scenarios of interest detailing all possible combinations of the fixed state variables must be determined in order to structure a data collection effort and target appropriate sample populations. There will eventually be a decision function derived for each of the identified combinations if the methodology is to be used. This effort would be best performed through the efforts of the U.S. Army Center for Army Lessons Learned (CALL) using information from throughout the military.

b. Expanded Survey and Regression Capability

The fidelity of this survey and corresponding regression were discussed previously. Continuing data collection and analysis efforts should be more detailed in terms of categorization and the number of levels or groups used for the independent variables. There is certainly a balance needed between the amount of fidelity desired in the model and the magnitude of the collection and analysis effort. The populations used for these efforts should also be expanded and examined closely to insure the appropriate sample is surveyed. Larger samples would certainly lower the error and increase the power of any such test. These actions should be a cooperative effort between the Army Research Institute (ARI) and TRADOC Analysis Command (TRAC).

c. Multiple Vehicle Paths and Formation Structure

The need to model units using a formation structure or by defining a path width for each arc on the battlefield which can be used to control movement will be a necessary requirement prior to interfacing this model with other combat models. This area of research alone is practically unbounded. A decision should be made by the Army Model Board concerning which approach to use. A formation structure could be applied similar to that found in DYNTACS [Ref. 3: pp. 150-155] or developing path parameters for the digitized terrain data and then limiting the optimization to only those arcs with a minimum acceptable width [Ref. 17: pp. 33-36] are both feasible. It is also possible to perform a combinatorial optimization using LaGrangian relaxation on three variables to include path width. This effort would be best accomplished by the TRADOC Analysis Command (TRAC).

d. Relative Effective Range Determinations

A similar type of pyschophysical analysis needs to be conducted in order to determine if combatants' perceived lethality sufficiently corresponds to actual lethality curves. The same method of categorical judgements could be used to derive exact regression equations or lethality curves for desired weapons systems in the model or actual classified lethality curves could be instituted if there is strong correlation between the perceived and actual results. The data and curves would certainly be classified in either case. These actions should also be a cooperative effort between the ARI and TRAC or the Army Material Systems Analysis Activity (AMSAA) and TRAC.

e. Symmetric Applications

There is also a need to determine if psychometric analysis and functions done with U.S. and allied sample populations can be extrapolated to and or directly applied to Soviet or other forces and if so, at what levels and for which actions. This analysis is necessary unless some drastic assumptions are made concerning symmetry between opposing force decision processes and tactics in general. This effort will certainly be classified and require the assistance of all major intelligence agencies.

2. Methodology Utilization and Future Applications

a. Tactical Decision Tool

A major advantage of this methodology used in a model versus a Tactical Decision Aid (TDA) such as the CAMMS is the ability of this model to provide or make a tactical decision in real time. The CAMMS and other models only provide pertinent information to the combat decision maker to assist him in choosing a course of action. The model can make tactical decisions in a laboratory or analytical environment and could be used in the field environment given the appropriate terrain data bases and intelligence input. The system and model have been developed to be easily transportable.

b. Tactical Training Tool

The model would make an excellent Tactical Training Tool allowing personnel to compare their decisions in a laboratory or classroom environment to computer simulations based on the model. This application could be performed using a variety of mediums. This application could even be done as a field exercise given the flexibility of current personal computers.

c. Combat Model Preprocessor | Subroutine

The methodology could be used as a pre-processor to provide sets of optimum path points during the initialization of any number of current combat models and then be used interactively as an event driven subroutine to recompute path changes during the course of a battle. This is highly desirable in development of systemic models where we wish to remove the human from the process and decrease variability in the battle calculus. The major problems will be to determine which events would drive an update in the path evaluation and whether to use the paths at an individual vehicle or unit level depending on resolution.

The model has been designed and structured to make it compatible with several existing combat models in terms of the terrain data bases used, the path output, and program languages used. These include the Battalion Combat Outcome Model (BCOM) developed by the BDM Corporation, both versions of JANUS combat models. CASTFOREM, and others.

d. Research and Analysis Tool

The methodology has numerous applications and great potential as an analysis tool in current form or as part of a systemic research model. The methodology can be applied in evaluating any type of decision process when the appropriate state variables can be determined and a proper sample population identified. Similar techniques can be used to include these decision functions in models leading to true systemic models and expert systems.

This specific model, once scenarios are determined and analysis performed to fully expand the model, can be used to analyze alternative General Defense Plans concerning movement. It may be incorporated into models such as the Obstacle Planner System (OPS) to assist in analyzing optimum placement of available engineer resources in countermobility or mobility roles. These are only a couple of possible research and analysis applications.

e. The Generalized Value System, GVS

The methodology also provides a theoretically sound method of determining total traversal times for the time domain network of the battlefield which is a necessary input to the Generalized Value System. There is additional work to be done in applying the methodology to the GVS. This specifically relates to the decision level at which a future state decision is made in the GVS versus the level at which paths are computed in the model. The problem does not exist at lower levels such as section or platoon. However, it may not be feasible to extrapolate values of the time domain network at a higher level from a number of smaller units comprising a large unit. The use of the path width discussed previously may be one solution. However, there would need to be a method of determining traversal speeds and other data for aggregated units with combinations of vehicles which the CAMMS and this model can not accomplish.

D. SUMMARY

The methodology demonstrates a way to determine optimum, tactical movement paths for a specified vehicle and or small unit based on the operator's cognitive decision processes, as well as the physical effects of terrain and environment on mobility. The approach uses psychometric techniques inherent to the Generalized Value System (GVS) in order to determine a decision function based on the specific tactical scenario and given equipment configuration which provides a means to determine the Tactical Movement Potential (TMP) for each terrain cell. This cognitive value in an interval scale can then be translated into the same scale as the physical continuum. The cognitive time value based on the user's decision process is then added to the physical traversal times for each cell computed from output provided by The Condensed Army Mobility Management System (CAMMS). This renders a value mapping which can be optimized using Dijkstra's Algorithm or a combinatorial method could be instituted. The resulting sets of path points are optimized for speed/time and the cognitive tactical considerations evaluated using these psychometric methods thereby rendering a truly optimum, tactical movement path and optimum traversal time. The movement path and resulting times can be used in a multitude of modelling or analytical applications and particularly in determining the time values needed to compute the Situationally Inherent Power (SIP) of the GVS. In actuality, this methodology could be applied to almost any tactical decision process in the development of expert systems and models and shows great potential for future use.

APPENDIX A. A SURVEY OF FACTORS INFLUENCING TACTICAL / COMBAT MOVEMENT.

A. INTRODUCTION.

1. Purpose.

The purpose of this survey is to obtain an estimate of the degradation to a system's Tactical Movement Potential (TMP) based on changes in 3 key variables and combinations of these variables. The results of analysis to be performed on these survey responses will then be used to develop input to a larger tactical decision tool designed to provide sets of optimum path points to commanders in the field. Your response to each question will reflect the value you place on a given combination of the 3 key variables with respect to Tactical Movement Potential (TMP). Your responses as a tactical decision maker / commander will assist in determining accurate representations of how changes in each key variable affect the rating of its relative importance to tactical movement. They may also enable us to determine how the key variables are correlated.

2. Structure.

a. Key Variables.

There are 3 key variables which have been identified as critical in determining a system's TMP. These 3 key variables are:

- 1. System Speed based on the cross-country movement rate.
- 2. Cover and Concealment based on enemy line-of-sight (LOS).
- 3. Range based on the distance to known or suspected enemy positions.

b. Rating Categories.

There are 5 rating categories from which to choose in evaluating TMP. These are a mutually exclusive set of successive intervals that collectively exhaust all possible values of the TMP. These 5 rating categories are:

- 1. No Tactical Movement Potential.
- 2. Marginal Tactical Movement Potential.
- 3. Effective Tactical Movement Potential.
- 4. Good Tactical Movement Potential.
- 5. Excellent Tactical Movement Potential.

c. Discussion.

A short discussion to insure complete understanding of the variables and the rating category you should select based on your tactical experience and judgement regarding each scenario is required. We will first examine the key variables and then define ' discuss the rating categories.

The 3 key variables represent the primary factors considered by a vehicle or unit commander when selecting an Axis-of-Advance or Route-of-Movement in operations such as an Attack, Movement-to-Contact, Withdrawal, or other operation. In each given scenario; which is simply a combination of the 3 key variables; the system employed will have a varying TMP. For example, a system travelling over rolling, open terrain at a range exceeding 4 km. from the nearest opposing force with a formation of low hills preventing enemy observation based on LOS would be capable of moving at great speed and in relative safety. This would result in high values for each key variable and exhibit "Excellent Tactical Movement Potential". On the other hand, a system moving through a peat bog and becoming virtually mired within 800 m. of several known enemy positions with little or no cover and concealment would almost certainly be destroyed or at least badly damaged and become combat ineffective. This would result in low values for each key variable and suggest the system has "No Tactical Movement Potential". Varying combinations of the 3 key variables render scenarios which will be rated between these two extremes. This leads to the second portion of our discussion.

In order to insure consistent responses between the respondents when evaluating each scenario, all respondents must thoroughly understand the definition of each rating category. These categories are:

- "No Tactical Movement Potential" implies the system cannot move through an area, a No-Go area such as a swamp, or that the system has practically no probability of surviving such a scenario in the judgement of the respondent. This may be due to a slow speed, numerous enemy observations at a close range, etc.. This represents a tactical situation any prudent commander would never select if possible.
- "Marginal Tactical Movement Potential" implies the system can move at a marginal rate and has some probability of surviving the scenario which is low. However, this is a situation where although the system can survive; the simple act of survival would render the system combat ineffective for a period of time. This represents a tactical situation which is only acceptable as a last resort for brief periods of time.
- "Effective Tactical Movement Potential" implies the system can move reasonably well and (or has a moderate probability of survival and mission success all things considered. This represents a tactical situation most commanders would consider acceptable in most cases although not preferable.

- "Good Tactical Movement Potential" implies the system can move at better than average cross-country movement rates and or has a relatively high probability of survival and subsequent mission success. This is certainly a preferable tactical situation.
- "Excellent Tactical Movement Potential" implies the system can move at or near the maximum cross-country speed with relatively little or no probability of being engaged. This is the optimum tactical situation.

3. Instructions.

The survey consists of three sections. This 'Introduction' is the first section followed by a 'Personal History' section used to collect population data. The actual tactical situation and survey compose the 'Tactical Movement Survey' section which is the last but most important section.

Please insure you feel comfortable with the variables and especially the rating categories. Fill in the required personal data as completely as possible and proceed to the survey.

You will begin by reading a synopsized OPORD giving the Task Organization, Situation, and Mission. Once you fully understand the tactical situation you will continue by answering or rating the TMP for 64 questions ; scenarios. Please rate ALL scenarios in accordance with your initial judgement in as timely a manner as possible. This is done in order to replicate the manner in which such decisions are made in fastpaced, tactical operations. Do not change answers once you have recorded your initial response unless the change is due to an inadvertent error. Answer ALL scenarios. Thank you for your cooperation.

B. PERSONAL HISTORY DATA. 1. Present Rank: • LTC, O-5 or above • MAJ, O-4 • CPT. O-3 • LT, O-1 & O-2 • E8 - E9 • E6 - E7 • E5 or below 2. Branch or MOS: Armor / Cavalry • Infantry • Aviation • Air Defense Field Artillery • Engineer • Other 3. Experience: Time on active duty Years ____ Years ____ Months Time spent in Combat Arms units Years Months • Time attached to Combat Arms units ... Years ____ Months 4. Opinion: Do you feel any other variables should be included in the scenarios which could

significantly affect the tactical decision logic?

• Yes _____ No

If so, what are these variables and how do they impact tactical movement?

C. TACTICAL MOVEMENT SURVEY.

1. OPORD 1-89, HQ/TF 1-15 XXX

Task Organization :

Team Yankee 1-15 XXX (-)

2 Mech. Plt. (M2) 2 Tank Plt. (M1) Team HQ's

1 Engineer Sqd. w/ CEV 1 Stinger 1 Fist

- 1. Situation.
 - a. Enemy Forces:

Unidentified forces of the Soviet 111TH MRR are defending in sector. The enemy is estimated to be at 72% strength in men, equipment, and supplies. They are preparing defensive positions. The enemy is equipped with organic BMP IFV's and BRDM ATV's as well as being reinforced by a T80 Guards Tank Battalion and what is left of the Regimental T72 Tank Battalion. Expect enemy artillery support from the RAG using 122 SP's. Other artillery support is possible. The enemy may receive Helo support in the form of HIP or HIND-D units if our operations are successful. The status of enemy fixed-wing support is not known at this time. The enemy has positions about 5 Kilometers away. Some enemy forces have been located and identified (assume you have an Intelligence Overlay). Other larger enemy forces are known to be preparing positions behind their security zone.

b. Friendly Forces:

Team Yankee has been conducting a Movement-to-Contact as part of TF 1-15 XXX and the 10TH Brigade. The Scouts and Team X-Ray are to our front and have encountered enemy forces in a security zone forward of their main defensive belt. Team X-Ray lost 3 vehicles today. Team Whiskey and Team Zulu are on are left and right respectively. The TF has a Battalion of 155 SP's in DS. Teams Whiskey and Zulu will attack abreast to secure intermediate Objectives Frick and Frack. Team X-Ray will provide supporting fires from their present positions.

2. Mission.

Team Yankee TF 1-15 XXX will attack NI T 1000 hours passing through Team X-Ray vicinity CP66 and between teams Whiskey and Zulu vicinity CP99 in order to sieze high ground vicinity Objective Sam. Team Yankee will then defend in place until relieved.

- 3. *
- 4. *
- 5. *

Based on the above given tactical situation; place yourself in the position of a vehicle, platoon, or unit commander and give your rating of the Tactical Movement Potential for each of the following scenarios.

2. Example Survey Scenarios for Questions 34 through 41.

- 34. You are moving cross-country as a part of Team Yankee attacking to seize Objective Sam under the following conditions:
 - Range to the nearest known or suspected enemy position is about 1475 meters.
 - Your cross-country speed is less than 5 KMPH or 3 MPH.
 - You are within the LOS of 1 known or suspected enemy location.

What do you rate the Tactical Movement Potential of this scenario as -

(_)No TMP (_)Marginal TMP (_)Effective TMP (_)Good TMP (_)Excellent TMP

- 35. You are moving cross-country as a part of Team Yankee attacking to seize Objective Sam under the following conditions:
 - Range to the nearest known or suspected enemy position is 3740 meters
 - Your cross-country speed is greater than 45 KMPH or 27 MPH.
 - You are within the LOS of 4 or more known or suspected enemy locations. What do you rate the Tactical Movement Potential of this scenario as -

(_)No TMP (_)Marginal TMP (_)Effective TMP (_)Good TMP (_)Excellent TMP

- 36. You are moving cross-country as a part of Team Yankee attacking to seize Objective Sam under the following conditions:
 - Range to the nearest known or suspected enemy position is about 750 to 770 meters.
 - Your cross-country speed is approximately 20 KMPH or 12.5 MPH.
 - You are not within the LOS of any known or suspected enemy locations.

What do you rate the Tactical Movement Potential of this scenario as -

(_)No TMP (_)Marginal TMP (_)Effective TMP (_)Good TMP (_)Excellent TMP

- 37. You are moving cross-country as a part of Team Yankee attacking to seize Objective Sam under the following conditions:
 - Range to the nearest known or suspected enemy position is 2575 meters
 - Your cross-country speed is approximately 42 KMPH or 26 MPH.
 - You are not within the LOS of any known or suspected enemy locations.

What do you rate the Tactical Movement Potential of this scenario as -

(_)No TMP (_)Marginal TMP (_)Effective TMP (_)Good TMP (_)Excellent TMP

- 38. You are moving cross-country as a part of Team Yankee attacking to seize Objective Sam under the following conditions:
 - Range to the nearest known or suspected enemy position is 1440 to 1515 meters.
 - Your cross-country speed is less than 5 KMPH or 3 MPH.
 - You are within the LOS of 4 or more known or suspected enemy locations.

What do you rate the Tactical Movement Potential of this scenario as -

(_)No TMP (_)Marginal TMP (_)Effective TMP (_)Good TMP (_)Excellent TMP

- 39. You are moving cross-country as a part of Team Yankee attacking to seize Objective Sam under the following conditions:
 - Range to the nearest known or suspected enemy position just more than 3500 meters.
 - Your cross-country speed is less than 5 KMPH or 3 MPH.
 - You are within the LOS of 1 known or suspected enemy location.

What do you rate the Tactical Movement Potential of this scenario as -

(_)No TMP (_)Marginal TMP (_)Effective TMP (_)Good TMP (_)Excellent TMP

- 40. You are moving cross-country as a part of Team Yankee attacking to seize Objective Sam under the following conditions:
 - Range to the nearest known or suspected enemy position is slightly less than 650 meters.
 - Your cross-country speed is less than 5 KMPH or 3 MPH.
 - You are within the LOS of 4 or more known or suspected enemy locations.

What do you rate the Tactical Movement Potential of this scenario as -

(_)No TMP (_)Marginal TMP (_)Effective TMP (_)Good TMP (_)Excellent TMP

- 41. You are moving cross-country as a part of Team Yankee attacking to seize Objective Sam under the following conditions:
 - Range to the nearest known or suspected enemy position is between 2280 and 2320 meters.
 - Your cross-country speed is approximately 40 KMPH or 25 MPH.
 - You are within the LOS of 4 or more known or suspected enemy locations.

What do you rate the Tactical Movement Potential of this scenario as -

(_)No TMP (_)Marginal TMP (_)Effective TMP (_)Good TMP (_)Excellent TMP

APPENDIX B. TRANSFORMING THE CATEGORICAL RESPONSES TO AN INTERVAL SCALE

A. RAW FREQUENCIES

STATE VARIABLES RESPONSE

RESPONSE FREQUENCIES

QUES NUM	R. (M.	ANGE ETERS)	<u>L</u> (ŌS QTY)	S (PEED KMPH)	NŌ TMP	MARG TMP	ĒFF TMP	GOOD TMP	ĒXĒ TMP
01	3	2400	-2-	2.5	3	22.0	 0	9	20	11	
02	2	1600	4	0.0	1	5.0	0	12	19	9	0
63	4	3200	2	2.5	4	40.0	0	2	6	20	12
04	1	750	2	2.5	1	5.0	17	18	5	0	U
05	3	2500	3	1.0	1	5.0	3	13	20	4	0
06	2	1400	1	4.5	2	11.0	5	30	5	0	0
07	4	3400	3	1.0	Э	24.0	0	0	4	22	14
08	1	640	2	2.5	J	24.0	Э	22	12	3	0
10	3	2500	1	4.5	1	5.0	3	27	9	1	0
10	2	1500	3	1.0	J	25.0	0	5	20	14	1
	4	0066	2	2.5	2	12.0	0	y 1	1/	12	2
12	1	800	4	0.0	1	5.0	2	13	22	3	0
13	3	2350	3	1.0	4	40.0	0	1	8	19	12
14	2	15/5	2	2.5	1	5.0	3	30	7	0	0
15	4	3450	3	1.0	4	35.0	0	0	5	19	16
16	1	700	1	4.5	2	11.0	16	18	6	0	0
1/	3	2450	3	1.0	2	10.0	0	Э	30	7	0
18	2	1450	2	2.5	4	38.0	Ō	11	23	5	1
19	4	3400	1	4.5	1	5.0	5	20	13	1	1
20	1	5/5	4	0.0	4	42.0	0	3	y	12	16
21	3	2600	4	0.0	3	25.0	0	0	6	19	15
22	2	1525	2	2.5	2	11.0	2	22	16	0	0
23	4	3600	4	0.0	1	5.0	2	6	16	10	6
24	1	550	2	2.5	4	42.0	2	14	16	/	1
25	3	2625	1	4.5	3	22.0	2	19	16	5	
26	2	1480	4	0.0	4	39.0	0	1	8	16	15
27	4	3300	Ţ	4.5	3	25.0	0	10	24	5	1
28	Ť	060	3	1.0	2	10.0	5	18	14	3	0
29	3	2600	4	U.U N E	1	5.0	0	13	19	8	0
30	2	1080	1	4.5	3	23.0	2	30	8	0	17
31	4	3 3 3 0	4	U.U	3	20.0	111	17	3	20	1/
32	1	400	T	4.0	3	23.0	14	10	10	2	0
33	3	2040	2	2.0	2 1	11.U	0	19	19	2	0
34	2	14/5	2	1.U	1	5.0	2	20	10	17	0
30	4	3740	1	4.5	4 0	45.0	T	5	10	1/	2
30	2	2575	++ }1	0.0	3	20.0	0	3	12	10	20
3/	3	20/0	4	U.U	4	42.0	16	20	0	10	30
30	2	1480	2	4.5	1	5.0	10	16	12	0	1
23	4	5050	1	1.0	1	5.0	2 5	15	13	9	T
40	2	2205	1	4.0 N 5	1	10.0	20	15	10	6	0
4 I 11 O	5	2505	1	4.5	2	12 0	0	2	73	15	0

64 1 625 3 1.0 3 22.0 3 11 17 8 1

B. GROUPED FREQUENCIES

		STATE	VĀRĪ	ABLES			 RES	PONSE	FREG	, UENCI	ĒS
QUES NUM	R. (M)	ANGE ETERS)	 ((OS QTY)		PEED KMPH)	NO TMP	MARG TMP	\overline{EFF} TMP	GOOD TMP	ĒXC TMP
QN 97 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 120 125 125 120 125 125 125 125 125 125 125 125 125 125	- (<u>14344432321414142144424243342333223</u>	$\begin{array}{c} STATE \\ STATE \\ \hline STATE \\ \hline STERS \\ \hline \\ \hline \\ ANGES \\ \hline \\ STERS \\ \hline \\ STERS \\ \hline \\ STERS \\ \hline \\ \\ \\ \\ STERS \\ \hline \\ \\ \\ \\ STERS \\ \hline \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ $	VARIA 	$\begin{array}{c} ABDES\\ ABDES\\ COSTY)\\ \hline 0.0\\ 0.0\\ 0.0\\ 0.0\\ 0.0\\ 0.0\\ 0.0\\ 0$	<u>()</u> ++のの+のの++++のへ+へ+への++のへ+のへ++へのの++へく	\overline{PED} \overline{KMPH}) -40.0 26.0 25.0 25.0 40.0 20.0 42.0 25.0 12.0 11.0		<i>MARG MARG TMP</i> 0 10 4 9 13 12 13 15 12 19	FKE_{0} EFF TMP 0 0 0 0 0 0 0 0 0 0 0 0 0	GOENCI GOOD TMP 10 20 22 19 19 28 16 12 20 22 19 19 28 16 12 20 22 19 19 28 16 12 20 22 19 19 28 16 12 20 22 19 19 28 16 12 0 22 19 19 28 16 12 0 22 19 19 28 10 20 22 19 10 20 22 19 19 28 10 20 22 19 10 20 22 19 10 20 22 19 10 20 22 19 10 20 22 10 20 22 19 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 22 10 20 20 20 20 20 20 20 20 20 20 20 20 20	$\begin{array}{c} - & \mathbf{F} \\ - & \mathbf{F} \\ \mathbf$
24 64 47	1 1 4 1	550 625 3500 3475	2 3 1 2	2.5 1.0 4.5 2.5	1 4 3 2 1	42.0 22.0 12.0	2 3 3 5	14 11 14 19	16 17 20 13	- 8 0 0 n	00000
64 47 55 19 05 56 32	1 4 4 3 1	625 3500 3475 3400 2500 500 400	3 1 2 1 3 1 1	1.0 4.5 2.5 4.5 1.0 4.5 4.5	3 2 1 1 4 3	22.0 12.0 5.0 5.0 5.0 40.0 23.0	3 5 5 3 10 14	11 14 19 20 13 15 17	17 20 13 13 20 10 7	g 332452	
25 08 12 28	3 1 1 1	2625 640 800 660	1 2 4 3	4.5 2.5 0.0 1.0	3 3 1 2	22.0 24.0 5.0 10.0	2 3 2 5	19 22 13 18	16 12 22 14	3 3 3 3 3	0 0 0

62 09 34 22 14 60 52 30 16 04 61 38	23222113212132	$1500 \\ 2500 \\ 1475 \\ 1525 \\ 1575 \\ 540 \\ 700 \\ 2375 \\ 1585 \\ 700 \\ 1400 \\ 750 \\ 2500 \\ 1480$	2 1 3 2 2 3 2 2 1 1 2 1 1 2 1	$\begin{array}{c} 2 \cdot 5 \\ 4 \cdot 5 \\ 1 \cdot 0 \\ 5 \cdot 5 \\ 2 \cdot 5 \\ 1 \cdot 2 \\ 2 \cdot 5 \\ 5 \cdot 5 \\$	3 1 1 2 1 1 2 1 3 2 2 1 2 1 2 1	$\begin{array}{c} 24.0\\ 5.0\\ 5.0\\ 11.0\\ 5.0\\ 10.0\\ 23.0\\ 11.0\\ 11.0\\ 5.0\\ 10.0\\ 5.0\\ 10.0\\ 5.0\end{array}$	2 3 2 3 9 12 5 2 16 5 17 9 16	18 27 20 22 30 22 27 30 18 30 18 27 22	20 10 16 7 11 6 8 8 6 5 5 4 2		000000000000000000000000000000000000000
61 38	3	2500 1480	1	4.5 4.5	2 1	10.0	9 16	27	4	0	0
40	1 	600	1	4.5 	1 	5.0	25	15 	0	0	0

C. RELATIVE FREQUENCIES

RI	ESPONSI	E FREQU	DENCIES	5
EXC TMP	GOOD TMP	ĒFF TMP	MARG TMP	NO TMP
0.75 0.75 0.35 0.35 0.375 0.375 0.375 0.375 0.375 0.225 0.05	$\begin{array}{c} 0.125\\ 0.25\\ 0.555\\ 0.475\\ 0.475\\ 0.475\\ 0.475\\ 0.475\\ 0.475\\ 0.475\\ 0.475\\ 0.475\\ 0.355\\ 0.355\\ 0.355\\ 0.355\\ 0.325\\ 0.355\\ 0.225\\ 0.325\\ 0.225\\ 0.325\\ 0.225\\ 0.325\\ 0.225\\ 0.325\\ 0.225\\ 0.325\\ 0.225\\ 0.225\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.255\\ 0.075\\ 0.0$	$\begin{array}{c} 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 5 \\ 0 \\ 1 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 5 \\ 0 \\ 1 \\ 1 \\ 1 \\ 2 \\ 2 \\ 2 \\ 5 \\ 5 \\ 0 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 2 \\ 2 \\ 2 \\ 2 \\ 5 \\ 0 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1 \\ 1$	$\begin{array}{c} 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ $	$\begin{array}{c} 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ 0\\ $

$\begin{array}{cccccccccccccccccccccccccccccccccccc$
--

D. CUMULATIVE RELATIVE FREQUENCIES

RESPONSE FREQUENCIES

		0.5 0.45 0.4 0.175 0.275 0.15 0.2 0.15 0.125 0.125 0.1 0.05 0	0.95 0.925 0.95 0.925 0.775 0.77 0.875 0.95 0.6 0.875 0.575 0.775 0.6 0.775 0.6 0.375	1 1 1 1 1 1 1 1 1 1 1 1 1 1
--	--	---	--	--

E. EXTREME INSTANCES EXCELLENT CASES

0.87	5 1	<u>1</u> 1	<u>1</u> 1	<u>1</u> 1
POOR	CASES			
				75 1

F. GROUPED CUMULATIVE RELATIVE FREQUENCY MATRICES GROUPI

111111111111

0.425	0.925	1	1	1
0.35	0.9	1	1	1
0.4	0.875	1	1	1
0.375	0.85	1	1	1
0.125	0.825	1	1	1
0.3	0.775	1	1	1
0.375	0.775	1	1	1

TGROUPI

25	Ο.	92	5
35	Ο.	9	
ŀ	Ο.	87	5
375	Ο.	85	
.25	Ο.	82	5
3	Ο.	77	5
875	Ο.	77	5
	25	25 0. 5 0. 75 0. 25 0. 25 0. 8 0. 8 0.	25 0.92 35 0.9 0.87 75 0.85 25 0.82 0.77 0.77

GROUPII

0.4	0.7	0.925	1	
0.3	0.8	0.95	1	
0.075	0.625	0.925	1	
0.225	0.625	0.95	1	
0.125	0.45	0.825	1	
0.05	0.35	0.775	1	
0.05	0.425	0.85	1	
0.075	0.425	0.8	1	
0.05	0.275	0.75	1	
0.05	0.475	0.85	1	
0.15	0.4	0.8	1	

TGROUPII

0.4	0.7	0.925
0.3	0.8	0.95
0.075	0.625	0.925
0.225	0.625	0.95
0.125	0.45	0.825
0.05	0.35	0.775
0.05	0.425	0.85
0.075	0.425	0.8
0.05	0.275	0.75
0.05	0.475	0.85
0.15	0.4	0.8

GROUPIII

0	0.375	0.875	1	
0	0.25	0.8	1	
0	0.15	0.725	1	
0	0.15	0.75	1	
0	0.575	0.9	1	
0	0.275	0.775	1	
0	0.25	0.575	1	
0	0.375	0.95	1	
0	0.325	0.875	1	
0	0.275	0.775	1	
0	0.2	0.675	1	
0	0.225	0.7	1	
0	0.175	0.925	1	
0	0.15	0.625	1	
0	0.05	0.375	1	
0	0.075	0.7	1	
0	0.05	0.525	1	

111111111111111111

TGROUPIII

0.375	0.875
0.25	0.8
0.15	0.725
0.15	0.75
0.575	0.9
0.275	0.775
0.25	0.575
0.375	0.95
0.325	0.875
0.275	0.775
0.2	0.675
0.225	0.7
0 175	0 925
0 15	0 625
0.15	0.025
0.075	0.3/3
0.075	0 525
0.00	0.323

GROUPIV

0	0.2	0.6	0.95	1
0	0.225	0.65	0.925	1
0	0.075	0.575	0.925	1
0	0.075	0.4	0.875	1
0	0.05	0.375	0.875	1
0	0.1	0.6	0.925	1
0	0.125	0.375	0.75	1
0	0.05	0.225	0.65	1
0	0.075	0.475	0.95	1
0	0.075	0.375	0.925	1
0	0.075	0.625	0.95	1
0	0.075	0.425	0.875	1

TGROUPIV

0.2	0.6	0.95
0.225	0.65	0.925
0.075	0.575	0.925
0.075	0.4	0.875
0.05	0.375	0.875
0.1	0.6	0.925
0.125	0.375	0.75
0.05	0.225	0.65
0.075	0.475	0.95
0.075	0.375	0.925
0.075	0.625	0.95
0.075	0.425	0.875

GROUPV

0	0	0.5	0.95	1
0	0	0.25	0.925	1
0	0	0.45	0.95	1
0	0	0.4	0.95	1
0	0	0.175	0.925	1
0	0	0.275	0.775	1
0	0	0.15	0.7	1
0	0	0.2	0.875	1
0	0	0.2	0.95	1
0	0	0.15	0.6	1
0	0	0.125	0.875	1
0	0	0.125	0.575	1
0	0	0.1	0.775	1
0	0	0.05	0.6	1

TGROUPV

0.5	0.95
0.25	0.925
0.45	0.95
0.4	0.95
0.175	0.925
0.275	0.775
0.15	0.7
0.2	0.875
0.2	0.95
0.15	0.6
0.125	0.875
0.125	0.575
0.1	0.775
0.05	0.6

Tł	HE APL COMPUTER PROGRAM NORM
	$\nabla NORM[D] \nabla$
[1]	∇ NORM
	$ = \nabla NORM; MTX; NOR; ROWAV; GRAV; S; AA; B; AAI; II $
[3] [ม]	□<'INPUT THE CUMREL FREQUENCY MATRIX'
[5]	NOR+NQUAN MTX
[6] [7]	$S \leftarrow pMTX$ $ROWAV \leftarrow (+/NOR) \div (S[2])$
[8]	$ROWAV \leftarrow (S[1], 1) \rho ROWAV$
[9] [10]	$COLAV \leftarrow (+/NOR) \div (S[1])$ $GRAV \leftarrow (+/(+/NOR)) \div ((S[1]) \times (S[2]))$
[11]	□<'NORMALIZED VALUES ROW AVERAGE!
[12]	$\Box \leftarrow NOR, ROWAV$
[14]	$\Box \leftarrow 1 \qquad i$
[16]	$\Box \leftarrow 1 1$
[17]	$\Box \leftarrow COLAV$
[19]	$\square \leftarrow ' GRAND AVERAGE'$
L20J [21]	$\Box \leftarrow CRAV$
[22]	
[23] [24]	AAI←Sp0 II←0
[25]	$L2:II \leftarrow II + 1$
[27]	$AA \leftarrow (NOR[;(II)] - ,ROWAV) \times 2$ $AAI[;II] \leftarrow AA$
[28]	$\rightarrow (II < S[2])/L2$
[30]	AAI + / AAI
[31]	B←+/((COLAV-GRAV)*2) SQR←(B÷AAT)*0.5
[33]	$SQR \leftarrow ((S[1]), 1) \rho SQR$
[34] [35]	SSI <grav-(rowav×sqr) AAI<(S[1].1)0AAI</grav-(rowav×sqr)
[36]	$GRAV \leftarrow (S[1], 1) \rho GRAV$
[38]	$\Box \leftarrow ' \qquad B \qquad '$
[39]	
[40]	$\Box \leftarrow ^{1} AI \qquad ^{1}$
[42] [43]	$\Box \leftarrow 1 1$ $\Box \leftarrow 2 \Delta T$
[44]	
[45]	$\Box \leftarrow SCALE VALUES = GRAND AVERAGE - (ROW AVERAGE \times (B \neq AI) \times \Box \leftarrow I = I = I = I = I = I = I = I = I = I$
[47]	□←SSI,GRAV,ROWAV,SQR
[49]	□ ← ' COLUMN AVERAGES '
[50]	$\Box \leftarrow COLAV$
	∇

G. COMPUTER PROGRAMS USED

VNQUAN[[]]V ∇ Z+NQUAN P;A;B;C;D [1] $\rightarrow ((+/(A \leftarrow (P \le 0) \lor (P \ge 1))) > 0)/L1$ [2] C← 2.515517 0.802853 0.010328 [3] *D*← 1.432788 0.189269 0.001308 [4] $P \leftarrow ((A \leftarrow (P \le 0.5)) \times P) + ((P > 0.5) \times (1-P))$ $B \leftarrow (\otimes P \times 2) \times 0.5$ [5] [6] $Z \leftarrow ((2 \times A) - 1) \times -B - ((B \circ . * 0 1 2) + . \times C) \div (1 + ((B \circ . * 1 2 3) + . \times D))$ [7] $\rightarrow 0$ [8] L1: $\Box \leftarrow THERE$ IS NO QUANTILE FOR $P = \uparrow, \overline{\Phi}A/P$ ∇

THE APL COMPUTER PROGRAM TRANS

 $\nabla TRANS[\Box]\nabla$ V TRANS [1] A VTRANS; UP; LOW; BETA; ALPHA; MX; COLUP; COLLOW; TRCOL [2] □ + 'INPUT COL AVERAGES' [3] $COL \leftarrow \Box$ [4] S+pCOL [5] COLUP+COL[S] [6] $COLLOW \leftarrow COL[1]$ □ + 'INPUT THE VECTOR OF BOUNDRY VALUES TO BE TRANSFORMED! [7] [8] $MX \leftarrow \Box$ [9] □ + 'INPUT UPPER BOUNDRY VALUE' [10] UP←□ [11] □ + ' INPUT LOWER BOUNDRY VALUE ' [12] $LOW \leftarrow \Box$ [13] $BETA \leftarrow (UP - LOW) \div (COLUP - COLLOW)$ [14] $ALPHA \leftarrow UP - BETA \times COLUP$ [15] $TR \leftarrow ALPHA + BETA \times MX$ [16] *TRCOL*+*ALPHA*+*BETA*×*COL* [17] □ ← 'TRANSFORMED UPPER BOUNDS ARE' [18] $\Box \leftarrow TRCOL$ [19] $\Box \leftarrow 1$ □ + ' TRANSFORMED DATA ' [20] $\Box \leftarrow TR$ [21] ∇

TGROUPII NORMALIZED VALU	'ES I	ROW AVERAGE	
$\begin{array}{c} 0.2529332678\\ 0.5240018704\\ 1.43980047\\ 0.7551784916\\ 1.150435626\\ 1.64521144\\ 1.64521144\\ 1.43980047\\ 1.64521144\\ 1.64521144\\ 1.64521144\\ 1.64521144\\ 1.64521144\\ 1.64521144\\ 1.64521144\\ 1.036431485\end{array}$	$\begin{array}{c} 0.5240018709\\ 0.8414567179\\ 0.318199862\\ 0.318199862\\ 0.1253809933\\ 0.384877085\\ 0.1887560409\\ 0.1887560409\\ 0.1887560409\\ 0.597404898\\ 0.0625448363\\ 0.2529332673\end{array}$	4 1.43980047 4 1.64521144 5 1.64521144 5 1.64521144 1 0.9345033954 0.7551784916 4 1.036431485 4 0.8414567174 5 1.036431485 4 0.8414567174 5 0.67418914 35 1.036431485 8 0.8414567174	0.5702896907 0.6542220957 0.1060666208 0.4027442703 -0.1137710747 -0.4249700112 -0.2658453318 -0.2623665976 -0.5228090662 -0.2237749304 -0.1493026786
COLUMN AVERA	<i>GES</i> 01829137737 1	.117242841	
<i>GRAND AVERAGE</i> 			
В			
2.682775012			
AI 1.435887596 2.405328399 4.213551553 2.891657548 2.173687547 2.883347076 3.604518528 2.610194948 2.698156333 3.634597104 1.779340999			
SCALE VALUES =	GRAND AVERAGE	- (ROW AVERAGE >	(<i>B</i> ÷AI) * .5)
-0.8003854753 -0.7117889701 -0.1054995408 -0.4087904496 0.1055285172 0.3890574987 0.2084841776 0.2451241358 0.5004515703 0.1713888323 0.1624633793	-0.020865182 -0.020865182 -0.020865182 -0.020865182 -0.020865182 -0.020865182 -0.020865182 -0.020865182 -0.020865182 -0.020865182 -0.020865182 -0.020865182	98 0.5702896907 98 0.6542220957 98 0.1060666208 98 0.4027442703 98 0.1137710747 98 0.2658453318 98 0.2623665976 98 0.5228090662 98 0.2237749304 98 0.1493026786	1.366884769 1.056099743 0.7979358365 0.9632049299 1.110947581 0.9645920205 0.8627172766 1.01380786 0.9971455871 0.8591400964 1.227898683

COLUMN AVERAGES -----1.198129767 0.01829137737 1.117242841 TRANS INPUT UPPER BOUNDRY VALUE 100.0 INPUT LOWER BOUNDRY VALUE Π: 0.0 TRANSFORMED UPPER BOUNDS ARE 7.105427358E⁻15 53.53673384 100 TRANSFORMED DATA 17.17841399 21.00486097 47.1902545 34.09124367 56.30447038 68.54997163 60.75108343 62.3335483 73.36103621 59.14895057

TGROUPI NORMALIZED VALUES ROW AVERAGE 0.6255222146 0.1887560404 1.43980047 0.384877085 0.4484258358 1.281728757 -0.2529332678 1.150435626 0.4487511792 0.3181998625 1.036431485 0.3591158114 1.150435626 0.9345033954 0.1079661155 0.5240018704 0.7551784916 0.1155883106 0.3181998625 0.7551784916 0.2184893146

COLUMN AVERAGES

GRAND AVERAGE 0.3011323644

58.76346389

B 1.122999532

AI 1.326098153 1.388787515 0.9847221265 0.917513044 2.173485362 0.8181511992 0.5760705455

SCALE VALUES = GRAND AVERAGE - (ROW AVERAGE \times (B ÷ AI) \times .5) - - - - -_____ 0.2744993195 0.3011323644 0.9202417922 0.6255222146 0.1021066199 0.3011323644 0.4484258358 0.8992322745 0.1780916163 0.4487511792 1.067905786 0.3011323644 1.106327389 0.09616729347 0.3011323644 0.3591158114 -0.1079661155 0.3787390085 0.3011323644 0.7188055603 0.1657110832 0.1155883106 0.3011323644 1.17158284 0.003925450303 0.3011323644 0.2184893146 1.396213885

COLUMN AVERAGES

TRANSFORMED DATA 6.20511592 12.36348848 9.649081675 12.57565863 29.54070381 21.93072188 15.87080765

TREATERTT

IGNUUFIII		
NORMALIZED VALUES	ROW	AVERAGE
-0.3181998625	1.150435626	0.4161178819
-0.67418914	0.8414567174	0.08363378866
-1.036431485	0.5974048985	0.2195132933
-1.036431485	0.67418914	0.1811211726
-0.1887560404	1.281728757	0.7352423985
-0.5974048985	0.7551784916	0.07888679654
-0.67418914	0.1887560404	0.2427165498
-0.3181998625	1.64521144	0.6635057888
-0.4533333679	1.150435626	0.3485511292
-0.5974048985	0.7551784916	0.07888679654
-0.8414567174	0.4533333679	0.1940616747
-0.7551784916	0.5240018704	0.1155883106
-0.9345033954	1.43980047	0.2526485371

1.036431485 0.3591158114 0.3181998625 1.64521144 0.9817056513 0.3181998625 -0.4578992996 -1.43980047 0.5240018704 0.7913333019 1.64521144 0.06254483635 COLUMN AVERAGES 0.8126365611 0.7084504496 GRAND AVERAGE _ _ _ _ _ _ _ _ _ _ _ _ _ _ 0.05209305576 В _ _ _ _ _ _ _ 1.156852847 AI _ _ _ _ _ _ _ _ _ _ _ 1.078445099 1.148591183 1.334710664 1.463111462 0.5972946791 0.9147409136 0.3723371922 1.927491972 1.286037493 0.9147409136 0.8382406825 0.8181511992 2.818659422 0.917513044 0.8804798637 1.928259815 1.45821575 SCALE VALUES = GRAND AVERAGE - (ROW AVERAGE \times (B ÷ AI) \star .5) _ _ _ _ _ _ . 0.4830723627 0.05209305576 1.035714459 0.4161178819 -0.05209305576 0.1360270889 0.08363378866 1.00358999 -0.1522718504 0.05209305576 0.2195132933 0.9309910257 0.05209305576 0.1089602245 0.1811211726 0.8892018419 0.05209305576 1.075327804 0.7352423985 1.391697147 0.05209305576 0.1408074984 0.07888679654 1.124579099 0.05209305576 0.2427165498 0.3757359646 1.762669339 -0.5661218971 0.05209305576 0.6635057888 0.774716438 -0.05209305576 0.3826747026 0.3485511292 0.9484452039 -0.05209305576 0.1408074984 0.07888679654 1.124579099 0.05209305576 0.1940616747 0.1758857464 1.174774991 0.08535423712 -0.05209305576 0.1155883106 1.189110665 0.05209305576 0.2526485371 0.2139511961 0.640645468 -0.05209305576 0.3511505256 0.3591158114 1.122878939 -0.05209305576 1.07318704 0.9817056513 1.146249992 0.05209305576 0.4578992996 0.7745621745 0.3025784214 0.05209305576 0.7913333019 0.6527421852 0.8906932632

COLUMN AVERAGES 0.8126365611 0.7084504496 TRANS INPUT UPPER BOUNDRY VALUE 100.0 INPUT LOWER BOUNDRY VALUE 53.536734 TRANSFORMED UPPER BOUNDS ARE 53.536734 100 TRANSFORMED DATA 63.60363281 74.20451018 83.01091652 81.68791555 45.51254274 74.05848734 89.83687224 61.06679397 66.67038912 74.05848734 83.7322288 80.96684485 71.82423312 89.08588313 111.141278 87.60219509

98.29833015

TGROUPIV NORMALIZED VALUES	S ROW	AVERAGE	
-0.8414567174 -0.7551784916 -1.43980047 -1.43980047	0.2529332678 0.384877085 0.1887560404 0.2529332678	1.64521144 1.43980047 1.43980047 1.43980047 1.150435626	0.3522293302 0.3564996877 0.06291868014 0.1807660371

1.64521144 0.3181998625 1.150435626 -0.27099189211.43980047 1.281728757 0.2529332678 0.1370016603 0.3181998625 1.150435626 0.67418914 0.2648154496 -0.7551784916 0.6718376156 1.64521144 0.384877085 1.43980047 0.06254483635 1.64521144 0.04762204472 1.43980047 0.3181998625 0.1060666208 1.43980047 -1.43980047 1.64521144 0.1745369443 0.3181998625 1.43980047 0.1887560404 1.150435626 0.1593736279 COLUMN AVERAGES 1.329835441 0.06802605834 1.267100775 GRAND AVERAGE -----0.04358690797 B ----3.372934763 AI --------3.106548825 2.410174235 4.169803347 3.36247368 3.911164149 3.723520871 1.668902612 2.071048262 4.776854354 4.213551553 4.789607793 3.355956505 SCALE VALUES = GRAND AVERAGE - (ROW AVERAGE \times (B + AI) \star .5) 0.04358690797 0.3522293302 0.4106074699 1.041993186 0.04358690797 0.4653211892 0.3564996877 1.182986398 -0.04358690797 0.100175096 0.06291868014 0.8993861263 0.04358690797 0.1374601038 0.1807660371 1.001554356 0.04358690797 0.2709918921 0.2080690671 0.9286476179 0.04358690797 0.1739794959 0.1370016603 0.9517591802 -0.2648154496 0.04358690797 0.3328843213 1.4216362 0.04358690797 0.6718376156 0.8137927532 1.276170969 0.08360358382 0.04358690797 0.04762204472 0.8402973052 0.04358690797 0.1060666208 0.05131141717 0.8947048978 -0.04358690797 0.1745369443 -0.04358690797 -0.1593736279 0.1900544398 0.8391778165 0.1161893582 1.002526379 COLUMN AVERAGES 1.329835441 0.06802605834 1.267100775 TRANS

INPUT UPPER BOUNDRY VALUE □: UPEINPUT LOWER BOUNDRY VALUE □: 53.536734 TRANSFORMED UPPER BOUNDS ARE 53.536734 99.9999999 149.1630147 TRANSFORMED DATA 87.38521723 85.37050872 98.81618467 107.5665614 110.1665762 96.09850519 114.7626146 132.4709759 99.42639298

95.50658187 106.7833145 TGROUPV NORMALIZED VALUES ROW AVERAGE 1.010066757E⁻7 6.741891400E⁻1 8.226057706*E*1 1.645211440*E*0 1.439800470*E*0 3.828056648*E*⁻1 -1.253809931*E*_1 1.645211440*E*0 $7.599152235E^{-1}$ 2.529332678*E*1 $6.961390862E^{-1}$ 1.645211440*E*0 -9.345033954*E*-1 2.526485371E⁻1 1.439800470*E*0 -5.974048985*E* 7.551784916*E*1 5.240018704*E*1 7.888679654E-2 1 -2.562148074E1.036431485*E*0 -8.414567174*E*_1 1.150435626E0 1.544894545*E* -8.414567174*E*-1 1.645211440*E*0 4.018773614*E*1 3.917491087*E*1 1.036431485*E*0 $2.529332678E^{-1}$ -1.150435626*E*0 1.150435626*E*0 0.00000000*E*0 -4.808397929E-1 1.887560404*E*1 7.551784916*E*1 1.150435626*E*0 _2.632751325E ----1.281728757E0 -1.645211440E0 -6.961390862E-1 2.529332678*E*1

COLUMN AVERAGES 0.8262856749 1.035021384

GRAND AVERAGE _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ 0.1043678548

104.3943316

В _ _ _ _ _ _ _ _ 1.732231984 1

1

1

AI	
1.3533601	75
2.2344700	50
1.5674987	82
1.8014766	66
2.8186594	22
0.9147409	136
1.2174761	29
1.9838175	54
3.09175920	63
0.8312307	332
2.6470042	6
0.8967171	601
2.0744955	69
1.8014766	66

лT

SCALE VALUES = GRAND AVERAGE - (ROW AVERAGE \times (B:AI) \star .5) 0.8262857891 1.131348305 0.1043678548 0.8226057706 0.880471243 0.1043678548 0.2326815247 0.3828056648 0.6944809054 1.051234053 0.1043678548 0.7599152235 0.5782611302 0.1043678548 0.6961390862 0.9805928133 0.09369293795 0.1043678548 0.2526485371 0.7839380152 0.004189260708 0.1043678548 0.07888679654 1.37611261 0.2562148074 0.4099845144 0.1043678548 1.192814197 0.1043678548 0.9344415953 0.0399935175 0.1544894545 0.1964431591 0.1043678548 0.4018773614 0.7485144544 0.3917491087 0.6698908224 0.1043678548 1.443584567 0.1043678548 0.1043678548 0 0.8089575013 -0.4808397929 0.7726743588 1.389873538 0.1043678548 -0.2632751325 0.3449462429 0.9137907782 0.1043678548 0.6961390862 0.7869968397 0.9805928133 0.1043678548

COLUMN AVERAGES

O.8262856749 1.035021384
 TRANS
 INPUT UPPER BOUNDRY VALUE
 UPE
 INPUT LOWER BOUNDRY VALUE
 100.0
 TRANSFORMED UPPER BOUNDS ARE
 100 149.1630147
 TRANSFORMED DATA
 99.99999698
 115.6789657
 103.4813814
 106.5511138

119.3500945 121.7141701

- 132.6538113
- 120.7684663

1	1	6	•	6	З	6	1	3	5	7
1	З	9		5	1	8	7	6	0	1
1	2	4		5	8	1	5	0	7	3
1	4	2		2	3	З	5	9	8	8
1	3	0		9	3	5	9	4	4	5
1	4	2		6	1	1	9	0	0	9

I. THE REGRESSION MATRIX

STATE VARIABLES

SCALE VALUE

\overline{QUES}	RANGE	LOSX		TMP
NUM	(METERS)	1000(QTY)	100(<i>KMPH</i>)	RATING
	· · · · · · · · · · · · · · · · · · ·			
31	3550	0	2600	6.20511592
7	3400	1000	2400	12.36348848
15	3450	1000	3500	9.64908167
21	2600	0	2500	12,57565863
54	1390	0	2400	29.54070381
13	2350	1000	<u>u</u> 000	21,93072188
26	11280	1000	3900	15 87080765
20	575	0	1200	17 17841399
20	2200	2500	4200	21 00486097
26	760	2300	4000	17 1902515
50	2650	0	2000	
03	5000	1000	1100	54.09124307
44	275	1000	4200	50.50447038 C0 EU007163
11	3300	2500	1200	68.5499/163
46	1565	1000	4000	60.75108343
48	500	0	1000	62.3335483
51	3450	2500	2100	73.36103621
35	3740	4500	4500	59.14895057
23	3600	0	500	58.76346389
10	1500	1000	2500	63.60363281
43	3300	1000	1000	74.20451018
18	1450	2500	3800	83.01091652
27	3300	4500	2500	81.68791555
49	2480	0	1100	45.51254274
57	2475	2500	4200	74.05848734
39	3550	1000	500	89.83687224
42	1620	0	1200	61.06679397
53	2600	1000	2200	66.67038912
1	2400	2500	2200	74.05848734
29	2600	0	500	83.7322288
2	1600	0	500	80.96684485
17	2450	1000	1000	71.82423312
41	2305	4500	4000	89.08588313
50	1500	4500	4000	111.141278
58	1550	1000	1100	87.60219509
33	2640	2500	1100	98.29833015
24	550	2500	4200	87.38521723
64	625	1000	2200	85.37050872
47	3500	4500	1200	98.81618467
55	3475	2500	500	107.5665614
19	3400	4500	500	110.1665762
5	2500	1000	500	96.09850519
56	500	4500	4000	114.7626146
32	400	4500	2300	132.4709759
25	2625	4500	2200	99.42639298
8	640	2500	2400	104.3943316
12	800	0	500	95,50658187
28	660	1000	1000	106.7833145
62	1500	2500	2400	99,99999698

9 34 22 14 60 52 45 30 16 64 61	2500 1475 1525 1575 540 700 2375 1585 700 1400 750 2500	4500 1000 2500 2500 2500 2500 4500 4500 4500 4500 4500 4500 4500 4500 4500 500 4500 500	$ \begin{array}{r} 500\\ 500\\ 1100\\ 500\\ 1000\\ 500\\ 2300\\ 1100\\ 1100\\ 500\\ 1000\\ 500 \end{array} $	115.6789657 103.4813814 106.5511138 119.3500945 121.7141701 132.6538113 120.7684663 116.6361357 139.5187601 124.5815073 142.2335988 130.9359445 142.6110000
61	2500	4500	1000	130.9359445
38	1480	4500	500	142.6119009

APPENDIX C. REGRESSION ANALYSIS OF COGNITIVE FACTORS AFFECTING MOVEMENT

A. SURFACE PLOTS

Surface plots of all possible combinations of independent variables were done in order to determine if there were any particular relationships between variables with respect to TMP which needed to be accounted for in the regression analysis. These are used in a fashion similar to scatter plots in simple regression. Note the linear or planar relationship between most combinations shown.



Figure 3. Surface Plot of TMP Versus SPD and RNG for No LOS



Figure 4. Surface Plot of TMP Versus SPD and RNG for 2-3 LOS



Figure 5. Surface Plot of TMP Versus SPD and RNG for 4- LOS



Figure 6. Surface Plot of TMP Versus SPD and RNG for All LOS



TMP VERSUS SPEED AND NUMBER OF LINES OF SIGHT

Figure 7. Surface Plot of TMP Versus SPD and LOS for All RNG



TMP VERSUS RANGE AND NUMBER OF LINES OF SIGHT

Figure 8. Surface Plot of TMP Versus RNG and LOS for All SPD

B. REGRESSION USING GRAFSTAT

MULTIPLE REGRESSION USING BACKWARD ELIMINATION

TABLE OF COEFFICIENTS

63 OBSERVATIONS R-SQUARED = 0.9048 STANDARD ERROR = 12.486 5 VARIABLES ADJ R-SQUARED = 0.8983

COEF	<i>ESTIMATE</i>	STD ERR	T STAT	SIG LEVEL
INTERCEPT	1.1824 <i>E</i> 2	5.2563 <i>E</i> 0	22.495	1.6653 <i>E</i> -16
RNG3	-1.4744 <i>E</i> -2	1.4786 <i>E-</i> 3	-9.9715	3.4722E-14
LOS3	1.1545 <i>E</i> -2	1.6888 <i>E-</i> 3	6.8366	5.5107 <i>E-</i> 9
SPD 3	-1.9871 <i>E</i> -2	1.7745 <i>E-</i> 3	-11.198	6.3838 <i>E</i> -16
(LOS3-SPD3)	1.9839 <i>E-</i> 6	6.8170 <i>E</i> -7	2.9102	5.1154 <i>E-</i> 3

The assumptions of normality in the residuals and homogeneity of variance in the residuals are supported. The model is valid based on the standard error of the estimate and the extremely high R^2 .

ANOVA RESULTING FROM THE REGRESSION

ANALYSIS OF NORMAL DISTRIBUTION FIT

DATA SELECTION X AXIS LABEL SAMPLE SIZE CENSORING FREQUENCIES EST. METHOD CONF METHOD	RESIDUAL ALL CRESIDUAL 63 NONE 1 MAXIMUM L ASYMPTOTI	IKELIHOOD C NORMAL APPRO	XIMATION	
PARAMETER E MU SIGMA	<i>ESTIMATE</i> 2.0510 <i>E</i> 13 1.1980 <i>E</i> 1	CONF. INTERVA (95 PERCENT) LOWER UPPE 2.9589 2.9 9.8878 14.0	LS COVARIAN PARAMETE R MU 589 2.27 72 0	CE MATRIX OF R ESTIMATES SIGMA 81 0 1.1391
MEAN STD DEV SKEWNESS: KURTOSIS:	SAMPLE 1.9331E ⁻ 13 1.2076E1 -3.1684E-2 2.6120E0	FITTED 2.0510E ⁻ 13 1.1980E1 0.0000E0 3.0000E0	GOODNESS OF CHI-SQUARE : DEG FREED: SIGNIF :	FIT 2.9566 3 0.39836
PERCENTILES 5: 10: 25: 50: 75: 90:	SAMPLE -20.102 -14.305 -8.0305 -1.0027 10.122 14.321	FITTED -1.9710E1 -1.5355E1 -8.0768E0 1.2101E-6 8.0768E0 1.5355E1	SIGNIF CRAMER-V M : SIGNIF ANDER-DARL : SIGNIF	0.97341 0.037255 > .15 0.22113 > .15



Figure 9. Residual Analysis of the Four Variable Regression

95: 19.153 1.9710*E*1

GOODNESS OF FIT ON THE RESIDUALS FROM THE REGRESSION

CHI-SQUARE GOODNESS OF FIT TABLE

<i>LOWER</i>	UPPER	OBS	EXP	0 – E	((O-E)*2)*E
-INF.	-15.639	6	6.0403	0.040285	0.00026868
-15.639	7.8194	11	10.149	0.85093	0.071344
7.8194	0	16	15.311	0.68937	0.031039
0	7.8194	11	15.311	-4.3107	1.2136
7.8194	15.639	14	10.149	3.8509	1.4612
15.639	+INF.	5	6.0403	-1.0403	0.17916
TOTAL		63	63		2.9566



Figure 10. Residual Analysis of the Five Variable Regression

C. REGRESSION USING SAS

1. THE FIRST SAS MULTIPLE REGRESSION

OPTIONS LINESIZE=80; DATA ONE; CMS FILEDEF DD1 DISK GDATA22 DATA A; INFILE DD1; INPUT RANG LOSS SPED TAMP; PROC STEPWISE DATA=ONE; MODEL TAMP = RANG LOSS SPED / BACKWARD MAXR;

	SAS	9:54 <i>TU</i>	ESDAY, J	UNE 13,	1989		
	BACKWARI	D ELIMINAT	ION PROC	EDURE F	OR DEPEN	IDENT VARI	ABLE TAM.
STEP 0	ALL VARI	IABLES ENT	ERED	R S C(P	QUARE =	0.8909952 4.0000000	ч 0
	DF	SUM OF S	QUARES	MEAN S	QUARE	F	PROB>F
REGRESS. ERROR TOTAL	ION 3 59 62	84699.83 10362.21 95062.05	472023 574916 046940	28233.2 175.6	7824008 3077541	160.75	0.0001
	B VALUE	STD	ERROR	TYPE	II SS	F	PROB>F
INTCPT RANG LOSS SPED	110.4773 -0.0148 0.0156 -0.0159	5149 2470 0.0 3357 0.0 5209 0.0	0156910 0099485 0122666	15677. 43371. 29702.	3226081 3604309 3114397	+ 89.26 246.95 3 169.12	0.0001 0.0001 0.0001
BOUNDS	ON CONDI	TION NUMBE	<i>CR</i> : 1	.002224	9	.013743	
ALL VAR	IABLES I	N THE MODE	L ARE SI	GNIFICA	ANT AT T	<i>HE</i> 0.1000	LEVEL.

86

2. THE SECOND SAS MULTIPLE REGRESSION

OPTIONS LINESIZE=80; DATA ONE; CMS FILEDEF DD1 DISK GDATA22 DATA A; INFILE DD1; INPUT RANG LOSS SPED TAMP; RS = RANG*SPED; LS = LOSS*SPED; RL = RANG*LOSS; PROC STEPWISE DATA=ONE; MODEL TAMP = RANG LOSS SPED RS LS RL / BACKWARD MAXR;

SAS 9:55 TUESDAY, JUNE 13, 1989

BACKWARD ELIMINATION PROCEDURE FOR DEPENDENT VARIABLE TAMP

STEP 0	ALL	VARIAB	LES EI	VTERED	R C (SQUARE = P) =	0.90984757 7.00000000	
		DF S	UM OF	SQUARES	MEAN	<i>SQUARE</i>	F	PROB>F
REGRESS ERROR TOTAL	SION	6 8 56 8 62 9	6491.9 570.07 5062.0	97593599 7453341)5046940	14415. 153.	32932267 03704524	94.20	0.0001
	B V.	A <i>LUE</i>	SI	TD ERROR	TYP	PE II SS	F	PROB>F
INTCPT RANG LOSS SPED RS LS RL	109.0 -0.0 -0.0 -0.0 -0.0	0798549 0101762 0133716 0172817 0000013 0000020 00000009	6 7 0 5 0 3 0 3 0	00299509 00249723 00270126 00000106 00000068 00000086	1766 4387 6263 240 1373 179	.6605027 .8253343 .8341026 .9863333 .7204536 .4216166	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	0.0013 0.0001 0.0001 0.2147 0.0041 0.2835
BOUNDS	ON CO	ONDITIO	N NUM	BER:	7.23914	6, 2	206.9791	
STEP 1	VARIABLE	RL REMOVED	<i>R SQUARE</i> = 0.9 <i>C</i> (<i>P</i>) = 6.1	0796016 7240643				
--	--	---	--	--				
	DF	SUM OF SQUARES	MEAN SQUARE	F PROB>F				
REGRESS ERROR TOTAL	<i>SION</i> 5 57 62	86312.55431939 8749.49615001 95062.05046940	17262.51086388 11 153.49993246	2.46 0.0001				
	B VALUE	STD ERROR	TYPE II SS	F PROB>F				
INTCPT RANG LOSS SPED RS LS	112.322060 -0.01170 0.011369 -0.017055 -0.000005 0.000005	019 732 0.0026442 915 0.0016805 147 0.0026969 146 0.0000010 206 0.0000006	9 3008.87281840 9 7024.89975456 4 6136.04920158 5 292.39366190 8 1411.56803480	$\begin{array}{cccc} 19.60 & 0.0001 \\ 45.76 & 0.0001 \\ 39.97 & 0.0001 \\ 1.90 & 0.1729 \\ 9.20 & 0.0036 \end{array}$				
BOUNDS	ON CONDIT	ION NUMBER:	6.576496, 116.9	728				
STEP 2	VARIABLE	RS REMOVED	<i>R SQUARE</i> = 0.9 <i>C</i> (<i>P</i>) = 6.0	0488434 8301351				
	DF	SUM OF SQUARES	MEAN SQUARE	F PROB>F				
REGRESS ERROR TOTAL	510N 4 58 62	86020.16065748 9041.88981191 95062.05046940	21505.04016437 1 155.89465193	37.95 0.0001				
	B VALUE	STD ERROR	TYPE II SS	F PROB>F				
INTCPT RANG LOSS SPED LS	118.23954 -0.01474 0.01154 -0.01987 0.00000	426 358 0.00147857 539 0.00168875 087 0.00177449 198 0.00000068	15500.71093605 7286.43553484 19548.66357433 1320.32593725	99.430.000146.740.000125.400.00018.470.0051				
BOUNDS	ON CONDIT	ION NUMBER:	4.72315, 45	.35				
ALL VAL	RIABLES IN	THE MODEL ARE	SIGNIFICANT AT THE C	0.1000 <i>LEVEL</i> .				
SUMMAR	Y OF BACKW	ARD ELIMINATION	I PROCEDURE FOR DEPEN	NDENT VARIABLE				
	VARTABLE	NUMBER PARTIA	L MODEL					

STEP	RMVED	IN	R**2	R**2	C(P)	F	PROB>F
1	RL	5	0.0019	0.9080	6.17241	1.1724	0.2835
2	RS	4	0.0031	0.9049	6.08301	1.9048	0.1729

SAS 9:55 TUESDAY, JUNE 13, 1989

MAXIMUM R-SQUARE IMPROVEMENT FOR DEPENDENT VARIABLE TAMP STEPS 1 THROUGH 3 OMITTED STEP 4 VARIABLE LS ENTERED R SQUARE = 0.90488434C(P) =6.08301351 DF SUM OF SQUARES MEAN SQUARE F PROB>F 86020.16065748 21505.04016437 137.95 0.0001 REGRESSION 4 589041.889811916295062.05046940 ERROR 9041.88981191 155.89465193 TOTAL FB VALUE STD ERROR TYPE II SS PROB > F*INTCPT* 118.23954426 0.00147857 15500.71093605 99.43 0.0001 0.00168875 7286.43553484 46.74 0.0001 -0.01474358 RANG 46.74 0.0001 LOSS 0.01154539 -0.01987087 0.00000198 0.00177449 19548.66357433 -0.01987087 125.40 0.0001 SPED 0.0000068 1320.32593725 LS 8.47 0.0051 BOUNDS ON CONDITION NUMBER: 4.72315, 45.35

THE ABOVE MODEL IS THE BEST 4 VARIABLE MODEL FOUND.

STEP 5 VARIABLE RS ENTERED R SQUARE = 0.90796016C(P) =6.17240643 DFSUM OF SQUARES MEAN SQUARE FPROB > F586312.5543193917262.51086388112.460.0001578749.49615001153.499932466295062.05046940 REGRESSION ERROR TOTAL STD ERROR TYPE II SS F PROB>F B VALUE 0.0001 0.0001 0.0001 0.1705 *INTCPT* 112.32206019 -0.011707320.002644293008.8728184019.600.011369150.001680597024.8997545645.76-0.017051470.002696946136.0492015839.97-0.00001460.00000105292.393661901.900.000002060.000000681411.568034809.20 RANG -0.01170732 LOSS SPED -0.01705147 RS LS 0.0036 BOUNDS ON CONDITION NUMBER: 6.576496, 116.9728 _____ THE ABOVE MODEL IS THE BEST 5 VARIABLE MODEL FOUND. STEP 6 OMITTED

APPENDIX D. COMBINATORIAL OPTIMIZATION PROGRAM USING LAGRANGIAN RELAXATION

DDOODAN NETTOR

PRUGRAM	NIWRKS	
******	$ c_{sc} c_{sc}$	ראר
PROBLEM:	A TACTICAL UNIT MUST MOVE FROM START POINT A, THROUGH	75
	AN INTERMEDIATE POINT B, TO OBJECTIVE C IN NO MORE THAN	75
	TBAR TIME UNITS. EACH ARC/EDGE (U,V) IN THE NETWORK	が
	HAS A TRAVERSAL TIME TC(E) AND EXPOSURE/TACTICAL DIFFI-	5'5
	CULTY MOVEMENT ANTI-POTENTIAL OF TD(E). WE WISH TO FIND	3'0
	A PATH FROM A THROUGH B TO C WHICH HAS AN ACCEPTABLE	75
	TRAVERSAL TIME AND TACTICAL DIFFICULTY OR TO MINIMIZE	75
	TD SUBJECT TO TBAR. IT IS ASSUMED THAT THERE EXISTS AT	×
	LEAST 1 FEASIBLE PATH FROM A THROUGH B TO C.	7'5
AUTHORS:	RICHARD MILLER. MAJOR. USMC	쑸
	CHARLES H. SHAW, CAPTAIN, USA	75
	IAN KEITH. CAPTAIN. USMC	*
SUBROUTINE:	DYKSTR - DIJKSTRA'S ALGORITHM	3'
VARIABLES:	UVCD - INPUT ARRAY OF EDGES (U.V).TIME COST TC(E). AND	*
111111111111111111111111111111111111111	TACTICAL DIFFICULTY TD(E).	7'5
	EDGES - NUMBER OF ARCS/EDGES (10000 MAXIMUM).	*
	X1 X2 - BOOLEAN VECTORS FROM X IN SUBROUTINE DLIKSTRA.	7:
	OPTX - BEST VECTOR X1 X2 X3 FOUND THUS FAR	*
	NODES - NUMBER OF NODES I E VERTICES (1100 MAXIMUM)	75
	S T - START/STOP VERTICES FOR DI KSTRA'S ALGORITHM	*
	U V - ALL ARBITRARY VERTICES	75
	FPS - FPSILON & SMALL NUMBER OR DIFFERENTIAL	*
	TRAR - MAYIMUM TIME ALLOWED IN NETWORK (INPUT)	25
	PRED - PREDECESSOR OF & NODE	*
	D - D(V) 'IAREI' ARRAY FOR DIJKSTRA'S ALCORITHM	25
	DMIN - DMIN FOR DIIKSTRA'S ALCORITHM	20
	EP - ENTRY POINT ARRAY	-10
	OUTDEG - OUTDEGREE OF NODE TO COMPUTE ENTRY POINT ARRAY	*
	ADI - ADIACENT VERTICES ARRAY	sle.
	LENGTH - EDGE LENGTH (TIME) APPAY	40
	TACHIE - EVOLUER/TACTICAL DIFFICULTY APPAY	3'5
	TDMAY - LARGEST VALUE OF TACDIE()	ste.
	ORI - ORIECTIVE FUNCTION VALUE OF PI IN DIRECTRA	25
	ORIMAY - ORIECTIVE FUNCTION MAYIMUM FOR D3	مرايد ا
	LAM - LACRANCIAN MULTIDITED IN SUBPOUTINE DITESTRA	
	LAMMIN - TEMDODADY MINIMUM OF LAM	مرايد ا
	LAMMID - MIDDOINT OF LAMMIN AND LAMMAY	2.
	LAMMAY - TEMPODADY MAYIMUM OF LAM	ي. م
	ENDIAM - REST VALUE OF IAM	
	TRUDAN - DESI VALUE UF LAN. TRIAMT - (TR - IAMBRANT) ADDAV	et.
	SIDE _ SIDE (TONY _ TEAD) IN SUBDOUTINE DI WETER	36
و مارد مارد مارد مارد مارد مارد مارد مارد	- SLOFE - SLOFE (10°A - IDAK) IN SUDRUUTINE DIJASTRA Istologiciologiciosticiosticiosticiosticiosticiosticiosticiosticiosticiosticiosticiosticiosticiosticiosticiosti	مارمم
	PROBLEM: AUTHORS: SUBROUTINE: VARIABLES:	 PROBLEM: A TACTICAL UNIT MUST MOVE FROM START POINT A, THROUGH AN INTERMEDIATE POINT B, TO OBJECTIVE C IN NO MORE THAN TBAR TIME UNITS. EACH ARC/EDGE (U,V) IN THE NETWORK HAS A TRAVERSAL TIME TC(E) AND EXPOSURE/TACTICAL DIFFI- CULTY MOVEMENT ANTI-POTENTIAL OF TD(E). We WISH TO FIND A PATH FROM A THROUGH B TO C WHICH HAS AN ACCEPTABLE TRAVERSAL TIME AND TACTICAL DIFFICULTY OR TO MINIMIZE TD SUBJECT TO TBAR. IT IS ASSUMED THAT THERE EXISTS AT LEAST 1 FEASIBLE PATH FROM A THROUGH B TO C. AUTHORS: RICHARD MILLER, MAJOR, USNC CHARLES H. SHAW, CAPTAIN, USA IAN KEITH, CAPTAIN, USA IAN KEITH, CAPTAIN, USA IAN KEITH, CAPTAIN, USA CHARLES I. UVGD - INPUT ARRAY OF EDGES (U,V),TIME COST TC(E), AND TACTICAL DIFFICULTY TD(E). EDGES - NUMBER OF ARCS/EDGES (10000 MAXIMUM). X1,X2 - BOOLEAN VECTORS FROM X IN SUBROUTINE DIJKSTRA. OPTX - BEST VECTOR XI,X2,X3 FOUND THUS FAR. NODES - NUMBER OF NODES, I. E., VERTICES (1100 MAXIMUM). S, T - START/STOP VERTICES FOR DIJKSTRA'S ALGORITHM. U, V - ALL ARBITRARY VERTICES. EPS - EPSILON, A SMALL NUMBER OR DIFFRENTIAL. TBAR - MAXIMUM TIME ALLOWED IN NETWORK (INPUT). PRED - PREDECESSOR OF A NODE. D - D(V) 'LABEL' ARRAY FOR DIJKSTRA'S ALGORITHM. DY - LEAGEST VALUE OF NODE S ALGORITHM. EP - ENTRY POINT ARRAY. OUTDEG - OUTDEGREE OF NODE TO COMPUTE ENTRY POINT ARRAY. ADJ - ADJACENT VERTICES ARRAY. LENGTH - EDGE LENGTH (TIME) ARRAY. TACDIF - EXPOSURE/TACTICAL DIFFICULTY ARRAY. ADJ - ADJACENT VERTICES MRAY. ADJ - ADJACENT VERTICES IN ALGORITHM. EP - ENTRY POINT ARRAY. ADJ - ADJACENT VERTICES ARRAY. ADJACENT VERTICES TO ALUE OF TACDIF(). OBJ -

```
INTEGER UVCD(10000,4),X1(10000),X2(10000),OPTX(10000)
      INTEGER EP(10001), OUTDEG(10001)
      INTEGER ADJ(10001), LENGTH(10001), TACDIF(10001)
      INTEGER EDGES, I, J, K, NODES, A, B, C, TDMAX, L, TIME, U, V
      REAL TBAR, LAMMIN, LAMMID, LAMMAX, OBJMAX, EPS, P1, ENDLAM
      REAL SLOPE1, SLOPE2, SLOPE3, OBJ1, OBJ2, OBJ3
      COMMON UVCD, EP, ADJ, LENGTH, TACDIF, EDGES, NODES, TBAR, A, B, C
      PARAMETER (EPS = 0.0001)
* SET FILEDEFS
      CALL EXCMS('FILEDEF 01 DISK PROJNET DATA B')
      CALL EXCMS('FILEDEF 02 DISK NETWORKS OUTPUT A')
* INITIALIZE ARRAYS TO ZERO
      DO 5 I = 1, 10001
           OUTDEG(I) = 0
           EP(I) = 0
           ADJ(I) = 0
           LENGTH(I) = 0
           TACDIF(I) = 0
   5 CONTINUE
* READ IN THE DATA ONE ROW AT A TIME AND FIND
* THE NUMBER OF NODES AND MAXIMUM VALUE OF TD(E)
      READ(1,*) NODES, A, B, C, TBAR
      I = 1
      TDMAX = 0
   10 READ(1,*,END=20) (UVCD(I,J), J=1,4)
      TDMAX = MAX(UVCD(1,4), TDMAX)
      I = I + 1
      GO TO 10
   20 IF (NODES .GT. 1100) THEN
           STOP '*** ERROR, NUMBER OF NODES EXCEEDS 1000 ***'
      END IF
* COMPUTE NUMBER OF EDGES IN THE NETWORK
      EDGES = I - 1
      IF (EDGES .GT. 10000) THEN
           STOP '*** NUMBER OF EDGES EXCEEDS SIZE DEFINED ***'
      END IF
* COMPUTE OUTDEGREE FOR EACH NODE
```

```
91
```

```
DO 30 I = 1, EDGES
           OUTDEG(UVCD(I,1)) = OUTDEG(UVCD(I,1)) + 1
   30 CONTINUE
* INITIALIZE ENTRY POINT ARRAY EP()
      EP(1) = 1
      DO 40 I = 1, NODES
           EP(I+1) = OUTDEG(I)
           EP(I+1) = EP(I+1) + EP(I)
   40 CONTINUE
* COMPUTE THE HIERARCHICAL ADJACENCY LISTS FOR EACH NODE, EP() TO
* ADJ() AND LIST ALL THE NODE'S ADJACENT VERTICES AND CORRESPONDING
* LENGTH OR TIME COST AND EXPOSURE/TACTICAL DIFFICULTY
      K = 1
      DO 50 I = 1, NODES
           DO 51 J = 1, EDGES
                IF (UVCD(J,1) . EQ. I) THEN
                     ADJ(K) = UVCD(J,2)
                     LENGTH(K) = UVCD(J,3)
                     TACDIF(K) = UVCD(J, 4)
                     K = K + 1
                END IF
                IF (K .GT. 10000) THEN
                   STOP '*** ADJACENCY LISTS EXCEEDS SIZE DEFINED ****'
                END IF
   51
           CONTINUE
   50 CONTINUE
      PRINT *, 'INITIALIZATION COMPLETE AND BEGINNING SEARCH'
* FIND BOUNDS ON LAM
      LAMMIN = 0.0
      LAMMAX = (NODES - 1) * TDMAX
      L = 0
      CALL DYKSTR(LAMMIN, X1, SLOPE1, OBJ1)
      WRITE(2,*) 'LAMMIN=', LAMMIN, 'SLOPE1=', SLOPE1, 'OBJ1=', OBJ1
      CALL DYKSTR(LAMMAX, OPTX, SLOPE3, OBJ3)
      OBJMAX = OBJ3
      WRITE(2,*) 'LAMMAX=', LAMMAX,' SLOPE3=', SLOPE3,' OBJ3=', OBJ3
      PRINT *, 'INITIAL DIJKSTRA COMPLETE'
   70 LAMMID = (LAMMIN + LAMMAX)/2.0
      IF (ABS(LAMMAX - LAMMIN) . LE. EPS) GO TO 500
      L = L + 1
      PRINT *, 'ITERATION', L, 'STARTING'
```

```
CALL DYKSTR(LAMMID, X2, SLOPE2, OBJ2)
     WRITE(2,*) 'LAMMID=',LAMMID,' SLOPE2=',SLOPE2,' OBJ2=',OBJ2
     IF (SLOPE2 .GT. 0) THEN
           LAMMIN = LAMMID
     END IF
     IF (SLOPE2 . LE. 0) THEN
           LAMMAX = LAMMID
           IF (OBJ2 .GT. OBJMAX) THEN
                OBJMAX = OBJ2
                ENDLAM = LAMMID
                DO 80 I = 1, EDGES
                      OPTX(I) = X2(I)
 80
                CONTINUE
          END IF
     END IF
     GO TO 70
500 WRITE(2,*) 'WITH',L,'ITERATIONS THE '
     WRITE(2,85) OBJMAX
  85 FORMAT(' MAXIMUM OBJECTIVE FUNCTION VALUE FOR P2 IS ', F10. 3)
     TIME = 0
     P1 = 0.0
     DO 90 I = 1, EDGES
          TIME = OPTX(I) * UVCD(I,3) + TIME
           P1 = OPTX(I) * UVCD(I,4) + P1
  90 CONTINUE
     WRITE(2,*) 'THE SOLUTION FOR (TD*X) IS ',P1
WRITE(2,*) 'EPSILON IS ',P1 - OBJMAX,', TIME ON THE PATH IS ',TIME
     WRITE(2,*) 'AND THE LAST VALUE OF LAM IS ',ENDLAM
WRITE(2,*) 'THE BEST PATH FROM NODE ',A,', THROUGH NODE ',B,','
     WRITE(2,*) 'TO OBJECTIVE NODE ',C,'IS ALONG PATH: '
     WRITE(2,95) A
  95 FORMAT('NODE ', I5)
     U = A
 550 I = 1
 600 IF ((U . EQ. UVCD(I,1)) . AND. (OPTX(I) . EQ. 1)) THEN
           WRITE(2,95) UVCD(1,2)
           IF (C.EQ. UVCD(I,2)) STOP 'THE END'
           U = UVCD(1,2)
           GO TO 550
     ELSE
           I = I + 1
           GO TO 600
     END IF
     END
```

```
SUBROUTINE DYKSTR(LAM,X,SLOPE,OBJ)
      INTEGER PRED(1100), I, J, K, S, T, U, V, VMIN, X(10000)
      INTEGER UVCD(10000,4), EP(10001), ADJ(10001), LENGTH(10001)
      INTEGER TACDIF(10001), EDGES, NODES, A, B, C
      REAL D(1100), DMIN, SLOPE, OBJ, LAM, TDLAMT(10001), TINF, TBAR
      COMMON UVCD, EP, ADJ, LENGTH, TACDIF, EDGES, NODES, TBAR, A, B, C
      PARAMETER (TINF = 1.0E15)
* SET TDLAMTC() FOR NEW LAM
      DO 300 I = 1, EDGES + 1
           TDLAMT(I) = TACDIF(I) + LAM * LENGTH(I)
  300 CONTINUE
* RESET OPTIMAL PATH FOR NEXT SEGMENT
      DO 305 I = 1, EDGES
           X(I) = 0
  305 CONTINUE
* DIJKSTRA'S ALGORITHM FOR SHORTEST PATH FROM S TO ALL NODES
      S = A
      T = B
* INITIALIZE THE SHORTEST PATH AND PREDECESSOR ARRAYS
  400 \text{ DO } 310 \text{ I} = 1, NODES
           PRED(I) = 0
           D(I) = TINF
  310 CONTINUE
* INITIALIZE START VERTEX, S
      D(S) = 0.0
      PRED(S) = S
      DO 320 I = 1, NODES
           DMIN = TINF
           DO 330 J = 1, NODES
                 IF ((PRED(J).GE.O) .AND. (D(J).LT.DMIN)) THEN
                      DMIN = D(J)
                      VMIN = J
                 END IF
  330
           CONTINUE
           PRED(VMIN) = -PRED(VMIN)
```

```
DO 340 K = EP(VMIN), EP(VMIN+1)-1
                IF ((D(VMIN) + TDLAMT(K)) . LT. D(ADJ(K))) THEN
                     D(ADJ(K)) = D(VMIN) + TDLAMT(K)
                     PRED(ADJ(K)) = VMIN
                END IF
  340
           CONTINUE
  320 CONTINUE
* CONVERT PRED() TO PATH X()
      V = T
  360 I = 1
  370 IF ((-PRED(V) . EQ. UVCD(I,1)) . AND. (V . EQ. UVCD(I,2))) THEN
           X(I) = 1
           V = -PRED(V)
           GO TO 360
      ELSE
           IF (V.EQ. -PRED(S)) GO TO 380
           I = I + 1
           GO TO 370
      END IF
  380 IF (S .EQ. B) GO TO 390
* NOW GET SHORTEST PATH FROM B TO C
      S = B
      T = C
      GO TO 400
* COMPUTE OBJECTIVE FUNCTION VALUE AND SLOPE FOR LAM
  390 \text{ OBJ} = 0.0
      SLOPE = 0.0
      DO 450 I = 1, EDGES
           OBJ = (UVCD(I,4) + LAM * UVCD(I,3)) * X(I) + OBJ
           SLOPE = UVCD(I,3) * X(I) + SLOPE
  450 CONTINUE
      OBJ = OBJ - LAM * TBAR
      SLOPE = SLOPE - TBAR
      END
```

APPENDIX E. EXAMPLE MODEL OUTPUT

The purpose of these example output plots is to demonstrate proper functioning of the model in terms of tactical movement decision logic and some sensitivity analysis of the cognitive time scale values. Plots are appropriately labelled with all normal Tactical Optimum Path (TOP) output plots being expected value model runs unless otherwise noted. High risk averse plots use an input value of 30 minutes and extreme risk averse plots use an input value of 60 minutes rather than the expected value of 5.5 minutes.

These verification model runs are based on the Lauterbach map sheet near Fulda in the central region of The Federal Republic of Germany. The base map is one version of the terrain relief map available in the CAMMS. The NATO vehicle represented is an M1A1 Main Battle Tank moving as part of a deliberate attack against the specified Warsaw Pact systems shown in a deliberate defense.

The sequence of numbers shown on the mapping represents the path points in the order specified by the user. The continuous line connecting these points is the resulting optimum path from the optimization. The other irregular polygon shapes represent the user input area of operations which appropriately restricts the network searched during the optimization. The set of optimum path points and large amounts of audit data are available in data files for use directly in combat models and analysis rather than output to a screen or map.

CONDENSED ARMY MOBILITY HODEL SYSTEM (CAMMS) Tactical Optimum Path MISSION :BLUE:Dellberg RED: Dellbergr Vehlele:M1A1 OMHI JULY DRY ELEVATION CONTOUR MAP SSS < SE5 METERS 3885 - 850 METERS 3350 - 375 METERS 🖂 375 - 400 METERS 223400 - 425 METERS 425 - 450 METERS []]450 - 475 METERS 2001 > 475 METERS

ì

1



Figure 11. CAMMS Output Mapping For Set 3



Figure 12. TOP Output Mapping For Set 3













Figure 15. CAMMS Output Mapping For Set 5

ł



Figure 16. TOP Output Mapping For Set 5



Figure 17. CAMMS Output Mapping For Set 6



Figure 18. TOP Output Mapping For Set 6



Figure 19. CAMMS Output Mapping For Set 15



Figure 20. TOP Output Mapping For Set 15



Figure 21. TOP Mapping With A High Risk Averse Posture For Set 15



Figure 22. CAMMS Output Mapping For Set 16



Figure 23. TOP Output Mapping For Set 16



Figure 24. TOP Mapping With A High Risk Averse Posture For Set 16



Figure 25. TOP Mapping With An Extreme Risk Averse Posture For Set 16

LIST OF REFERENCES

- 1. Taylor, James G., An Examination of Soviet Work on Lanchester-Type Combat Models that Reflect Continuous Spatial Distribution of Forces, Unpublished Paper, Naval Postgraduate School, CA, No Date.
- 2. Clark, Gordon M., and Bishop, A.D., *The Tank Weapon System, Final Report,* Number AR 69-2, Systems Research Group, Ohio State University for The U.S. Army Combats Development Command, 1969.
- Clark, Gordon M., and Howland. Daniel D., *The Tank Weapon System, Annual Report*, Number AR 66-1, Systems Research Group, Ohio State University for The U.S. Army Combats Development Command, June 1966.
- 4. Hartman, James K., Lecture Notes on Hi-Resolution Combat Models, Naval Postgraduate School, CA, 1985.
- 5. Kramer, James S., Simulation of Dynamic Tactical Route Selection with Application in The STAR Model, M.S. Thesis, Naval Postgraduate School, March 1979.
- 6. Situmorang, Posma R.M., Dynamic Route Selection for Land Combat Simulation Models, M.S. Thesis, Naval Postgraduate School, March 1981.
- Falls, T.C., and Ahlvin R.B., *The Condensed Army Mobility Management System* (CAMMS), USACE-WES Technical Report (DRAFT), Mobility Systems Division, U.S. Geotechnical Laboratory, U.S. Army Waterways Experiment Station, 1989.
- 8. Crawford, Paul M., *Dynamic Study of Factors Impacting on Combat Power*, M.S. Thesis, Naval Postgraduate School, March 1988.
- Kilmer, Robert A., *The Generalized Value System and Future State Decision Making*, M.S. Thesis, Naval Postgraduate School, March 1986.

- 10. Torgerson, Warren S., Theory and Methods of Sealing, Wiley, 1958.
- 11. Thurstone, Louis L., The Measurement of Values, Chicago Press, 1959.
- 12. Lindsay, Glenn F., Constructing Interval Seales from Categorieal Judgements, Unpublished Paper, Naval Postgraduate School, CA, September 1981.
- Bonder, Seth, and Farrell, Robert, A discussion of range dependency equations and previous analysis done concerning the effects of range on lethality obtained from telephone conversations conducted by CPT.(P) Charles H. Shaw, III on 7 and 10 April 1989.
- 14. Taylor, James G., Lanchester-Type Models of Warfare, Volume II, The Military Operations Research Society, Monograph, No Date.
- 15. Jane's Information Group. Jane's Weapons Systems 1988-89, Jane's Information Group Inc., Surrey, U.K., 1989.
- 16. Aho, A.V., Hopcroft, J.E., and Ullman, J.D., *Data Strueures and Algorithms*, Addison-Wesley, 1983.
- 17. Choi, Seok Cheol, Determination of Network Attributes from a High Resolution Terrain Data Base, M.S. Thesis, Naval Postgraduate School, March 1987.

BIBLIOGRAPHY

Conover, W.J., Practical Nonparametric Statistics, 2d ed., Wiley, 1980.

Dean, T.C., Robinson, J.H., and Bullock, D.C., *Digital Mobility-Terrain Data Base Development and Mobility Evaluations in Australia*, USACE-WES Technical Report, Number GL-87-11, Mobility Systems Division, U.S. Geotechnical Laboratory, U.S. Army Waterways Experiment Station, May 1987.

Dupuy, Trevor N., The Fundamental Information Base for Modelling Human Behavior in Combat, Publisher Unknown, No Date.

JANUS Development Team, *The JANUS Version 4.0 Document*, M-226 Technical Report, Lawrence Livermore National Laboratory, January 1988.

McKinley, George B., Mobility Models Utilizing Acceleration and Deceleration, USACE-WES Technical Report, Number GL-88-19, Mobility Systems Division, U.S. Geotechnical Laboratory, U.S. Army Waterways Experiment Station, September 1988.

Rimoldi, H.J.A., and Hormaeche. M., "The Law of Comparative Judgement in the Successive Intervals and Graphic Rating Scale Methods", *Psychometrika*. Vol. 20, Number 4, pp. 307-318, 1955.

Rolands & Associates Corporation, *Modelling Soviet Surface-to-Surface Missile Relocation Decision Logic to Analyze Effects of Improved Detection Capality*, Contract Report for the Naval Postgraduate School, Monterey, CA, 1986.

Saffir, Milton J., "A Comparative Study of Scales Constructed by Three Psychophysical Methods", *Psychometrika*, Vol. 2, Number 34, pp. 179-198, 1937.

Scott, William A., and Wertheimer, M., Psychological Research, Wiley, 1962.

STSC. Inc., APL*PLUS System for the PC Reference Manual, STSC, Inc., 1987.

STSC, Inc., Statgraphics Statistical Graphics System User's Guide, STSC, Inc., 1987.

Taylor, James G., Lanchester-Type Models of Warfare, Volume I, The Military Operations Research Society, Monograph, No Date.

INITIAL DISTRIBUTION LIST

		No. Copies
1.	Defense Technical Information Center Cameron Station Alexandria, VA 22304-6145	2
2.	Library, Code 0142 Naval Postgraduate School Monterey, CA 93943-5002	2
3.	Deputy Undersecretary of the Army for Operations Research Room 2E261, The Pentagon Washington, D.C. 20310	2
4.	Director Attn:Mr. E.B. Vandiver III U.S. Army Concepts Analysis Agency Bethesda, MD 20814	2
5.	Director Requirements & Programs Director Headquarters, USA-TRADOC Attn:ATRC-RP (COL Brinkley) Fort Monroe, VA 23651-5143	2
6.	Commander U.S. Army TRADOC Analysis Command Attn:ATRC Fort Leavenworth, KS 66027-5200	2
7.	Commander and Director U.S. Army TRADOC Analysis Command TRAC-Monterey Monterey, CA 93943	5
8.	Commander and Director U.S. Army TRADOC Analysis Command TRAC-FLVN Attn:ATRC-F (Dr. LaRocque) Fort Leavenworth, KS 66027-5200	1
9.	Commander and Director U.S. Army TRADOC Analysis Command TRAC-FLVN Attn:ATRC-ZD (Mr. Bauman) Fort Leavenworth, KS 66027-5200	2

10.	Commander and Director U.S. Army TRADOC Analysis Command TRAC-WSMR Attn:ATRC-W (Dr. Collier) White Sands Missle Range, NM 88002-5502	1
11.	Commander and Director U.S. Army TRADOC Analysis Command TRAC-WSMR Attn:ATRC-RD (Mr. Hue McCoy) White Sands Missle Range, NM 88002-5502	2
12.	Commander and Director U.S. Army TRADOC Analysis Command TRAC-LÉE Attn:ATRC-LC Fort Lee, VA 23801-6000	2
13.	Professor Samuel H. Parry Department of Operations Research Naval Postgraduate School, Code 55Py Monterey, CA 93943-5000	5
14.	Professor Arthur L. Schoenstadt Department of Mathematics Naval Postgraduate School. Code 532h Monterey, CA 93943-5000	5
15.	Captain Ian H. Keith, USMC 5109 Pommeroy Drive Fairfax, VA 22032	2
16.	Captain(P) Charles H. Shaw,III 407 Powell Street Philadelphia, MS 39350	5
17.	Chief Defense Scientist Office Operations Analysis Department Attn:Sim Cheng Hwee Ministry of Defense Mindef Building, Sombak Drive Singapore 2366 The Republic of Singapore	2
18.	Commander and Director USACE-WES Attn:CEWES-GM (Dr. John Farr) 3909 Halls Ferry Road Vicksburg, MS 39180-6199	5
19.	Commander and Director USACE-WES	1

Attn:CEWES-GV-A (Dr. Paul Hadala) 3909 Halls Ferry Road Vicksburg, MS 39180-6199



Thesis

S43723 Shaw

c.1 A psychomatric method for determining optimum, tactical paths in combat decision making and analysis.






