



**Calhoun: The NPS Institutional Archive**  
**DSpace Repository**

---

Reports and Technical Reports

All Technical Reports Collection

---

1981-07-09

# Voice of America HF Curtain Array Interference Study

Adler, Richard W.

Monterey, California. Naval Postgraduate School

---

<https://hdl.handle.net/10945/68898>

---

This publication is a work of the U.S. Government as defined in Title 17, United States Code, Section 101. Copyright protection is not available for this work in the United States.

*Downloaded from NPS Archive: Calhoun*



Calhoun is the Naval Postgraduate School's public access digital repository for research materials and institutional publications created by the NPS community. Calhoun is named for Professor of Mathematics Guy K. Calhoun, NPS's first appointed -- and published -- scholarly author.

**Dudley Knox Library / Naval Postgraduate School**  
**411 Dyer Road / 1 University Circle**  
**Monterey, California USA 93943**

<http://www.nps.edu/library>

AD-A104 310

BDM CORP MONTEREY CA

F/G 17/2.1

VOICE OF AMERICA HF CURTAIN ARRAY INTERFERENCE STUDY.(U)

JUL 81 R W ADLER

N00014-79-C-0088

UNCLASSIFIED

BDM/N-TK-0015-81

NL

1 OF 1  
413 A  
10-81



END  
DATE  
FILMED  
10-81  
DTIC

LEVEL

12



P.O. BOX 2019 2600 GARDEN ROAD MONTEREY CALIFORNIA 93740 408-549-3551

AD A104310


ENC FILE COPY

DTIC ELECTE  
S SEP 17 1981 D  
E

This document has been approved for public release and sale; its distribution is unlimited.

818 24010  
818 24010

LEVEL II (12)



PO BOX 1017 2200 WASHINGTON A MILITARY CAMP WASHINGTON DC 20314-1017

9 July 1981

BDM/M-TR-0015-81

VOICE OF AMERICA HF CURTAIN ARRAY

INTERFERENCE STUDY

BY

RICHARD W. ADLER

Project Engineer

DTIC  
S 17 1981  
E

This document is prepared for public release and its distribution is unlimited.



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

14 REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER BDM/M-TR-0015-81	2. GOVT ACCESSION NO. AD-A10	3. RECIPIENT'S CATALOG NUMBER	
6 4. TITLE (and Subtitle) VOICE OF AMERICA HF CURTAIN ARRAY INTERFERENCE STUDY		5. TYPE OF REPORT & PERIOD COVERED 9 Technical Study 3-81 to 7-81	
7. AUTHOR(s) 10 RICHARD W. ADLER Project Engineer		8. PERFORMING ORG. REPORT NUMBER BDM/M-TR-0015-81	
9. PERFORMING ORGANIZATION NAME AND ADDRESS The BDM Corporation 2600 Garden Road Monterey, CA 93940		8. CONTRACT OR GRANT NUMBER(s) 15 N00014-79-C-0088	
11. CONTROLLING OFFICE NAME AND ADDRESS Dean of Research, Code 012 Naval Postgraduate School Monterey, CA 93940		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Work Order No. 303	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Mr. Robin Simpson Administrative Contracting Officer Stanford University, Room 165, Durond Aero Bldg. Stanford, CA 94305		12. REPORT DATE 11 9 July 1981	
16. DISTRIBUTION STATEMENT (of this Report) Please see Page 11		13. NUMBER OF PAGES 11	
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		15. SECURITY CLASS. (of this report) UNCLASSIFIED	
18. SUPPLEMENTARY NOTES		16. DECLASSIFICATION/DOWNGRADING SCHEDULE	
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report describes the results of a computer modeling investigation in which the interference to VHF and UHF communications/navigation equipments from a Voice of America HF relay station was determined. The radiating portions of the station were modeled using the Numerical Electromagnetic Code (NEC). Worst case interference models predict, based on the limited data available, that the relay station and the nearby airport-based equipments are not compatible. Recommendations for improving the quality and quantity of input data are made. It is anticipated that this would reduce the predicted interference margins to acceptable levels.			

41016-20

ABSTRACT

This report describes the results of a computer modeling investigation in which the interference to VHF and UHF communications/navigation equipments from a Voice of America HF relay station was determined. The radiating portions of the station were modeled using the Numerical Electromagnetic Code (NEC). Worst case interference models predict, based on the limited data available, that the relay station and the nearby airport-based equipments are not compatible. Recommendations for improving the quality and quantity of input data are made. It is anticipated that this would reduce the predicted interference margins to acceptable levels for some equipments.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	<i>on file</i>
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
<b>A</b>	

## TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT	iii
TABLE OF CONTENTS	v
LIST OF FIGURES	vii
A. THE PROBLEM	1
B. GIVEN DATA AND PARAMETERS	1
1. HF Relay Station (6 - 17 MHz)	1
2. Avionics Equipment	1
C. THE APPROACH	2
D. THE HF MODEL OF THE ARRAY	3
E. THE VHF MODEL OF THE ARRAY	3
F. THE TRANSMISSION LINE MODEL	3
G. GEOMETRY OF THE AIRPORT/ANTENNA FARM	4
H. PREDICTED INTERFERENCES	
1. HF Transmitter Emissions (-60 dB below output)	4
2. Interference Equation	5
3. Interference Margins	5
I. RECOMMENDATIONS	6

THE BDM CORPORATION

LIST OF FIGURES

<u>Figure Number</u>		<u>Page</u>
1a	NEC VERSUS TCI HF ARRAY MODEL	7
1b	NEC VERSUS TCI HF ARRAY MODEL	8
2	AIRPORT AND ANTENNA FARM	9



# THE BDM CORPORATION

## A. THE PROBLEM

The Voice of America is planning to locate an HF relay station a few miles from an international airport. Electromagnetic interference is a possibility because of the closeness of the airport communication/navigation equipments and the radiating portions of the relay station (the curtain antenna array and the open-wire transmission line). The out-of-band (VHF and UHF) radiation characteristics of the VOA HF system must be determined as part of an interference calculation. The NEC program, with acceptable limits, can provide that information. Once the radiated interference levels are predicted, they can be compared to acceptable interference levels established by the avionics users, providing margins of safety or interference.

## B. GIVEN DATA AND PARAMETERS

The following represent information provided by VOA, describing the HF site and the avionics interference criteria:

### 1. HF Relay Station (6 - 17 MHz)

Six 250 Kw AM transmitters; two transmitters diplexed into one 4 x 4 horizontal half-wave dipole curtain array (similar to a TCI 611), fed through 1,000 to 3,000 feet of 300 ohm, 4-conductor open-wire transmission lines. The spurious output level of each transmitter is at least -60 dB below rated output.

### 2. Avionics Equipment

The equipment listed below is located distances of from one to three miles from the HF relay station. The airport is at three miles, but the nearest approach of the flight path to the relay station is one mile.

Maximum acceptable interference levels, as established by the International Civil Aeronautics Organization (ICAO), as applicable to this scenario are, in dBW/M<sup>2</sup>:

# THE BDM CORPORATION

<u>Service</u>	<u>Level</u>
75 MHz VHF Marker	- 105.
120 MHz Aircraft ILS Localizer	- 136.8
120 MHz VOR	- 134.8
120 MHz Aircraft VHF Communications	- 136.2
120 MHz Ground VHF Communications	- 136.8
330 MHz Aircraft ILS Guide Path	- 116.8
1200 MHz Aircraft VOR/DME	- 102.

## C. THE APPROACH

Since a VHF/UHF (out-of-band) performance prediction is required for the antenna and transmission line, and was nonexistent at commencement of the study, a step-by-step plan was developed to go from the known HF characteristics of the radiating system to the unknown VHF/UHF performance.

These steps were followed:

1. A full-model of the HF array was developed using NEC; the results were compared to the TCI published patterns, validating the modeling process in-band.
2. A vertical and a horizontal "cell" of the array were modeled at HF. Array theory was applied to produce the full array performance, demonstrating the principle for later application at VHF/UHF.
3. The smaller "cell" models were then run on NEC at VHF/UHF to produce out-of-band characteristics for these workable-sized representations of the antenna system.
4. Expected full-array out-of-band characteristics were calculated from the above, applying the same array theory. This established radiation for the antenna array portion of the RF system of the relay station.
5. The transmission line was modeled as an explicit wire model on NEC allowing prediction of radiation from the line at VHF/UHF.
6. The contribution of total RF system radiation caused by the transmission line was then established for use in the interference assessment portion of the study.
7. The worst case signal levels produced by the VOA system were estimated from (4) and (6) above, and interferences noted.

## THE BDM CORPORATION

### D. THE HF MODEL OF THE ARRAY

The HF array was modeled using NEC. The radiation patterns which were produced were very close to the published predicted patterns from TCI. Figures 1a and 1b demonstrate a sample of the correlation of patterns. This validates the numerical model at HF and permits the next step: a model of a portion of the array at HF, later to be extended to VHF/UHF.

### E. THE VHF MODEL OF THE ARRAY

As with all numerical analysis, model sizes must be limited to those which are reasonable both from an economic and time standpoint. A good example of a system which cannot be fully extended from HF to VHF/UHF is the VOA curtain array. A full-blown analysis of any radiating system using the NEC program or any other similar model is limited in terms of wavelengths of extent of the structure. The in-band HF model was large but not excessive, however, the full model run at the lowest VHF frequency of interest would have proven excessive in computer resource consumption.

To bound the VHF/UHF radiation, a vertical and a horizontal four element "cell" was run and validated at HF, then exercised at VHF/UHF. The HF cell model agreed as expected with the full model. When run at VHF/UHF the vertical and horizontal cells yielded 8 dBi and 15 dBi gains respectively, resulting in:

$$\frac{8 + 15}{2} = 11.5 \text{ dBi peak gain for the array.}$$

The average gain was approximately -7.5 dBi.

### F. THE TRANSMISSION LINE MODEL

A 2000' long line was modeled (no bends were assumed) to determine the attenuation and radiation characteristics out-of-band at VHF/UHF. The attenuation per wavelength and total attenuation for a 2000' run were calculated

# THE BDM CORPORATION

and found to dominate the radiation from the line at lower frequencies. At UHF, radiation patterns were examined and found to produce 12 dBi peak and -7 dBi average gain. The following table summarizes the NEC modeling:

<u>Frequency</u>	<u>Attenuation /<math>\lambda</math></u>	<u>Total Attenuation (2000')</u>
75 MHz	0.04 dB	6 dB
120 MHz	0.045 dB	11 dB
330 MHz	0.06 dB	40 dB*
1200 MHz	2.2 dB	-- *

\* = Radiation Dominates (12 dBi peak/-7 dBi average)

## G. GEOMETRY OF THE AIRPORT/ANTENNA FARM

Figure 2 demonstrates that the lines of bearings for the VOA arrays (320°, 350° and 10° to 50°T) fairly well cover the airport runway and flight path. The closest distance to the flight path is one mile and the airport runway is at three miles. The worst case free space path loss calculated at one and three miles provides a range of possible values for interference calculations:

### FREE SPACE LOSS

	<u>75 MHz</u>	<u>120 MHz</u>	<u>330 MHz</u>	<u>1200 MHz</u>
at 1 mile	- 73 dB	- 78 dB	- 86 dB	- 97 dB
at 3 miles	- 83 dB	- 88 dB	- 96 dB	-107 dB

## H. PREDICTED INTERFERENCES

### 1. HF Transmitter Emissions (-60 dB below output)

With 250 KW per transmitter and two transmitter per antenna, three antennas per site, the range of emitted VHF/UHF power runs from:

0.25 watts (-6 dBW) to 3.0 watts (+5 dBW)

THE BDM CORPORATION

2. Interference Equation

$$S_{\text{Receiver}} = P_{\text{Transmitter}} + G_{\text{Antenna or Transmission Line}} - L_{\text{Free Space}} - L_{\text{Transmission Line}} + \underbrace{4\pi - \lambda^2}_{\text{Effective Aperture Factor}} \text{ dB}$$

where

S is Power Density,

P is Power,

G is Gain (radiation),

and L is Loss, all in decibels.

NOTE: Transmission line losses are actually long-wire type radiation losses or energy leakage along the line.

3. Interference Margins

When the interference power balance equation is exercised, considering ranges of values for some of the terms, the predicted range of received power densities is obtained. Comparing this to the allowable signal levels results in acceptable performance from an interference viewpoint, or from an interference margin (unacceptable).

The following limits are calculated for the conditions of one transmitter, three mile distance and average gains, as a best case and six transmitters, one mile distance and peak gains as the worst case. Thus, the values listed in the table cover the range of possible levels based on the limited data available at this time.

## THE BDM CORPORATION

Frequency Band MHz	Interference Margin dB
75	+11.5 to + 15.5
120	+37 to + 77
330	+10.5 to + 50.5
1200	-15.5 to + 24.5

### I. RECOMMENDATIONS

The rather dismal prospects for coexistence of the HF relay station and the airport avionics represent, to a large extent, quite limited information and the HF relay station components. If the following information is obtained, it is likely that the margins presented here can be reduced, and in some cases, made negative (safe operation).

1. The transmitter output spectrum from 75 - 1200 MHz might be well below the rated -60 dB. This should be ascertained.

2. The coupler/balun response has been neglected in this study, yet it must have out-of-band performance which would provide relief from the calculated signal levels.

3. No transmission line bends/corners were assumed. Since bends contribute substantially to out-of-band radiation, the details of the line layout are needed.


4. The HF array's feed harness is an unknown. For this worst case analysis, all elements were assumed to be such that VHF/UHF radiation from each element was in-phase at broadside, a highly unlikely situation. Feed harness details will enable out-of-band predictions which are more realistic.

5. The ICAO interference criteria did not match some of that provided by equipment manufacturers. This should be resolved and one clear set of criteria formed.

An alternate, and possible more easily obtained set of data, which would prove quite enlightening for this problem involves a ground-based and aerial field intensity survey of an existing VOA site, such as the one at Delano, California. A properly conducted survey could bracket expected levels of out-of-band interference and is recommended at this time.

V0A SRI LANKA CURTAIN ARRAY/TCI 611


ELEVATION PATT/PERF GND/ 8.00 MHZ



○ = (TCI Data -3 dB)

Figure 1a. NEC VERSUS TCI HF ARRAY MODEL

V0A SRI LANKA CURTAIN ARRAY/TCI 611  
AZ PATT/10 DEG EL ANG/PERF GND/8.00MHZ



○ = (TCI Data -3 dB)

Figure 1b. NEC VERSUS TCI HF ARRAY MODEL






Figure 2. AIRPORT AND ANTENNA FARM

THE BDM CORPORATION

INITIAL DISTRIBUTION LIST

	<u>DDAAD Code</u>	<u>No. of Copies</u>
1. Mr. Robin Simpson Administrative Contracting Officer Office of Naval Research Resident Rep. Stanford University, Room 165 Durond Aeronautics Building Stanford, CA 94305		1
2. Professor William E. Tolles Dean of Research, Code 012 Naval Postgraduate School Monterey, CA 93940	N62271	3
3. Library, Code 0212 Naval Postgraduate School Monterey, CA 93940		2
4. Director, Naval Research Laboratory Attn: Code 2627 Washington, D.C. 20375	N00173	6
5. Defense Documentation Center Cameron Station, Building 5 Alexandria, VA 22314	S47031	12
6. Associate Professor Stephan Jauregui Code 62Ja Naval Postgraduate School Monterey, CA 93940		5
7. Dr. Richard W. Adler Project Engineer The BDM Corporation Code 62 Naval Postgraduate School Monterey, CA 93940		5
8. International Communications Agency Code VOA/EPML Attn: Ray Ulrich Washington, D.C. 20547		5

**DATE**  
**ILME**