



Calhoun: The NPS Institutional Archive

DSpace Repository

Theses and Dissertations

1. Thesis and Dissertation Collection, all items

2007-06

Port security strategy 2012

Ames, Morgan; Chan, Chun Man; Chng, Kim Chuan; Cole, Andrew; Johnson, Dale; Kwai, Kiah Wen; Koh, Kim Leng; Lim, Horng; Lim, Thiow Yong; Liu, Yilei...

Monterey, California. Naval Postgraduate School

https://hdl.handle.net/10945/6921

Downloaded from NPS Archive: Calhoun



Calhoun is the Naval Postgraduate School's public access digital repository for research materials and institutional publications created by the NPS community. Calhoun is named for Professor of Mathematics Guy K. Calhoun, NPS's first appointed -- and published -- scholarly author.

> Dudley Knox Library / Naval Postgraduate School 411 Dyer Road / 1 University Circle Monterey, California USA 93943

http://www.nps.edu/library





Port Security Strategy 2012 SEA-11 Naval Postgraduate School TDSI National University of Singapore May 31, 2007



Port Security Strategy 2012 Team

TEMASEK DEFENCE SYSTEMS INSTITUTE

SEA-11 LCDR Joseph Torian LT Morgan Ames Mr. Henry Nguyen Mr. Horng Lim ENS Andrew Cole ENS Laura Okruhlik ENS Alan Marsh ENS Yilei Liu

Faculty Advisors Richard Williams, RADM (Ret.), USN Eugene Paulo, LTC (Ret.), USA

TDSI

Mr. Chun Man Chan MAJ Kim Chuan Chng LCDR Dale Johnson Mr. Kim Leng Koh MAJ Kiah Wen Kwai Mr. Thiow Yong Lim LT Claude McRoberts Mr. Chee Wan Ng Mr. Chee Wai Ng Mr. Min Yew Ng Ms. Pei Tze Oh Mr. Kar Leong Ong Mr. Lin Kiat Peh MAJ Wei Ting Soh MAJ Chee Leong Tan Mr. Leng Huei Toh MAJ Yi Jim Wong







1300-1310 Introduction 1310-1330 **Terrestrial Threats Group** 1330-1335 **Question Break #1** 1335-1355 **Regional Seaborne Threats Group** 1355-1400 **Question Break #2** 1400-1420 Source Seaborne Threats Group 1420-1425 **Question Break #3** 1425-1445 **Internal Personnel Threats Group** 1445-1500 **Question Break #4** 1500-1600 **Breakout Session in Bullard 100A**



Tasking Letter Meyer Institute of SE



- Design a conceptual system of systems to improve Port Security measures for U.S. ports, and Force Protection options for U.S. forces in U.S. and foreign ports.
- Potential focus areas:
 - Provide individual ship self protection
 - Integrate shipboard protection systems with shorebased systems
 - Integrate Allied and Navy vessels to commercial port security systems



Selected Documents



- Homeland Security Presidential Directive 13 (HSPD-13)
- National Strategy for Maritime Security
- International Outreach and Coordination Strategy
- International Ship & Port Facility Security Code and SOLAS Amendments 2002



SE Design Process

TEMASEK DEFENCE SYSTEMS INSTITUTE





Stakeholders Concerns

TEMASEK DEFENCE SYSTEMS INSTITUTE

- Land based
 - Attacks on infrastructure
- Sea based
 - Attack from local waterways
 - Attack via container from foreign ports
- Internal based
 - Attack via employee sabotage



Overall Effective Need



"To protect commercial and Allied shipping by deterring and denying potential terrestrial, seaborne, and internal threats."





Problem Decomposition

TEMASEK DEFENCE SYSTEMS INSTITUTE

- Terrestrial Threats
 Group
 - Threats from landside port perimeter
- Source Seaborne Threats Group
 - Threats from originating port

- Regional Seaborne Threats Group
 - Threats from seaside of in-port ship to port boundary
- Internal Personnel
 Threats Group
 - Threats from personnel at port facility





Terrestrial Threats Group

Andrew Cole – Group Lead Yi Wong – Deputy Lead MAJ Kim Chuan Chng MAJ Wei Ting Soh Mr. Leng Huei Toh Mr. Lin Kiat Peh



Terminal Operator's Greatest Concern



 Prevent a vehicle laden with explosives from gaining access to the ports facilities while keeping total life cycle cost and impact on normal port operations to a minimum.



Terrestrial Threats Group Scenario



 A Container truck laden with explosives attempts to gain access to a terminal in a major U.S. port by speeding past the security guard at the terminal' s entrance.













Terrestrial Threats Group Alternatives

TEMASEK DEFENCE SYSTEMS INSTITUTE



17



Key Findings



- Each port terminal needs to assess its vulnerability to a vehicular IED attack
- Perimeter fencing should be hardened before gate security improvements are made
- In our study, an armed guard was not cost effective
- Physical barriers are more effective than armed guards.
- Pop-Up Barriers with staggered concrete blocks before the barrier and at least 300' between the guardhouse and barrier provide the best effectiveness.



Terrestrial Threats Group Modeling



The effect of staggered concrete blocks to slow incoming vehicles

3 levels: No blocks, blocks before guardhouse, and blocks before barrier

 The effect of the distance between the guard house and the barrier

5 levels: 100', 300', 500', 700', and 900'



Terrestrial Threats Group Metrics



System Effectiveness

1-(Number Successful Attacks)/(Number Attempted Attacks)

	FLVAL DEAR SIL		
	Modeling Tool	Input Parameters	MOEs Obtained
Deny	Arena	 Obstacle Delay Barrier Delay Security Zone Delay Report Delay Reliability Effectiveness 	1. System Effectiveness



Terrestrial Threats Group Modeling Replication Parameters



Modeled in Arena

50 alternative permutations considered

 34,680 simulated attacks ran against each permutation

(120 days with 289 attempted attacks per day)



Terrestrial Threats Group Model

TEMASEK DEFENCE SYSTEMS INSTITUTE





Terrestrial Threats Group Modeling Results







Terrestrial Threats Group Modeling Results



Alternative	Maximum Effectiveness	Configuration		
Status Quo	0%	N/A		
Pop-Up Barriers	95%	300'+, Blocks Before Barrier		
Spike Strips	47%	900', Blocks Before Guardhouse		
Armed Guard	16%	500', Blocks Before Guard		



Terrestrial Threats Group Cost Estimation



Alternative	Anticipated Annual Lifecycle Cost (FY07\$)				
Status Quo	0				
Pop-Up Barriers	37,100				
Spike Strips	15,656				
Armed Guard	36,365				



Terrestrial Threats Group Cost Benefit Analysis



Overall Cost V Effectiveness



26



Terrestrial Threats Group Dominance



Overall Cost V Effectiveness





Terrestrial Threats Group Conclusions



 Each port terminal needs to assess its vulnerability to a vehicular IED attack

 Perimeter fencing should be hardened before gate security improvements are made



Terrestrial Threats Group Conclusions



 Pop-Up Barriers with staggered concrete blocks before the barrier and at least 300' between the guardhouse and barrier provide the best effectiveness

In our study, an armed guard was not cost effective

REPTRI



Terrestrial Threats Group Recommended Future Study

TEMASEK DEFENCE SYSTEMS INSTITUTE

- At gate screening for incoming vehicles. Study the effectiveness at preventing vehicular IEDs and the impact that additional screening would have on commerce.
- Additional screening for imported containers. Study the effectiveness for different screening methods and the impact that the screening would have on commerce. Possible collaboration Sandia National Laboratories.





Regional Seaborne Threats Group

LT Morgan Ames – Group Lead Mr. Thiow Yong Lim - Deputy Lead Mr. Chee Wai Ng Mr. Chee Wan Ng Mr. Kim Leng Koh Mr. Chun Man Chan



Pier-side Ships' Greatest Concerns



 To increase port waterside readiness prior to terrorist attack while carrying on day to day port operations by detecting, tracking and employing appropriate courses of action.



Options:

Regional Seaborne Group Modeling Scenario



- Small boat attacks (SWARM)
- Large ship collision
- Swimmer attack
- RPG attack

Stakeholders' Conclusion: Small boat attack scenario

Scenario:

Multiple small boats attack container terminal from different threat axis to inflict the most damage to moored ships and to the terminal. Desire of the terrorist is to inflict physiological damage and render the port facilities inoperable for a period of time.



Regional Seaborne Group Alternatives Generation



• Current "As Is" configuration:

- 1 Helo
- 4 Patrol craft
- 1 Radar

Increase detection capability by adding:

- Shore based Assets:
 - Radars, EO/IR Sensors, Sonars and Buoys

 E.g. Thermo Vision Sentry II
- Mobile Assets:
 - USV



Regional Seaborne Group Alternatives Configuration

TEMASEK DEFENCE SYSTEMS INSTITUTE

35

Sensor Configuration Type of Sensor Platform	(A) Current	(B) (A) + USV	(C) (B) + 1 Radar	(D) (B) + 2 Radars	(E) (D) + SentryII	(F) (E) + Sentinel	(G) (F) + Buoys + Sonars
1 x Helo	>	~	<	>	<	<	>
4 x Patrol Craft	>	~	~	~	<	>	>
1 x Radar Configuration (Existing)	>	✓					>
2 x Radar Configuration			~				~
3 x Radar Configuration				~	~	~	~
2 x Unmanned Surface Vessels (USV)		~	~	~	✓	✓	>
2 x ThermoVisionSentryII					~	~	>
5 x ThermoVisionSentinel						~	>
2 x Networked Sensor (Buoys)							>
5 x Active OmniDirectional Sonar							~
4 x High Frequency Tactical Sonar							~


Regional Seaborne Group Key Findings



Most Effective:

1 x Helicopter 4 x Patrol Craft 1x Radar 2 x Radar 2 x USV 2 x Thermo Vision Sentry II

- Cost: \$21,312,000
- There needs to be:
 - network of sensors for port security
 - data fusion center
- Provide increased <u>AWARENESS</u>, increased port security



Regional Seaborne Group Modeling Metrics



• <u>MOE: Terrorist Infiltration</u> – MOP: Infiltration rate

MOE: Target Detection

 MOP: Detection rate

4	Modeling Tool	Input Parameters	MOEs Obtained
Protect	Simkit	 Number and type of sensors Number of terrorists 	 Target Detection Terrorist Infiltration



Regional Seaborne Group Modeling Tools



- Discrete Event Simulation
 - Event driven paradigm
 - Modeling of complex dynamic system
 - MOVES Simkit
 - Maneuvering Models
 - Sensor Models
 - Cookie-cutter
 - With detection and not detection



Regional Seaborne Group Model Design and Implementation

- Port Security Local Waterside Simulation Application
 - Create Threats behavior
 - Create Sensor (basic) behavior
 - Create Scenario for different alternatives
 - Collection of results
 - Analysis of results
 - Recommendation of Alternatives



Regional Seaborne Group Flow Chart

TEMASEK DEFENCE SYSTEMS INSTITUTE

Port Security - Local Waterside - Small Boat Procedure Flow Chart





Regional Seaborne Group Discrete Events





Regional Seaborne Group Discrete Events





Regional Seaborne Group Model Inputs

TEMASEK DEFENCE SYSTEMS INSTITUTE



🛃 Scenario Controller

		-
	Generate Stats	
Replications: 30	Visual Simulation	1: 🖌
Sensors Terrorist		
	Helo 1: 🗹 Highl	requencyTacticalSonar 1
Pat	rolCraft 1: 🗹 Highl	requencyTacticalSonar 2
Pat	rolCraft 2: 🗹 Highl	requencyTacticalSonar 3
Pat	rolCraft 3: 🔽 Highf	requencyTacticalSonar 4
Pat	rolCraft 4: 🔽	ThermoVisionSentryll 1
ThermoVision	Sentinel 1: 🔽	ThermoVisionSentryll 2
ThermoVision	Sentinel 2: 🔽	NetworkedSensor
ThermoVision	Sentinel 3: 🔽	NetworkedSensor 2
ThermoVision	Sentinel 4:	Radar
ThermoVision	Sentinel 5:	Radar 2
ActiveOmniDirection	alSonar 1:	Dadar 3
ActiveOmniDirection	alSonar 2: 14	
ActiveOmmDirection		USV
ActiveOmnibirection	alsonar 5: 🔽	050
ActiveOmniDirection	alSonar 4: 🗹	
ActiveOmniDirection	alSonar 5: 🗹	



Regional Seaborne Group Modeling Assumptions



- Homeland security level
 - Normal
- Focus is on small boat attacks
 - Threats come from within the San Francisco Bay, and originate from designated areas
 - Small boats travel at 30kts
 - Not considering air threats or threats from swimmers

Sensor Assets

- Placement of static sensors
- Routes for mobile sensors
- Search pattern follows detect-classify-recognize-identify algorithm
- False Alarm Rate not modeled



Regional Seaborne Group Model Area





Regional Seaborne Group Routes





Regional Seaborne Group Sensor Placement





Regional Seaborne Group Limitations of the Model



- Model focuses on the detection of terrorist small boats. A successful detection means
 - Terrorist fails in mission
 - Terrorist is deterred
- Sensor Characteristics
 - Sensors follow a detect-classify-recognize-identify algorithm that takes 3 mins for each stage of the process (in Simulation time)
 - Sensors can only perform target detection-classification for a single platform at any one time.
- SimKit only implements type Point2D
 - Subsurface detection, e.g. sonars may not be modeled accurately.
 - Diskit, which is able to implement Point3D, has stability issues, hence not used.



Regional Seaborne Group Results

TEMASEK DEFENCE SYSTEMS INSTITUTE



F + Buoys + Sonar Infiltration/Detection Rate for (G) Configuration

49



Regional Seaborne Group Results of the Modeling

TEMASEK DEFENCE SYSTEMS INSTITUTE

Terrorist Detection Rate



50



Regional Seaborne Group Cost Estimation



Configuration	\$FY07M Cost	\$FY18M Cost
А	4.14	41.4
В	14.64	76.4
С	17.89	83.9
D	21.14	91.4
E	21.31	91.48
F	21.45	91.96
G	46.65	133.96

**PROTECTOR USV used cost FY07 \$3.5 million **



Regional Seaborne Group Cost Benefit Analysis





Regional Seaborne Group Cost Benefit Analysis





RSTG Recommendation Revisited



Most Effective: 1 x Helicopter
 4 x Patrol Craft
 1x Radar
 2 x Radar
 2 x USV
 2 x Thermo Vision Sentry II

Cost: \$21,312,000
Without USVs: \$11,312,000



Regional Seaborne Group Conclusions



- Layered sensors are the most sure way to prevent a terrorist attack
- Implementation of a Data fusion center.
- Sharing of information and awareness are key attributes for port security
- Products exist such as: Hawkeye, Project Athena, and HarborGuard. Provides sensors as well as C2 platform for fusion center.



Regional Seaborne Group Recommended Future Study

- Since RSTG examined the prevent aspect the engagement problem still remains
- Did not look into a single sensor having the ability to track multiple crafts
- Examine and implement the air threats and intelligence aspects into Port security
- Address the false alarm issue





Source Seaborne Threats Group

LCDR Dale Johnson - Group Lead Ms. Pei Tze Oh – Deputy Lead Mr. Horng Lim ENS Alan Marsh ENS Laura Okruhlik



Source Seaborne Group Effective Need



- Design a system to detect and deny all containers holding undesired cargoes from loading onto a container ship.
 - Undesired cargoes are defined as:
 - chemical agents
 - biological agents
 - radiological material
 - explosives
 - conventional weapons
 - weapon system parts
 - human cargo
 - Containers enter the source port via:
 - railway
 - vehicle (trucks)
 - transshipment (berthed ships)



Source Seaborne Group Scenario Objectives



Good guys

 Detect and deny all WMD at the source port



This truck has 1.5 kg of high Atomic number material hidden in a motor. Even with a zoom the operator can't find it. But a dual energy algorithm can detect it easily with extremely low false alarms.

Contact Varian for more information about dual energy and the Linatron K9 dual energy accelerator Bad guys

 Get at least one container with WMD to each destination port





Source Seaborne Group Detection Capability Metrics



- Analysis Questions of Interest
 - Comparison of Alternatives
 - Optimal Sensor Mix to maximize Pd

MOE: Accuracy

- MOP: Probability of Detection
- MOP: Missed Detection
- MOP: False Alarm Rate
- MOE: Timeliness
 - MOP: Productivity
 - MOP: Average inspection time per container

	Modeling Tool	Input Parameters	MOEs Obtained
Deny	Extend	 Container Traffic Sensor Performance 	 Accuracy Timeliness
	REPUBLIC	S. Cher Content	





System	Manifest Screening	Scanning Location	Non-Intrusive Container Screening	% Screening	Intrusive Container Screening	Screening requirements	Data Sharing
Reference System	None	None	None	0%	None	None	None
0% inspection	ATS (status quo)	Mobile system	Gamma ray scanners	5%	Human	Containers that don't pass the non- intrusive inspection	Smart Tags
100% Inspection (100% of containers)	ATS+ (shippers submit manifests to ATS system 24 hours before ship loading)	On crane spreaders	X-ray scanners	25%	Animals	Random (fixed percentage)	Upload container screening data to destination port
Improved loading search		Fixed entry point with truck drive-through	Operator experience	50%	Portable Radiation Detectors	Containers tagged high risk by manifest screening	
Minimize port operations disruption			Trained animals	75%	Remotely-operated inspection robots	100%	
High Performance			Radiation detectors	100%			
100% Intrusive Inspection		F 1/ 10 1// 1 . 5 4	Scales				





Manifest Screening	Scanning Location	Non-Intrusive Container Screening	% Screening	Intrusive Container Screening	Screening requirements	Data Sharing
None	None	None	0%	None	None	None
ATS (status quo)	Mobile system	Gamma ray scanners	5%	Human	Containers that don't pass the non- intrusive inspection	Smart Tags
ATS+ (shippers submit manifests to ATS system 24 hours before ship loading)	On crane spreaders	X-ray scanners	25%	Animals	Random (fixed percentage)	Upload container screening data to destination port
	Fixed entry point with truck drive-through	Operator experience	50%	Portable Radiation Detectors	Containers tagged high risk by manifest screening	
		Trained animals	75%	Remotely-operated inspection robots	100%	
		Radiation detectors	100%			
1012	I U D H I MAD	Scales				
	Manifest Screening None ATS (status quo) ATS+ (shippers submit manifests to ATS system 24 hours before ship loading)	Manifest ScreeningScanning LocationNoneNoneATS (status quo)Mobile systemATS + (shippers submit manifests to ATS system 24 hours before ship loading)On crane spreadersFixed entry point with truck drive-throughFixed entry point with truck drive-through	Manifest ScreeningScanning LocationNon-Intrusive Container ScreeningNoneNoneNoneATS (status quo)Mobile systemGamma ray scannersATS (status quo)Mobile systemGamma ray scannersATS + (shippers submit manifests to ATS system 24 hours before ship loading)On crane spreadersX-ray scannersFixed entry point with truck drive-throughOperator experienceImage: Application of the systemImage: Application of the systemATS + (shippers submit manifests to ATS system 24 hours before ship loading)Image: Application of the systemImage: Application of the system <t< td=""><td>Manifest ScreeningScanning LocationNon-Intrusive Container Screening% ScreeningNoneNone0%Arnophic Status quo)Mobile systemGamma ray scanners5%ArtS (status quo)Mobile systemGamma ray scanners5%ArtS+ (shippers submit manifests to ATS system 24 hours before ship loading)On crane spreadersX-ray scanners25%Fixed entry point with truck drive-throughOperator experience50%50%Fixed entry point with truck drive-throughTrained animals75%Image: ScalesImage: Scales100%</td><td>Manifest ScreeningScanning LocationNon-Intrusive Container Screening% ScreeningIntrusive Container ScreeningNoneNoneNone0%NoneATS (status quo)Mobile systemGamma ray scanners5%HumanATS (status quo)Mobile systemGamma ray scanners5%AnimalsATS (status quo)On crane spreadersX-ray scanners25%AnimalsSystem 24 hours before ship loading)Fixed entry point with truck drive-throughOperator experience50%Portable Radiation DetectorsFixed entry point with truck drive-throughTrained animals75%Remotely-operated inspection robotsIntrusive ScalesIntrusive Container100%Intrusive ScalesIntrusive Scales</br></td><td>Manifest ScreeningScanning LocationNon-Intrusive Container Screening% ScreeningIntrusive Container ScreeningScreeningNoneNoneNone0%NoneNoneATS (status quo)Mobile systemGamma ray scanners5%HumanContainers that don't pass the non- intrusive inspectionATS (status quo)Mobile systemGamma ray scanners25%AnimalsRandom (fixed percentage)ATS (status quo)On crane spreadersX-ray scanners25%AnimalsRandom (fixed percentage)ATS + (shippers submit manifests to ATS system 24 hours before ship loading)On crane spreadersX-ray scanners25%AnimalsRandom (fixed percentage)ATS + (shippers submit manifest sto ATS system 24 hours before ship loading)On crane spreadersX-ray scanners25%AnimalsRandom (fixed percentage)ATS + (shippers submit manifest sto ATS system 24 hours before ship loading)On crane spreadersX-ray scanners25%AnimalsRandom (fixed percentage)ATS + (shippers submit manifest screeningOperator experience50%Portable Radiation DetectorsContainers tagged high risk by manifest screeningATS + (shippers submit manifest screeningTrained animals75%Remotely-operated inspection robots100%ATS + (shippers submit manifest screeningScales100%Interviewe high risk by manifest screening</td></t<>	Manifest ScreeningScanning LocationNon-Intrusive Container Screening% ScreeningNoneNone0%Arnophic Status quo)Mobile systemGamma ray scanners5%ArtS (status quo)Mobile systemGamma ray scanners5%ArtS+ (shippers submit manifests to ATS system 24 hours before ship loading)On crane spreadersX-ray scanners25%Fixed entry point with truck drive-throughOperator experience50%50%Fixed entry point with truck drive-throughTrained animals75%Image: ScalesImage: Scales100%	Manifest ScreeningScanning LocationNon-Intrusive Container Screening% ScreeningIntrusive Container ScreeningNoneNoneNone0%NoneATS (status quo)Mobile systemGamma ray scanners5%HumanATS (status quo)Mobile systemGamma ray scanners5%AnimalsATS (status quo)On crane spreadersX-ray scanners25%AnimalsSystem 24 hours before ship loading)Fixed entry point with truck drive-throughOperator experience50%Portable Radiation DetectorsFixed entry point with truck drive-throughTrained animals75%Remotely-operated inspection robotsIntrusive ScalesIntrusive Container100%Intrusive ScalesIntrusive 	Manifest ScreeningScanning LocationNon-Intrusive Container Screening% ScreeningIntrusive Container ScreeningScreeningNoneNoneNone0%NoneNoneATS (status quo)Mobile systemGamma ray scanners5%HumanContainers that don't pass the non- intrusive inspectionATS (status quo)Mobile systemGamma ray scanners25%AnimalsRandom (fixed percentage)ATS (status quo)On crane spreadersX-ray scanners25%AnimalsRandom (fixed percentage)ATS + (shippers submit manifests to ATS system 24 hours before ship loading)On crane spreadersX-ray scanners25%AnimalsRandom (fixed percentage)ATS + (shippers submit manifest sto ATS system 24 hours before ship loading)On crane spreadersX-ray scanners25%AnimalsRandom (fixed percentage)ATS + (shippers submit manifest sto ATS system 24 hours before ship loading)On crane spreadersX-ray scanners25%AnimalsRandom (fixed percentage)ATS + (shippers submit manifest screeningOperator experience50%Portable Radiation DetectorsContainers tagged high risk by manifest screeningATS + (shippers submit manifest screeningTrained animals75%Remotely-operated inspection robots100%ATS + (shippers submit manifest screeningScales100%Interviewe high risk by manifest screening





System	Manifest Screening	Scanning Location	Non-Intrusive Container Screening	% Screening	Intrusive Container Screening	Screening requirements	Data Sharing
Reference System	None	None	None	0%	None	None	None
0% inspection	ATS (status quo)	Mobile system	Gamma ray scanners	5%	Human	Containers that don't pass the non- intrusive inspection	Smart Tags
100% Inspection (100% of containers)	ATS+ (shippers submit manifests to ATS system 24 hours before ship loading)	On crane spreaders	X-ray scanners	25%	Animals	Random (fixed percentage)	Upload container screening data to destination port
Improved loading search		Fixed entry point with truck drive-through	Operator experience	50%	Portable Radiation Detectors	Containers tagged high risk by manifest screening	
Minimize port operations disruption			Trained animals	75%	Remotely-operated inspection robots	100%	
High Performance			Radiation detectors	100%			
100% Intrusive Inspection			Scales				





System	Manifest Screening	Scanning Location	Non-Intrusive Container Screening	% Screening	Intrusive Container Screening	Screening requirements	Data Sharing
Reference System	None	None	None	0%	None	None	None
0% inspection	ATS (status quo)	Mobile system	Gamma ray scanners	5%	Human	Containers that don't pass the non- intrusive inspection	Smart Tags
100% Inspection (100% of containers)	ATS+ (shippers submit manifests to ATS system 24 hours before ship loading)	On crane spreaders	X-ray scanners	25%	Animals	Random (fixed percentage)	Upload container screening data to destination port
Improved loading search		Fixed entry point with truck drive-through	Operator experience	50%	Portable Radiation Detectors	Containers tagged high risk by manifest screening	
Minimize port operations disruption			Trained animals	75%	Remotely-operated inspection robots	100%	
High Performance			Radiation detectors	100%			
100% Intrusive Inspection			Scales				





System	Manifest Screening	Scanning Location	Non-Intrusive Container Screening	% Screening	Intrusive Container Screening	Screening requirements	Data Sharing
Reference System	None	None	None	0%	None	None	None
0% inspection	ATS (status quo)	Mobile system	Gamma ray scanners	5%	Human	Containers that don't pass the non- intrusive inspection	Smart Tags
100% Inspection (100% of containers)	ATS+ (shippers submit manifests to ATS system 24 hours before ship loading)	On crane spreaders	X-ray scanners	25%	Animals	Random (fixed percentage)	Upload container screening data to destination port
Improved loading search		Fixed entry point with truck drive-through	Operator experience	50%	Portable Radiation Detectors	Containers tagged high risk by manifest screening	
Minimize port operations disruption			Trained animals	75%	Remotely-operated inspection robots	100%	
High Performance			Radiation detectors	100%			
100% Intrusive Inspection		F 11 D 1/1 1 4	Scales				





System	Manifest Screening	Scanning Location	Non-Intrusive Container Screening	% Screening	Intrusive Container Screening	Screening requirements	Data Sharing
Reference System	None	None	None	0%	None	None	None
0% inspection	ATS (status quo)	Mobile system	Gamma ray scanners	5%	Human	Containers that don't pass the non- intrusive inspection	Smart Tags
100% Inspection (100% of containers)	ATS+ (shippers submit manifests to ATS system 24 hours before ship loading)	On crane spreaders	X-ray scanners	25%	Animals	Random (fixed percentage)	Upload container screening data to destination port
Improved loading search		Fixed entry point with truck drive-through	Operator experience	50%	Portable Radiation Detectors	Containers tagged high risk by manifest screening	
Minimize port operations disruption			Trained animals	75%	Remotely-operated inspection robots	100%	
High Performance			Radiation detectors	100%			
100% Intrusive Inspection			Scales				





System	Manifest Screening	Scanning Location	Non-Intrusive Container Screening	% Screening	Intrusive Container Screening	Screening requirements	Data Sharing
Reference System	None	None	None	0%	None	None	None
0% inspection	ATS (status quo)	Mobile system	Gamma ray scanners	5%	Human	Containers that don't pass the non- intrusive inspection	Smart Tags
100% Inspection (100% of containers)	ATS+ (shippers submit manifests to ATS system 24 hours before ship loading)	On crane spreaders	X-ray scanners	25%	Animals	Random (fixed percentage)	Upload container screening data to destination port
Improved loading search		Fixed entry point with truck drive-through	Operator experience	50%	Portable Radiation Detectors	Containers tagged high risk by manifest screening	
Minimize port operations disruption			Trained animals	75%	Remotely-operated inspection robots	100%	
High Performance			Radiation detectors	100%			
100% Intrusive Inspection			Scales				



Key Findings



- Best alternative High Performance
 - Automatic Targeting System (Improved)
 - Gamma scanner and HAZMAT detector at container holding and loading areas
 - Fully equipped inspection station
 - US 2007 \$82.67 million
- Optimal sensor mix to maximize Pd
 - Gamma scanner at port of entry
 - Radiation detector, gamma scanner at holding area
 - Scales, gamma scanner at loading area
 - Gamma scanner, HAZMAT detector, and trained animals at intrusive inspection station





Modeling & Simulation

All models are wrong, but some models are useful. George Box

REPUBLICS

69



Source Seaborne Group What the Model...



IS...

- A tool to compare relative performance of alternatives
- A high level abstraction of many factors that could drive MOPs
- An experiment to identify the most significant factors

IS NOT...

- A detailed simulation of actual port processes
- A prediction of real life performance of various inspection configurations



Source Seaborne Group **Extend Model**

TEMASEK DEFENCE SYSTEMS INSTITUTE

Container Screening 22 May.mox

۲

Run

•






Source Seaborne Group Derivation of Port Statistics



 Based on traffic data of world's biggest transhipment hub, PSA Singapore

- Annual Container Traffic

 22.3m TEUs transhipment
 23.2m TEUs total
- Daily vessel traffic
 60 ships
- Facilities
 - 4 terminals, 41 berths, 131 quay cranes



Source Seaborne Group Design Of Experiments



- Analysis of Alternatives
 - 6 different alternative configurations
- Optimal Sensor Mix
 - 17 different sensor configuration parameters
 - Full factorial testing requires 2¹⁷ runs = 131072 = runs
 - Extended Nearly Orthogonal Latin Hypercube
 - Efficient space filling properties: Cover total experiment space with minimum sample points
 - Reduce total runs from 131072 runs to 65 runs





Analysis of Alternatives





Source Seaborne Group Raw Score of Alternatives



Alternative	Prob of Detection	Missed Detection Rate	False Alarm Rate	Good Productivity [Containers per hour]	Change in Productivity Relative to Status Quo [%]	Avg Insp Time Per Container [min]
Status Quo	13.9%	86.1%	0.3%	159	NA	34
100% Vol Inspection	81.6%	18.4%	0.2%	161	1.4%	27
Improved Loading Search	83.8%	16.2%	0.2%	153	-3.7%	33
Min Port Operation Disruption	0.0%	100.0%	0.0%	165	3.6%	19
High Performance	96.8%	3.2%	2.5%	143	-9.8%	37
100% Intrusive Inspection	99.7%	0.3%	28.8%	10	-93.7%	28



Source Seaborne Group Utility Ranking & Cost Estimation



Alternative	Utility Score	Cost (US 2007 \$ million)
100% Intrusive Inspection	47.09	62.1
Status Quo	59.37	97
Minimize Port Operations Disruption	60.64	63
Improved Loading Search	87.61	159.1
100% Volume Inspection	88.72	111
High Performance	90.57	82.7
REPUBLICS		7



Source Seaborne Group Cost Benefit Analysis

TEMASEK DEFENCE SYSTEMS INSTITUTE

Cost vs Utility Score of Alternatives







78

Optimal Sensor Mix for Pd

Regression Analysis



Source Seaborne Group Logistic Regression Model



- Purpose of Logistic Regression Model
 - Determine significant factors that influence Pd
 - Predict Pd for sensor configurations that were not modeled
- Pd converted to binary response variable
 - Dirty Container detected = 1
 - Dirty Container not detected = 0
- Logistic regression model with logit link function used to fit data.
 - Saturated Model assumes all factors are significant in influencing Pd



Ar

Source Seaborne Group **Logistic Regression Model**



Leaend		Df	Sum of Sq	Mean Sq	F Value	Pr(F)	Significant
e: Land Entry Point	eScales	1	0.03	0.03	1.06	0.3026	No
h: Transhinment	eAnimals	1	0.05	0.05	1.61	0.2044	No
Holding Area	eRadDetector	1	0.00	0.00	0.06	0.8118	No
i: Intrusive Inspection	eGammaScanner	1	0.38	0.38	12.30	0.0005	Yes
Team	hRadDetector	1	0.86	0.86	27.95	0.0000	Yes
• c: Crane (Loading)	hGammaScanner	1	17.54	17.54	568.30	0.0000	Yes
	iAnimals	1	14.56	14.56	471.60	0.0000	Yes
Mehrer	iRadDetector	1	1.68	1.68	54.58	0.0000	Yes
Stall.	iGammaScanner	1	22.09	22.09	715.81	0.0000	Yes
 Analysis Method Significance of Regressors 	iBioDetector	1	1.34	1.34	43.56	0.0000	Yes
	iChemDetector	1	0.91	0.91	29.50	0.0000	Yes
	cScales	1	0.00	0.00	0.05	0.8293	No
Type III Sums of	cRadDetector	1	0.00	0.00	0.05	0.8155	No
Squaree	cGammaScanner	1	32.89	32.89	1065.55	0.0000	Yes
Squares	ATS	1	0.33	0.33	10.57	0.0012	Yes
DDD	Entry Scan %	1	0.20	0.20	6.40	0.0114	Yes
	Intrusive Insp Random Selection %	1	0.05	0.05	1.70	0.1927	No



Source Seaborne Group Logistic Regression Model



- Subset Model Selection
 - stepAIC
 - Backwards elimination algorithm for finding best subset model
 - Mallow's Cp
 - Criteria for "best" subset model selection
- Factors NOT important to determining Pd
 - Land Entry Point: Scales, trained Animals, radiation detector
 - Crane: Radiation detector
 - Random selection percentage for intrusive inspection



Source Seaborne Group Logistic Regression Model



Gamma scanners most Significant contribution to Pd

Legend

- e: Land Entry
 Point
- h: Transhipment Holding Area
- i: Intrusive
 Inspection Team
- c: Crane (Loading)
- 0: Sensor OFF

Detected

1: Sensor ON

Interval Plot of Detected vs eGamma, hGamma, iGamma, cGamma 95% CI for the Mean







83

Optimal Sensor Mix for Pd

Partition Analysis



Source Seaborne Group Partition Tree: Pd



1: Sensor ON

TEMASEK DEFENCE

SYSTEMS

INSTITUTE



Source Seaborne Group Partition Tree: Pd



- Most Significant Factors for <u>minimum</u> Pd
 - Mean 31.4%
 - Crane Gamma scanner (off)
 - Holding area Gamma scanner (off)

AMERICANTER

- Most Significant Factors for <u>maximum</u> Pd
 - Mean 95.4%
 - Crane Gamma scanner (on)
 - Intrusive Insp Team
 Gamma Scanner (on)
 - Intrusive Insp Team Trained Animals (on)



Source Seaborne Group Partition Tree: Pd



Most Significant Factors

- Gamma scanners at various locations
- Locations in descending preference
 - Crane, holding area and intrusive inspection team
- Trained Animals a good supplement to increase Pd

Source Seaborne Group Partition Tree: False Alarm Rate (FAR)

TEMASEK DEFENCE SYSTEMS INSTITUTE

- Most Significant Factors for minimum FAR
 - Mean 0.22%
 - Intrusive Insp Team
 Gamma Scanner (off)
 - Intrusive Insp Team Chemical Detector (off)
 - Intrusive Insp Team Biological Detector (off)

- Most Significant Factors for <u>maximum</u> FAR
 - Mean 0.43%
 - Intrusive Insp Team Gamma Scanner (on)
 - ATS Current, ATS Improved
 - Crane Scales (on)



Source Seaborne Group Partition Tree: Productivity



- Most Significant Factors for <u>minimum</u> Productivity
 - Mean 151 containers per hour
 - Intrusive Insp Team Random selection percentage >= 8%
 - ATS Current, ATS Improved
 - Crane Scales (on)

- Most Significant Factors for <u>maximum</u> Productivity
 - Mean 163 containers per hour
 - Intrusive Insp Team Random selection percentage < 8%
 - Intrusive Insp Team Gamma Scanner (off)

Source Seaborne Group Partition Tree: Avg Inspection Time

TEMASEK DEFENCE SYSTEMS INSTITUTE

- Most Significant Factors for <u>minimum</u> Avg Inspection Time
 - Mean 29.6min
 - No ATS
 - Holding Area Gamma Scanner (off)

- Most Significant Factors for <u>maximum</u> Avg Inspection Time
 - Mean 44.9min
 - ATS Current, ATS Improved
 - Intrusive Insp Team Random selection percentage >= 0.07
 - Crane Gamma scanner (on)



Source Seaborne Group

TEMASEK DEFENCE SYSTEMS INSTITUTE

- Partitioning Analysis Recommendations
- Recommended Sensor Suite to optimize multiple MOPs
 - Gamma detectors
 - Crane, holding area, intrusive inspection teams
 - Trained animals complementary
 - No ATS risk profiling
 - Intrusive inspection random selection < 8%
 - Not deploying crane scales
- Estimated Performance
 - Average probability of detection of 90%
 - Average false alarm rate of 2.77%
 - Average productivity of 161 containers per hour
 - Average inspection time per container of 32.6 minutes





Conclusions and Recommendations





Source Seaborne Group Conclusions



- Source port and transit security is still in the infancy stage and providing an adequate security solution is a global problem.
- Large transshipment hubs pose additional security risks from cargo arriving by ship from less secure ports.
- False alarm rate is directly proportional to number of sensors in system and can negatively impact port operations and productivity.
- The number of inspection teams should be sufficient to handle the false alarms and volume of containers randomly selected for inspection.



Source Seaborne Group Recommendations



- Best alternative High Performance
 - Automatic Targeting System+
 - Gamma scanner and HAZMAT detector at container holding and loading areas
 - Fully equipped inspection station
 - US 2007 \$82.67 million



Source Seaborne Group Recommended Future Study

TEMASEK DEFENCE SYSTEMS INSTITUTE

- Conduct detailed analysis on manifest screening and random selection percentages on port operations and ability to detect undesired cargos
- Review security vulnerabilities in transshipment process
- Improve accuracy in modeling port operations and sensors
- Scenarios of interest
 - UAV attack on container ship in transit close to source or destination port
 - Sinking of large container ship over Hampton Roads Bay Bridge tunnel, while 4 carriers are in port





Internal Personnel Threats Group

Mr. Henry Nguyen – Group Lead LT Claude McRoberts – Deputy Lead MAJ Chee Leong Tan Mr. Min Yew Ng Mr. Kar Leong Ong MAJ Kiah Wen Kwai



Internal Personnel Group Effective Need



To prevent insiders from committing or supporting terrorist acts within/ through port facilities

- By: 1. Minimizing impact to current operations
- 2. Deterrence
- 3. Control access to information and to physical
 - locations
- 4. Respond if necessary



Internal Personnel Group Scenario



<u>Concept 1</u>: A disgruntled port terminal employee attempt to smuggle in explosives to cause damage to terminal infrastructures and prevent port operation.

<u>Concept 2</u>: Port terminal employee gain unauthorized access to electronics data to be used in support of planning and executing terrorist attacks.



Key Findings



- Combined scenarios with involving data access control, physical access control, and response implementing maximum alternative solutions were able to achieve an 18% improvement.
- By implementing metal detector, bag scanner, improved training, random searches, and improved communications can improve physical security by 194%.
- Additionally, if a mid-terminal fence is added and the gates are triggered shut upon intruder detection a total physical security improvement of 441% can be achieved.



Internal Personnel Group Alternatives for Modeling



- •Deterrence
- Physical Access Control
 - •Status Quo
 - Random searches
 - Metal detector & bag scanner
 - Training for guards
 - Mid-terminal fence (gate open/shut)
- Data Access Control
 - Two-factor authentication
- Response
 - Improved communication



Internal Personnel Group Metrics & Models



	MOEs	Input Parameters	Model
Deter	1. Probability of deterrence	 Probability of interdiction Severity of consequences for offenders 	Mathematical model of psychological deterrence (Excel)
Physical Access	 Probability of detection Mean delay time 	 Probability of detection for various detection measures Delay time associated with each detection measures 	Queuing theory (Extend)
Data Access	1. Probability of detection	1. Probability of detection at various points of data access	Probabilistic model (Excel)
Response	1. Probability of interdiction	 Quality of communications Existence of internal fence 	Agent based model (MANA)



Internal Personnel Group The Model- Combining



- Goal: P(Successful Interdiction)How?
 - -Each model produces probabilities
 - •Data Access Independent
 - Physical Access Independent
 - •Response Dependent on Physical Access
 - Detererence Dependent on all 3 above
 - -Link them all together
 - -Get P(Successful Interdiction) for all possible combinations and compare



Internal Personnel Group Data Access Modeling – System Level



- Model the intruder strategy at system level
- Nodes represent barriers that an intruder must penetrate
- Overall probability of success computed by considering the probability of success of all nodes





Internal Personnel Group Data Access Model – Random Test Case



Probabilistic Model

Based on Bayes Rule

BOX I. BAYES RULE.

 $\eta_1 = P(intrusion|signal)$ P(signal|intrusion)P(intrusion)

P(signal|intrusion)P(intrusion) + P(signal|no-intrusion)P(no-intrusion)

- and
- $\eta_2 = P(intrusion|no-signal)$

P(no-signal|intrusion)P(intrusion)

P(no-signal | intrusion) P(intrusion) + P(no-signal | no-intrusion) P(no-intrusion)

Results

- Min (Single Authentication and with IDS) – 79% effective
- Max (2 Factors Authentication and IDS) – 89% effective



Internal Personnel Group Physical Access Model



Alternatives modeled by EXTEND

- 1. Status Quo Turnstiles
- 2. Untrained Guard Alternative 1 + Random Search with handheld Metal detector
- 3. Trained Guard Alternative 2 + Training given to identify suspicious behavior
- 4. Maximum Control Alternative 3 + Metal gate detector with bag scanner





Internal Personnel Group Physical Access Model

Total SA Contacts:

Red Cas: 0

 TEMASEK DEFENCE SYSTEMS INSTITUTE

I Pause Run

MultiRun I Reset

14151764

errain Type LightBush add

CirLog Save Log

Internal movement models

- 1. Without internal fence rely only on watchmen for detection
- With internal fence Watchmen
 + guard at internal fence





Internal Personnel Group Physical Access Modeling Results

TEMASEK DEFENCE SYSTEMS INSTITUTE

2.500	Delay vs Time		P _{Detection}	Without Internal Fence	With Internal Fence
2.000		→ Status Quo	Status Quo	.343	.669
0.500 Delax	000 → Untrained Guard → Trained Guard → Max Control	 Untrained Guards Trained Guards Max Control 	Untrained Guards	.392	.694
0.000			Trained Guards	.497	.747
γ^{0} γ^{1} γ^{1			Max Control	.681 🤇	.839

Recommended: Max Control with internal fence

106



Internal Personnel Group Response Model

TEMASEK DEFENCE SYSTEMS INSTITUTE

Alternatives modeled in MANA

- 1. Poor Communications vs Good Communications
- 2. Mid-Terminal Fence w/ Gate Open vs w/ Gate Closed vs No Fence
- 3. Perpetrator starting at mid-field gate with good comms vs poor comms




Internal Personnel Group Response Modeling Results



SCENARIO	P(Successful Interdiction)		
No Fence, Bad Comms	0.32		
No Fence, Good Comms	0.52		
Fence w/ Open Gate, Bad Comms	0.63		
Fence w/ Open Gate, Good Comms	0.77		
Fence w/ Closed Gate, Bad Comms	0.48		
Fence w/ Closed Gate, Good Comms	0.87		
Mid-Terminal Start w/ Bad Comms	0.39		
Mid-Terminal Start w/ Good Comms	0.54		



Internal Personnel Group Deterrence Model – System Level



- Model based on research done by Robert Anthony (Institute for Defense Analysis) that appears in his paper "Deterrence and the 9-11 Terrorists"
- Involves both qualitative and quantitative analysis
- Provides quantitative value for psychological deterrence based on probability of interdiction
- The model also accounts for 'severity of <u>consequences</u>' from the perpetrator perspective.



Internal Personnel Group Deterrence Model – Results



•Equation: $P_D = 1 - \left(1 - P_I\right) \left(\frac{P_I}{P_O}\right)$ •Results Status Quo •0.904* Max Physical Access and Max Response $\bullet 0.935^{*}$ •An increase of 3.4%

*Note: these results are for the combined Physical Access Control and Response model results.



Internal Personnel Group Combined Model Results (with Data Access Results)



 Status Quo $\bullet 0.815$ Status Quo PA/Response with 2 factor authentication •0.903 Max PA/ Response with 1 factor authentication •0.927 Max PA/ Response with 2 factor authentication •0.962



Internal Personnel Group Physical Access - Response Combined Model Results



			Physical Access Control Measure			
P(Interdiction)		Status Quo	Untrained Guards	Trained Guards	Max Control	
No Internal Fence		Bad Comm	.1210	.1359	.1677	.2334
		Good Comm	.1816	.2068	.2609	.3557
With Internal Fence	Open	Bad Comm	.3068	.3311	.3828	.4735
		Good Comm	.4052	.4327	.4910	.5934
	Closed	Bad Comm	.2781	.2933	.3256	.3823
		Good Comm	.4243	.4579	.5291	.6542



Internal Personnel Group Cost Benefit Analysis

TEMASEK DEFENCE SYSTEMS INSTITUTE

Cost/Benefits Analysis



Probability of interdiction



Internal Personnel Group Cost Benefit Analysis

TEMASEK DEFENCE SYSTEMS INSTITUTE



114



Internal Personnel Group Conclusions



• With current port security infrastructure, incremental improvements in procedural changes and hardware modifications can increase the security effectiveness against internal threats from 12% to 36%.

• With substantial investment in manpower, procedural changes, and additional technologies implementation, the security effectiveness can be increased further to 65%.

• Given the difficulty of addressing internal threats and the potential impacts this has on the port operation, recommend making the investment for the higher performance gain.



Internal Personnel Group Recommended Future Study

TEMASEK DEFENCE SYSTEMS INSTITUTE

- Preventive mechanisms to monitor suspicious activity and act upon them before they become threats
 - Pattern analysis for identification of abnormal behaviors
- Data mining techniques for misuse and anomaly detection
 - Statistical modeling
 - Temporal sequence learning
 - Neural network
 - Genetic algorithms



Summary



- Different agencies, whose efforts collectively provide port security, have different jurisdictions, organizational structures, and funding.
- A coordination problem exists amongst different agencies.
- The information received from the agencies must be rapidly received, displayed, interpreted and responded to in order for many of the modeled alternatives to be effective.
- From conducting this study, PSS12 recognized that the fusion of data is a critical issue that needs to be addressed.



Questions



CEAN CAN A.11 TP

REPUBLICS

118