



Calhoun: The NPS Institutional Archive
DSpace Repository

Faculty and Researchers

Faculty and Researchers' Publications

2021

Assessment of Multispectral Imaging System for UAS Navigation in a GPS-denied Environment

Yakimenko, Oleg A.

Monterey, California: Naval Postgraduate School

<https://hdl.handle.net/10945/69768>

This publication is a work of the U.S. Government as defined in Title 17, United States Code, Section 101. Copyright protection is not available for this work in the United States.

Downloaded from NPS Archive: Calhoun



Calhoun is the Naval Postgraduate School's public access digital repository for research materials and institutional publications created by the NPS community. Calhoun is named for Professor of Mathematics Guy K. Calhoun, NPS's first appointed -- and published -- scholarly author.

Dudley Knox Library / Naval Postgraduate School
411 Dyer Road / 1 University Circle
Monterey, California USA 93943


<http://www.nps.edu/library>

Background and Motivation

- These days, an integrated EO/IR sensor and its associated signal or image processing is a standard payload for manned and unmanned aerial systems (UAS).
- Whether using multispectral (MS) imagery, a relatively new technology, has any benefits compared to a standard integrated EO/IR sensor?
- This includes enhancing accuracy and precision of object detection, classification and tracking (DCT) and additional/alternative aid to navigation (ATON) in the GPS-degraded or GPS-denied environments.



Unexploded ordnances (UXOs) / mines detection (DCT task)




MS-based DCT examples

MS-based Detection of UXOs

- Using MS vs traditional EO/IR imagery complimented with artificial intelligence (AI) methods has a clear benefit. MS imaging captures information that cannot be seen with the human eye and presents a more data-rich mosaic for applications within the remote-sensing.
- While DCT precision for each individual spectral band is lower than that of EO sensor, the detection outputs compliment each other.
- As a result, the integrated detector composed of pre-trained convolutional neural networks for each band happens to be a more reliable and precise DCT tool.

MS-based Odometry

- If the two consecutive images represent about the same scene [even though they are far apart from each other (slow flight, high-altitude flight, high sampling rate)], they share a significant number of matching features.
- Applying the most efficient computer-vision (CV) feature-finding algorithms for each spectral band of MS sensor increases a pool of complementary matching features from which a more accurate geometric transformation could be derived.
- The efficiency of the developed algorithms allows running them in real time on a secondary single-board computer aboard a small UAS.



Visual odometry based on the MS feature matching

Results and Recommendations for Future Work

- Utilizing a small UAS equipped with a MS sensor and CV/AI algorithms may be very beneficial to DoD and DoN enhancing existing and offering new capabilities related to both DCT and ATON.
- Future work includes tuning algorithms and studying effects of operating environment, terrain, altitudes, object size and material, time of the day, weather, number of spectral bands, and resolution.



Researcher: Prof. Oleg Yakimenko
Graduate School of Engineering and Applied Sciences
Topic Sponsor: N8 - Integration of Capabilities & Resources

NRP Project ID:
NPS-21-N029-A