



**Calhoun: The NPS Institutional Archive**  
**DSpace Repository**

---

Faculty and Researchers

Faculty and Researchers' Publications

---

2019-12

# AoA Paradigm for Early Visibility of Logistics and Cost in the Acquisition Process

Kress, Moshe

Monterey, California: Naval Postgraduate School

---

<https://hdl.handle.net/10945/69916>

---

This publication is a work of the U.S. Government as defined in Title 17, United States Code, Section 101. Copyright protection is not available for this work in the United States.

*Downloaded from NPS Archive: Calhoun*



Calhoun is the Naval Postgraduate School's public access digital repository for research materials and institutional publications created by the NPS community. Calhoun is named for Professor of Mathematics Guy K. Calhoun, NPS's first appointed -- and published -- scholarly author.

**Dudley Knox Library / Naval Postgraduate School**  
**411 Dyer Road / 1 University Circle**  
**Monterey, California USA 93943**

<http://www.nps.edu/library>

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department



NAVAL RESEARCH PROGRAM  
NAVAL POSTGRADUATE SCHOOL

MONTEREY, CALIFORNIA

# Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Period of Performance: 01/01/2019–12/31/2019

Researchers: Principal Investigator (PI): Professor Moshe Kress, GSOIS, Operations Research  
Co-Author: Professor Boaz Golany, IE, Technion, Israel Institute of Technology

Prepared for:

Topic Sponsor Lead Organization: OPNAV N4iL - Logistics Analytics Branch (LAB),

Topic Sponsor Name: CAPT Eric Morgan

Topic Sponsor Contact Information: [eric.morgan1@navy.mil](mailto:eric.morgan1@navy.mil), 703-614-3058

Distribution A: Approved for public release; distribution is unlimited.

## **NPS NRP Final Report**

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

### **Abstract**

Analysis of Alternatives (AoA) is a study comprising a crucial part in the process of acquiring new system for the DoD. AoA is essentially a multi-dimensional decision process that involves several criteria and stakeholders. There are three sets of criteria according which the alternatives are evaluated. Two of the three sets – effectiveness (what can the system do and how its capabilities fit the operational requirements) and cost of acquisition draw most of the attention in such a study. The third set, which in AoA studies typically draws somewhat less attention than the other two, is concerned with the long-term readiness, sustainment and logistics implications. In this report we study in detail the content of this set of criteria – what affects the long term viability and usefulness of an alternative – and propose an analytic framework for evaluating alternatives with respect to the criteria in this set.

**Keywords:** *Analysis of Alternatives (AoA), Readiness, Sustainment, Data Envelopment Analysis (DEA)*

## **NPS NRP Final Report**

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

### **1. INTRODUCTION**

The DoD Acquisition System comprises three interconnected stages that start with specifying requirements – a procedure called Joint Capabilities Integration and Development System (JCIDS). The second stage, called Acquisition Process, determines appropriate materiel solutions for the requirements. The third stage is concerned with funding and financial-controlling activities contained in the Planning, Programming, and Budgeting Execution (PPBE) process (Kress, M., and Morgan, B., 2018). Most of the decisions that have long term sustainment, readiness and logistics implications are taken at the second stage, where materiel choices are determined. The overarching process dominating this stage is the Analysis of Alternatives (AoA) that, in general, trades off the effectiveness of a materiel solution with its risks and costs. The AoA in the acquisition process is essentially a large-scale multi-criteria decision analysis (MCDA) problem that involves multiple stakeholders and many uncertainties (see (Kress, M., and Morgan, B., 2018)).

The set of criteria used in evaluating alternatives, and their weights or importance, depend, among others, on the state of the alternatives in the development and production process. For example, the risk associated with acquiring an off-the-shelf system is considerably lower than the risk in developing a new system. Thus, the “risk” criterion, with all its derivatives, is less prominent for the former than the latter. In this study we focus on systems that are still in various stages of development, which means that the AoA process is typically not a “one-shot” decision event but rather a sequence of decisions marked by milestones. In these settings, the AoA starts off with a set of potential alternatives being developed as prototypes. As time passes, data is collected and information is gained with respect to each contending alternative. Each mile-stone in the R&D phase involves solving a MCDA problem that determines which alternatives continue to be relevant, and therefore continue in the R&D phase, and which alternatives are dominated and therefore deleted from further consideration. The process culminates in a winning alternative.

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

The main purpose of this report is to investigate the criteria affecting readiness and sustainment, and develop a new paradigm that may facilitate better (and earlier) awareness to readiness and sustainability considerations during the acquisition process.

## 2. READINESS SUSTAINMENT AND LOGISTICS

The DoD Dictionary (DoD, 2019) defines *sustainment* as *the provision of logistics and personnel services required to maintain and prolong operations until successful mission accomplishment.* (JP 3-0). *Readiness* is defined as *the ability of military forces to fight and meet the demands of assigned missions.* (JP 1). *Logistics* is *planning and executing the movement and support of forces.* (JP 4-0). Notice that the term *logistics* is included in the definition of *sustainment*. Thus, henceforth we will focus on the two factors: readiness and sustainment (R&S).

Readiness and sustainment are terms that typically apply to the entire military force. They are considered two of the “four pillars” of military capability (Moore, et al., 1991). Measures of R&S describe features such as resources availability, level of training and percentage of platforms that are mission-ready at any time (Rich, et al., 1987).

In this study we consider these terms in a more restricted way; as they reflect the virtues and shortcomings of acquisition alternatives.

In the context of AoA, (see, e.g., (HAF, 2016)), the relative value or utility of a certain (new) acquisition alternative (compared to other alternatives) is based on three dimensions, each a combination of several criteria: (a) effectiveness during operations, (b) cost, and (c) R&S attributes. The R&S dimension accounts for all the factors not directly related to the first two, such as risks, dependencies on other systems and peripheral requirements. The three dimensions are not orthogonal. For example, sustainment involves (lifecycle) cost considerations, and effectiveness is affected by readiness.

Effectiveness of an alternative is measured through the gaps, if they exist, between the performances of each alternative and the operational requirements that were set during the JCIDS. Lifecycle cost (sometimes referred to as total ownership cost) is measured by accumulating the various expected costs directly associated with each alternative. Both

## **NPS NRP Final Report**

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

dimensions have been studied in depth and there exist proven methodologies that address them in AoA studies (e.g., combat simulations and cost estimation methods). In this report, we focus on the third dimension, R&S, which, we believe, demands as much attention as the other two dimensions. Failing to devote this attention, especially during the early stages of the AoA, may potentially lead to choosing an alternative that is most cost-effective from the point of view of the first two dimensions, but may become, economically burdensome and eventually even impossible to operate in the long run.

Next we describe the content of the R&S dimension and discuss its criticality.

### **2.1 Readiness**

Readiness of an acquisition system has three different aspects: technological, technical and functional. While technological readiness describes the state of a system still being developed and the projected time of completing its production and testing, technical and functional readiness relate to the actual operation of the system when it is fully operational and already deployed.

#### **2.1.1 Technological Readiness**

The technological aspect of readiness describes the maturity of the technology, and the production and testing capabilities needed for the newly developed system. As mentioned above, this type of readiness only applies to the development phase of the system; it describes how close the system is to becoming fully operational. Several scales have been used to evaluate this aspect. Back in the 1980's the National Aeronautics and Space Administration (NASA) used the Technology Readiness Level (TRL) to assess the maturity of a particular technology that is to be used in developing a system. The TRL is a nine-level scale that ranges from "Basic Principles Observed and Reported" (Level 1) to "Actual System Proven through Successful Mission Operations" (Level 9). According to the Department of Defense (DoD), a weapon system program cannot include a technology whose TRL is lower than level 7 (GAO, 1999). Sauser et. al. (Sauser, B. J., Ramirez-Marquez, J. E., Davanandham, H., DiMarzio, D., 2008) combine the TRL, which is purely technology-oriented, with a system-integration measure – the

## **NPS NRP Final Report**

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

Integration/Interface Readiness Level (IRL) – and produce the System Readiness Level (SRL), which is a more holistic engineering measure for the technological maturity of a system. (Atwater, B., and Uzdinski, J., 2014) generalized the SRL into, what they call, a “wholistic” view of system maturity that includes also functionality (i.e. man-machine interface).

Technological readiness is tied to the risk criteria in the AoA process. The risks associated with an alternative that is still in technological development stages reflect the uncertainties regarding the feasibility that the alternative will be mission-ready on time and within budget. Thus, during the AoA and the subsequent development and production phases, the technological readiness of a system can be defined by a value proportional to the (subjective) probability that the system will be completed on time and within budget. Note that since the AoA is only concerned with the relative values of alternatives, we do not need to assess the actual probabilities of successful completion but only their relative values.

As mentioned above, the technological readiness of a system has to do with projecting the completion time of the underlying research, development and production project (this time could be infinite if the project fails altogether), and the total cost of the system. The SRL, data from similar past projects, and most of all, inputs from subject matter experts are used to obtain the relative technological readiness values of the alternatives, using techniques similar to the one described in (Kress, M., and Morgan, B., 2018).

Finally, note that technological readiness changes dynamically during the R&D phase. It is updated periodically as the project advances; the closer is the project to completion, the more accurate is the estimate of this type of readiness.

### **2.1.2 Technical Readiness**

A system is technically ready if all its components are in a perfect working condition. Thus, technical readiness (TR) has to do with the reliability and maintainability of the system and its components. TR can be measured by the probability that the system is technically mission-ready

## **NPS NRP Final Report**

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

at any point in time during its life cycle. TR is closely tied with sustainment, which is discussed later on. TR is also related to the nature of the missions planned for the system and particularly to the typical alert time the forces are expected to have before launching a mission. For example, missile interception systems are expected to become ready within seconds of an alert while submarine missions will typically have alert times of days or even weeks.

Three main factors determine the TR of a system: (a) reliability, which is measured by the mean time between failures (MTBF), (b) the effort needed to fix the system, which is measured by the average service time, and (c) the availability of spare-parts needed for its maintenance and repair. Note that factor (b) depends to large extent on factor (c); availability, or lack thereof, of repair-parts affect the total service time of a system.

In principle, factor (a) – MTBF – is measurable; the MTBF of each component in the system, along with the associated reliability-graph of the system, can project the system-wide MTBF. The problem is that the MTBF figures for the various components are only estimates, based on limited data and simulations. The actual MTBF of the system cannot be robustly estimated until the system is fully operational for some time and enough failure data is collected. Similarly, to factor (a), the impact of factor (b) – service time – is practically unknown until the system is operational for some time and enough service-time data are collected. The fact that data regarding the first two factors are unavailable at the time when the AoA is initiated does not mean that they should be ignored. Technical details, comparisons with similar systems, meticulously designed simulations, and early testing of critical components should be utilized for evaluating these two important factors of technical readiness. The third factor is the availability of repair parts, which is affected by the number, complexity, variability, and cost of the system's components, as well as by the robustness of the supply chain that provides the repair-parts. These characteristics could be evaluated well in advance and factored in quite smoothly into the evaluation of technical readiness. For example, the lead time for delivering a certain repair part, a parameter that could be estimated from the features of its supply chain, will be used to estimate total repair time. The impact of unavailable repair parts is determined by design factors such as



## **NPS NRP Final Report**

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

redundancy of sub-systems and components. The modularity of subsystems affects the repair time (factor (b)). “Plug-and-Play”-type components obviously need less service time than components that require installing, reconfiguration and adjustments.

It is quite unlikely to have a robust TR measure during the early phases of the AoA process. There will not be enough data to support it. However, as the system advances in its development process, more knowledge and experience are accumulated, and the TR measure – combining MTBF, service time and repair-parts lead time – gets updated accordingly.

We discuss the specific features of a possible TR measure later on.

### **2.1.3 Functional Readiness**

The fact that a system is fully developed and technically ready for operations does not necessarily mean that it is also operational. In order to effectively function, a system may need that other, supporting or peripheral, systems will be fully functional too. Full functionality will also require that certain types of operators will be available to run it, and specific elements of infrastructure will be in place to support it. First, a system, as advanced and sophisticated as it may be, needs people to operate, control, maintain and utilize its outputs. These operators, controllers, support personnel and users need to be trained and available for their respective tasks. Shortage in any of the required manpower capabilities and expertise needed for the system may render the system nonoperational. Arguably, the impact of unavailable personnel varies among the tasks. A system that needs four operators during a shift may be operational, albeit less effectively, with just three operators. But, a repair technician who is not available when the system is down can be detrimental. A system may also need peripheral support such as protected environment, robust supply chain of resources, and access to communication networks. It may also depend on the operations of other systems, where failure in one or more of them may render our system nonoperational even if all other technical and functional factors are in perfect condition.

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

As mentioned above, we note the difference between the first type of *readiness* – technological readiness – and the other two. While the first type applies to the development/production stage of the alternative, the last two refer to the readiness of the system once it is deployable and ready for operation. In the following, when we refer to “*readiness*” as *operational readiness*, we restrict the definition to only the technical and functional aspects. The technological aspect does not apply to operational readiness and therefore should be treated separately.

Both technical and functional readiness can be further broken down into a vector of sub-factors that define it in greater granularity. Combining all these factors and sub-factors into a single operational readiness measure will require some weighting methods – a topic that will be discussed later.

## 2.2 Sustainment

In a nutshell, following acquisition, total ownership cost is the cost of sustainment – the cost of maintaining a system in an adequate operational condition. Technical and functional *readiness* are contingent on sustainment. *Sustainment* encompasses all the materiel and services needed for the effective and prolonged operation of a system so that it satisfies the missions for which it is designed. There are three facets to sustainment: supplies, facilities and personnel. Each facet requires efforts and resources in order to be an effective enabler of sustainment.

### 2.2.1 Supplies

Vehicles need fuel and repair parts, weapons need ammunition, source of energy, and repair parts, and operators of systems need food, water and other personal supplies. The quantity and diversity of the supply items needed to operate the system affect the economic burden on sustaining the system, and the availability of these resources affects the operational readiness of the system. Other supply-related factors that affect the economic burden are transportation and storage costs of these supply items. The responsiveness and reliability of the supply chain affect availability of supplies and thus the operational readiness.

## **NPS NRP Final Report**

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

### **2.2.2 Facilities**

Defense systems need storage, maintenance and support facilities. Advanced weapons and C2 systems may require also expensive training and simulation facilities. The size, quality and fitness of a facility will affect the readiness of the system that relies on them. For example, if a certain system requires certain environmental conditions, say, low temperature, for operating properly, then the quality and reliability of the air-condition capabilities in the facility are crucial for making the system mission ready.

### **2.2.3 Personnel**

All systems, as advanced as they may be, need humans to operate, control and maintain them. Personnel with a variety of skills and trainings need to be available for those tasks. If, for example, a system requires a 24/7 human controller, then sustaining proper readiness will entail at least three qualified personnel, operating in 8 hours shifts, in order to keep the system mission ready.

## **3. R&S FACTORS**

Based on the discussion in Section 2, we identify the following main factors that affect the R&S dimension:

- **Mean Time Between Failures (MTBF).** This is one of the most significant factors affecting technical readiness. The complexity of the system, and the reliability of each of its components determine the failure rate of the system – the probability that the system is technically fit at any given moment. Arguably, this parameter depends on the alternative's regular service and preventive maintenance schedule. This schedule, measured by the Mean Time Between Service (MTBS – see below), is inversely related to the MTBF; smaller MTBS will increase the MTBF of the system and thus enhance technical readiness, at an increased cost rate.

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

- **Mean Time Between Services (MTBS).** Each alternative system comes with instructions concerning regular service schedule and preventive maintenance actions. MTBS is measured by the frequency of such actions, as specified by the manufacturer.
- **Repair Time & Service Time.** The system is *down* while it is in (scheduled) service or (unscheduled) repair following a failure. Obviously, during those down times the system is inoperable. The length of a down time depends on the complexity of the system and the availability of resources – personnel, facilities, tools and spare-parts. For example, a modular system that facilitates “plug & play”-type repair technique would require less repair effort and therefore experience less down time than a non-modular system. Note that *repair* and *service* are actions that only apply to *technical readiness*, as defined earlier.
- **Repair Cost & Service Cost.** These are the costs for maintaining the system technically ready. These costs include spare-parts, tools, infrastructure and personnel. These costs can be reasonably estimated from analyzing the components of the system and from the manufacturer’s specifications regarding service and preventive maintenance. A possible service cost is derived from designated up-time. Certain systems require frequent uptime to maintain their lifetime expectancy while others can stay dormant for longer times. The larger the uptime requirement is, the more difficult it is to sustain the system.
- **Setup Time and Cost.** A system may be, by design, in a “cold” operational stand-by condition (e.g., a system that is only activated in an emergency). The setup time and cost that brings the system into a fully operational state is a crucial aspect in measuring readiness (time) and sustainment (cost).

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

- **Interdependency.** Dependency on other systems makes an alternative more vulnerable to failure and potentially more disruptive when failed than an alternative, which operates as stand-alone. Examples:
  - A vehicle that needs to be transported by other means of transportation to the area of deployment.
  - A moving platform (aerial, ground or sea) that depends on satellites availability for its navigation.
  - A system that requires extensive and expensive training facility to become operational.
  - A sensor, which is connected to an elaborate command and control system.
  
- **Personnel.** Any system requires operators, controllers and technicians. Finding qualified and skilled personnel, training them and then retaining them is always challenging. *Ceteris paribus*, a simpler alternative to operate and maintain, which requires a few, easily trained, operators and technicians is preferred to a more complex alternative, which requires highly skilled and trained personnel.
  
- **Supply Chain.** The availability of spare-parts that facilitate technical readiness depends on an efficient and robust supply chain. Supply chain is also one of the principal means for making a system *functionally ready*. A vehicle needs fuel, a sensor requires electrical power and a weapon will not operate without ammunition. The type of supplies (size, weight, scarcity, fragility, handling requirements), and the frequency at which they are needed, affect the cost of sustainment, and the length and robustness of the supply chain. Part of the supply chain is the logistic tail of the deployable system – certain systems require a large, expensive or difficult to maintain tail in order to ensure their functionality (e.g., a convoy of supply trucks) while others require little or even negligible tails (sometime referred to as "deploy & forget" systems). Obviously, larger logistic tail requirements imply more difficult to sustain a system. An alternative that requires more frequent deliveries of expensive supplies by a more fragile supply chain is inferior to a

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

more self-sustained alternative, which is supported by a simpler supply chain. There are several factors that determine the vulnerability of a supply chain – e.g., single source vs. multiple sources, geographical distances between the nodes in the chain, the required transportation means, their availability, and their robustness to environmental conditions such as weather and terrain.

We note that these factors are not necessarily independent. For example, MTBS affects MTBF; higher frequency of service will inversely affect the frequency of failures. To avoid dealing with such dependencies, we will define measures for “meta-factors”, which combine similar factors into (relative) measures.

### 4. MEASURING R&S FACTORS

Recall that this study is concerned with the R&S dimension in the context of AoA where *relative* evaluations – rather than *absolute ones* – are sufficient. This observation is important because many of the aforementioned factors, and the meta-factors defined below, are not easily measurable. We may need to use ordinal preferences, such as Likert scale (Allen & Seaman, 2007), and combine them, in some consistent way, with measurable factors to produce an overall ranking of the alternatives with respect to the R&S dimension.

Next we describe measures for evaluating the various facets of the R&S dimension.

#### 4.1 Mean Time Between Downs (MTBD)

The MTBD is a meta-factor, which is a combination of MTBF and MTBS. The mean time between failure of a system can be statistically estimated only after it has been in operation for some time and enough failure data has been collected. This is obviously not the case in an AoA setting where the alternatives are still in a development stage. One possible way to assess the MTBF is by considering the way the components relate to each other in the system (i.e., in parallel or in series) and evaluating separately the reliability of each component,

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences

Operations Research Department

assuming such data is available. Integrating all this information, say, in a simulation, can produce a reasonable estimate for the MTBF. The MTBS is derived from the manufacturer recommended service and preventive maintenance schedule. This parameter should be given as part of the specification of the system. If  $T_S$  is the (deterministic) MTBS, and the failure process follows an exponential distribution with mean  $\frac{1}{\lambda_F}$  (which may be dependent on  $T_S$ )

then, assuming a failure resets the service clock, the *MTBD* is given by

$$MTBD = T_S e^{-\lambda_F T_S} + \int_0^{T_S} t \lambda_F e^{-\lambda_F t} dt .$$

### 4.2 Mean Down Time (MDT)

The system is down while in (unscheduled) repair or (scheduled) service. If the mean repair time and the mean service time are  $\mu_F$  and  $\mu_S$ , respectively, then, assuming exponential distribution, the *MDT* is given by  $MDT = \mu_F (1 - e^{-\lambda_F T_S}) + \mu_S e^{-\lambda_F T_S}$ . Note that while  $\mu_S$  can be directly estimated from the service and preventive maintenance specifications,  $\mu_F$  is more elusive and may be estimated from simulation, similarly to the MTBF. Also note that the computation of both MTBD and MDT are easily generalized when the failure distribution is general, not necessarily exponential. Specifically, if the failure distribution has the CDF  $F_F(t)$ , and the down states generate a renewal process, then the MTBD and the MDT are

$$T_S (1 - F_F(T_S)) + \int_0^{T_S} t dF_F(t) \text{ and } \mu_F F_F(T_S) + \mu_S (1 - F_F(T_S)), \text{ respectively.}$$

### 4.3 Maintenance Cost (MC)

MC is truly a meta-factor encompassing all the resources needed to maintain the system in operational state. These expenditures include fix costs, denoted *FMC*, such as infrastructure (e.g., shops, storage facilities, labs, equipment, personnel) and variable cost (*VMC*) covering replaceable parts, energy and other resources needed for a specific maintenance mission.

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

Standard practices of cost estimation (Mislick and Nussbaum, 2015) may be used to obtain estimates for the two types of cost. Given  $VMC$  and  $MTBD$ , the cost rate is  $VMCR = \frac{VMC}{MTBD}$ .

Ignoring, for simplicity discount rates, and assuming a reference time horizon of length  $T$  time periods, the average maintenance cost per time period is

$$MC = \frac{FMC}{T} + VMCR.$$

### 4.4 Operational Cost (OC)

Operational cost is relatively simple to compute because it relates to a fixed set of actions that need to be executed by the system. Such a set is typically well defined as it establishes the foundation for functional readiness (see Section 2.1.3). The operational cost is the cost of daily, or recurrent, operations. It can be measured by the number of operators and controllers, broken down by required skills, cost of operating facility (when applicable) and the amount and type of energy needed for the operation. If the functional characteristics of the system to be selected is such that it is dormant most of the time and is activated only when needed, then the operational cost includes also the set-up cost and time required for activation. An alternative that can become active faster and at lower cost has lower operational cost than an alternative that takes time to set up. The parameter measuring OC is the average daily cost of operations.

### 4.5 Interdependency (INT)

This is a crucial, yet elusive, characteristics that is often ignored because it is challenging to measure. The more a system depends on other systems and processes, the more it is vulnerable to possible breakdowns and failures of those peripheral systems and processes. Thus, such dependency leads to lower functional reliability. To capture this vulnerability, we first define, for each alternative, the set of peripheral systems and processes upon which it depends. We call it the *Systems' Dependency Set*. Arguably, ceteris paribus, the larger the dependency set the lower the functional reliability of the alternative because more things can



## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences

Operations Research Department

go wrong. In particular, if an alternative is a fully stand-alone system, then interdependency has no effect.

We describe the state of the dependency set by a  $k$ -dimensional  $\{0,1\}$  vector  $x$ , where  $k$  is the cardinality of that set. If a system in the dependency set is up and running its corresponding entry in the vector is 1, otherwise that entry is 0. For example, if  $k = 3$ , then the vector  $x = (1,0,1)$  indicates that the first and third peripheral systems in the dependency set of the alternative are up and running while the second system is down.

The functional readiness of the alternative depends on the state vector of its associated dependency set. We denote that effect by the function  $D(x)$ . For example, if the number of peripheral systems of an alternative is  $k = 3$ , then  $D(1,1,1) = 1$  (no effect) and  $1 = D(1,1,1) > D(1,1,0) > D(1,0,0) > D(0,0,0) \geq 0$ . In other words, fewer functioning peripheral systems imply lower functional reliability of the alternative. In general,  $0 \leq D(x) \leq 1$ .

Let  $p_i, i = 1, \dots, k$  denote the probability that the  $i$ -th peripheral system in the dependency set of the alternative is operational and functioning. Assuming independence, which in many cases is a reasonable approximation, we have that

$$p(x) = \Pr[x = (x_1, \dots, x_k)] = \prod_{i=1}^k p_i^{x_i} (1 - p_i)^{1-x_i}$$

If  $2^x$  denotes the power set of  $x$  then we define the *interdependency index* of an alternative by

$$INT = \sum_{x \in 2^x} p(x) D(x).$$

The higher the value of  $INT$  the more robust is the alternative with respect to its dependency on other systems.

### 4.6 Personnel (PER)

The cost of personnel is accounted for in the operational cost (OC) discussed above. There is another aspect of personnel that affects the functional and technical reliability of an alternative –

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

the dependence on certain types of qualified personnel. The more a system relies on a large variety of skilled personnel the more it is vulnerable to their possible absence. Thus, like interdependency described above, such dependency may lead to lower functional and technical reliability. To capture the personnel vulnerability, we propose the same approach used for interdependency. We define for each alternative the *Personnel Dependency Set*, which comprises the skill set of persons needed for the operation of the system. We describe the state of the dependency set by a  $k$ -dimensional vector  $x$  of natural numbers, where  $k$  is the number of skill-types (e.g., technicians of certain types, operators of different training levels, etc.) needed for operating and maintaining the system, and  $x_i, i = 1, \dots, k$ , is the number of people of type  $i$  available at any given time. Let  $s_i, i = 1, \dots, k$ , denote the number of people of type  $i$  required by the system at any given time. Similarly to the interdependency case, we define

$R(x) = R(x_1, \dots, x_k)$ ,  $x_i \leq s_i$ , as the effectiveness of the system when the available personnel team is  $x$ . We have that  $R(s) = R(s_1, \dots, s_k) = 1$  and  $R(x) \leq 1$ . Trivial calculation show that there are

$S = \prod_{i=1}^k (s_i + 1)$  possible profiles of personnel availability.

The personnel-dependency measure is

$$PER = \frac{1}{S} \sum_{x_1=0}^{s_1} \dots \sum_{x_k=0}^{s_k} R(x_1, \dots, x_k).$$

An alternative that is reasonably functional with less personnel will have a higher *PER* score than an alternative that is sensitive to staffing.

For example suppose  $k = 3$  (three different types of personnel) and  $s_1 = 2, s_2 = 1, s_3 = 1$ . In other words, the system requires a team of four, say, two operators ( $i = 1$ ), one controller ( $i = 2$ ) and one technician ( $i = 3$ ). We have  $1 = R(2, 1, 1) > R(1, 1, 1) > R(1, 1, 0)$ , etc. The closer the *PER* of a system to 1 the smaller the effect of reduced staff.

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

### 4.7 Supply Chain (SC)

There are many factors that affect the robustness of a supply chain (SC) – e.g., single source vs. multiple sources of supply, geographical distances between the nodes in the chain, the type and availability of means of transportation, etc. The literature on SC has not reached a consensus on unified quantitative measures that can objectively assess the relative “value” of different SCs and hence we propose to use an ordinal scale where the alternatives in the AoA are simply ranked by subject matter experts in the AoA team. This is the only qualitative and subjective input into the R&S part of the AoA. We assume that subject matter expert can produce such a ranking that may have ties for alternatives that are evaluated as having equally effective and robust supply chain. Thus, the higher the rank SC of an alternative, the more robust and effective is its supply chain. Note that a higher rank implies a smaller (integer) value of SC.

## 5. USING DEA FOR EVALUATING R&S

In this section we propose a methodology to assess the R&S value of an alternative based on the seven aforementioned measures. Recall that our goal is to evaluate the *relative* value of an alternative with respect to the R&S factors, not its *absolute* value.

Suppose, for simplicity, that the R&S dimension comprise only two factors: MTBD and MC. Obviously we wish to have a reliable alternative with high MTBD and low maintenance cost MC. A reasonable relative measure for the alternative would be the “reliability-cost” ratio MTBD/MC. The higher this ratio, the better the alternative with respect to the R&S dimension. So, if the only R&S factors were MTBD and MC then we could easily rate the alternatives from best to worst according to the values of the reliability-cost ratios. However, in reality we have seven factors that affect this dimension. The challenge is how to extend the ratio idea described above with respect to MTBD and MC to all seven factors.

To meet this challenge, we propose to use the *Data Envelopment Analysis* (DEA) methodology. Since it was first proposed in the late 1970s by Charnes, Cooper and Rhodes, (1978), DEA has been applied to hundreds of application areas including several DoD-related applications such as evaluating the efficiency of air-force maintenance units (Charnes et al., 1984). Other relevant

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences

Operations Research Department

applications include (Bowlin, 1996), which describes how DEA can be used to address various DoD evaluation procedures; (Brockett et. Al, 1997) that evaluates the efficiency of US Army recruitment units; (Hong and So, 2011), which evaluates the performance of Korean Air-Force bases; (Sutton and Dimitrov, 2013) who uses DEA to assign sailors to tasks for the US Navy, and (Boehmke et al., 2017) that measures installation support activities in the US Air Force. Essentially, DEA is a non-parametric methodology for comparing multiple entities, all of which use the same set of inputs (albeit, in different quantities) to produce the set of outputs (again, with different quantities). If  $O_1, \dots, O_m$  denote a vector of outputs and  $I_1, \dots, I_n$  denotes a vector of inputs then the efficiency ratio is  $\frac{x_1 O_1 + \dots + x_m O_m}{y_1 I_1 + \dots + y_n I_n}$ . The question is what are the “right” weights

$x_1, \dots, x_m$  and  $y_1, \dots, y_n$ .

DEA evaluates the relative efficiency (i.e., determines the values of  $x_1, \dots, x_m$  and  $y_1, \dots, y_n$ ) of each alternative by solving a corresponding linear programming model that determines for the alternative the values of the aforementioned weights. The idea is to present each alternative in the best possible way while meeting some logical constraints. Normalizing the value of the highest relative efficiency to 100%, a system that receives a score that is smaller than 100% (i.e., its associated model failed to find a set of weights that will present it as 100% efficient) is by definition inefficient and DEA can assess the gap between its current performance and the efficient frontier that the methodology construct on the basis of the entities that were found to be 100% efficient. DEA was specifically designed to handle situations such as the one we face here as it is capable of handling data that is not easily converted into universal quantitative measure such as dollar. In our case we have measures associated with time (MTBD, MDT), money (MC, OC) effectiveness (INT, PER), and an ordinal scale (SC).

In our context, we distinguish between factors for which more is better – MTBD, INT, PER – and factors for which less is better – MDT, MC, OC and SC. Accordingly, we consider the “efficiency” ratio

$$ER = \frac{x_M MTBD + x_I INT + x_P PER}{y_D MDT + y_M MC + y_O OC + y_S SC}.$$

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences

Operations Research Department

With the exception of the ordinal SC, the standard DEA model will apply. The presence of the ordinal factor necessitates a modification of the standard DEA model, as described in (Cook et al. 1993).

### 6. THE DEA MODEL

Let  $n$  denote the number of alternatives to be evaluated with respect to the R&S dimension. The index  $i$ ,  $i = 1, \dots, n$ , indicates the identity of an alternative. We solve  $n$  linear programming problems – one for each alternative. The data for the optimization model are the quantitative parameters  $MTBD_i, INT_i, PER_i, MDT_i, MC_i, OC_i$ , and the qualitative ordinal parameter  $SC_i(k)$ ,  $i = 1, \dots, n$ ,  $k = 1, \dots, l$  where  $l$  is the number of rank positions, and

$$SC_i(k) = \begin{cases} 1 & \text{if alternative } i \text{ is ranked in the } k\text{-th place} \\ 0 & \text{Otherwise} \end{cases}$$

The idea is as follows: each alternative, in its turn, is given the “opportunity” to select its coefficients such that it gets the highest possible efficiency ratio  $ER$ . It can do it as long as the “best” coefficients it selected, when applied to the efficiency ratio of any other alternative, do not result in an efficiency ratio that exceeds 1. Thus, the maximum possible efficiency ratio is  $ER = 1$ . Those alternatives, which reach 1, are considered R&S efficient. In addition to the normalization constraint that limits each efficiency ratio not to exceed 1, we require that all coefficients are non-negative and the weights of the ordinal parameter ( $SC$ ) adhere to the rank positions, that is, a weight of rank 1 should be lower than the weight of rank 2, etc. For each alternative, temporarily assigned the index 0, we solve the following linear optimization problem, see (Cook et al. 1993) for details:

**NPS NRP Final Report**

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences

Operations Research Department

$$Max \ x_M MTBD_0 + x_I INT_0 + x_P PER_0$$

*st*

$$y_D MDT_0 + y_M MC_0 + y_O OC_0 + \sum_{k=1}^l w_k SC_0(k) = 1$$

$$x_M MTBD_i + x_I INT_i + x_P PER_i - (y_D MDT_i + y_M MC_i + y_O OC_i + \sum_{k=1}^l w_k SC_i(k)) \leq 0, \ i = 1, \dots, n$$

$$w_{k+1} - w_k \geq \varepsilon$$

All decision variables  $\geq \varepsilon$

where  $\varepsilon$  is an arbitrary separation parameter determined by the decision maker. In the next section we illustrate this methodology on an example.

**7. EXAMPLE**

At each milestone of the AoA more detailed and reliable information is gathered about the seven measures – MTBD, MDT, MC, OC, INT, PER and SC. The data is entered into the DEA model and the relative standings of the alternatives are obtained with respect to the R&S dimension.

Suppose there are currently three alternatives under consideration, and the R&S measures are as shown in Table 1.

Alternatives (systems)	MTBD (days)	INT (Section 4.5)	PER (Section 4.6)	MDT (days)	MC (K\$ per day)	OC (K\$ per day)	SC (ranking)
Alt1	33	0.7	0.7	3	18	5	I
Alt2	30	0.6	0.7	3	16	2	II
Alt3	20	0.6	0.5	2	15	4	III

Table 1: R&S Data for Three Alternatives

We see from the data that no alternative dominates another with respect to all seven R&S measures. For example, Alt1 has the highest (best) MTBD, INT and PER scores (it is tied with Alt2 with respect to the latter). Alt 1 is also ranked highest for SC. Alt2 has the lowest operational cost (OC), and Alt 3 has the lowest down time (MDT) and lowest maintenance cost (MC). Thus, a simple inspection of the data will not reveal which alternative is more R&S efficient.

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

Running the DEA model presented in Section 5, where we select for each alternative its maximum feasible value of  $\varepsilon$ , we obtain that while the *ER* values for Alt1 and Alt2 are 1, that is, they are R&S efficient, for Alt 3  $ER = 0.77$ , which means that the “best” coefficients it could find for its data still rate it 23% lower than Alt1 and Alt 2. Note that if  $\varepsilon$  is set at a value smaller than its maximum value, the differentiating power of the model decreases, that is, for a smaller  $\varepsilon$  all alternatives may be tied at the top. More on this differentiating effect in the next section.

### 8. SUMMARY, CONCLUSION AND FURTHER RESEARCH

This report bridges a gap in AoA, addressing the role of examining R&S in such analyses. In the first part of the report we define these characteristics and study their components. This study results in a set of measures that must be observed, calculated and updated as new data become available during the development process of a new system. In the second part of the report we propose an analytic procedure, grounded in the well-established methodology of DEA, to continuously assess the R&S aspects of an AoA.

Like all other quantitative methodologies, DEA has certain weaknesses that users must be aware of and be ready to address when the need arises. We describe below two such weaknesses along with recommendations on ways to overcome them.

- Differentiation power

DEA's differentiation power increases as the ratio between the number of alternatives and the number of MOEs increases. When this ratio is close to 1 (i.e., the number of alternatives is approximately the same as the number of MOEs), most alternatives are likely to be evaluated as fully efficient. In such scenarios, it is enough, for example, that the value of one of its numerator MOEs is larger than the corresponding values of all other alternatives to be evaluated as efficient. This phenomenon was discussed in Section 7. In the context of R&S evaluation, this scenario is quite likely as we have 7 MOEs and the typical number of alternatives in an AoA study is less than 12. To overcome this

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

difficulty, we recommend two possible remedies that have been implemented in similar situations elsewhere:

- Weight restrictions. The objective function of the model we presented above seeks to maximize the efficiency score for the alternative it evaluates. Thus, adding constraints to this model will cause a decrease in the efficiency score. The constraints should reflect qualitative assessment by the decision makers involved in the process. For example, putting some priorities on the weights (Roll and Golany, 1993).
- Adding alternatives. During the development of a certain alternative, there are several design and engineering options that could be explored – each generating another alternative. Also, one could add "utopian" alternatives, generated artificially based on past experience, and use them as benchmarks.
- Uniqueness  
Certain alternatives may be affiliated with some attribute that doesn't exist in other alternatives and hence it makes them unique. If we treat an alternative as unique, it is by definition fully efficient as we can't compare it to any other alternative. Suppose we evaluate the procurement of platforms that can transfer combat personnel from sea to shore and backwards and that all but one of the alternatives are different kinds of vessels and only one alternative is airborne. A Contractor may claim that his alternative is unique to ensure it is ranked as efficient, absent competitors. To avoid such claims, one should ensure that the MOEs are as general as possible but yet relevant and useful. The way we presented the MOEs in this report is indeed quite general and we believe that in most cases it can be used as is.

Future research should be focused on implementing the methodology and analyzing its benefits and possible drawbacks.



## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

### References

- Allen, I. E., & Seaman, C. A. (2007). Likert Scales and Data Analyses. *Quality Progress*, 64-65.
- Atwater, B., and Uzdinski, J. (2014). Wholistic Sustainment Maturity: The Extension of System Readiness Methodology across all Phases of the Lifecycle of a Complex System. *Procedia Computer Science*, 28, 601-609.
- Boehmke B.C., R.A. Jackson, A.W. Johnson, E.D. White, J.D. Weir and M.A. Gallagher (2017). Measuring US Air Force Installation Support Activities via Data Envelopment Analysis, *Military Operations Research*, Vol. 22, No. 1, pp. 39-58.
- Bowlin, W.F. (1996), Benchmarking and Efficient Program Delivery for the Department of Defense's Business-Like Activities, *Military Operations Research*, Vol. 2, No. 1 (1996), pp. 19-30
- Brockett, P.L., B. Golany, J.J. Rousseau, D.A. Thomas and L. Zhou (1997), "Forecasting and Allocation of US Army Recruiting Resources," *Military Operations Research*, Vol. 3, No. 3, 13-29.
- Charnes, A., C.T. Clark, W.W. Cooper and B. Golany (1984), "A Developmental Study of Data Envelopment Analysis in Measuring the Efficiency of Maintenance Units in the US Air Force," *Annals of Operations Research*, Vol. 2, pp. 95-112.
- Cook, W., M. Kress and L.M. Seiford (1993), "On the Use of Ordinal Data in Data Envelopment Analysis", *Journal of the Operational Research Society*, Vol. 44, No. 2, pp 133-140.
- DoD. (2019). *DOD Dictionary of Military and Associated Terms*.  
<https://www.jcs.mil/Portals/36/Documents/Doctrine/pubs/dictionary.pdf>.
- GAO. (1999). Better Management of Technology Development Can Improve Weapon System. In U. S. Office, *The Defense Acquisition System*. GAO/NSIAD-99-162.
- HAF. (2016). *Analysis of Alternatives (AoA) Handbook*. Kirtland AFB, NM: Headquarters Air Force HAF/A5R-OAS, Office of Aerospace Studies.
- Hong Kyu Han and So Young Sohn, DEA Application to Grouping Military Airbases. *Military Operations Research*, Vol. 16, No. 2 (2011), pp. 31-40.
- Kress, M., and Morgan, B. (2018). *A Robust Framework for Analyzing Acquisition Alternatives*. Monterey, CA: Naval Postgraduate School.
- Mislick, G. a. (2015). *Cost Estimation: Methods and Tools*. Wiley.
- Mislick, G. a. (2015). *Cost Estimation: Methods and Tools*. New York: Wiley.
- Moore, S. C., Stockfish, J. A., Goldberg, M. S., Holroyd, S. M., and Hilderbrandt, G. G. (1991). *Measuring Military Readiness and Sustainability*. Santa Monica, CA: RAND.

## NPS NRP Final Report

Measuring Readiness and Sustainment within Analysis of Alternatives in Military Systems Acquisition

Report Date: 12/31/19 Project Number (IREF ID): NPS-19-N176-A

Naval Postgraduate School Graduate School of Operational and Information Sciences  
Operations Research Department

Rich, M., Cohen, I. K., and Pyles, R. A. (1987). *Recent Progress in Assessing the Readiness and Sustainability of Combat Forces*. Santa Monica, CA: RAND.

Roll, Y. and B. Golany (1993), *Alternate Methods for Treating Factor Weights in DEA*, *OMEGA*, Vol. 21, No. 1, pp. 99-109.

Sausser, B. J., Ramirez-Marquez, J. E., Davanandham, H., DiMarzio, D. (2008). A system maturity index for the systems Engineering Life Cycle. *Int. J. Industrial and Systems Engineering*, V. 3, No. 6, pp 673-691 .

Sutton, W. and Dimitrov S. (2013) The U.S. Navy explores detailing cost reduction via Data Envelopment Analysis, *European Journal of Operational Research* Vol. 227(1), pp. 166–173.

### Acronyms

Analysis of Alternatives	AoA
Department of Defense	DoD
data envelopment analysis	DEA
multi-criteria decision analysis	MCDA
measure of effectiveness	MOE
research and development	R&D
supply chain	SC